
EWM-W162M2

802.11 ac/a/b/g/n + Bluetooth 4.2 M.2 2230 (E-Key) Card



Features

- IEEE 802.11 ac/a/b/g/n + Bluetooth 4.2 HS standard
- 64/128 bit WEP, 802.1x, TKIP and AES
- Operating temperature: -30 to 85 °C

ROHS COFFICE CE FCC

Specifications

| Main Chipset | Marvell 88W8897P |
|------------------------|---|
| Tx/Rx | 2Tx/ 2Rx (2 IPEX MHF4 connector Receptacle) |
| Standard Conformance | 802.11 ac/a/b/g/n |
| Form Factor | M.2 2230, E-key card |
| Interface | WIFI: PCI-E, Bluetooth: USB |
| Operation Voltage | DC 3.0 ~ 3.3V |
| Power Consumption | Continue TX: 345mA (Avg.), (BT is off) |
| Security | 64/128 bit WEP |
| O.S Supported | Linux (Kernel v4.10.12, the driver is available in kernel source tree.) |
| Temperature Ranges | Operation: -30 to 85 °C |
| Dimensions (L x W x H) | 22 x 30 x 2.2 mm |

Ordering Information

| Part No. | Product Description |
|---------------|---|
| EWM-W162M201E | Advantech Brand, 802.11 ac/a/b/g/n, Marvell 88W8897P, 2T2R, w/ BT4.2 (Low energy operation) |

Suggested Antenna and Cable

| Part No. | Specifications |
|---------------|--|
| 1750002842 | WiFi 2.4 GHz and 5 GHz dipole Antenna |
| 1750007965-01 | WiFi Coaxial Cable, SMA (M) to MHF4, 30 mm |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for WiFi Modules - 802.11 category:

Click to view products by Advantech manufacturer:

Other Similar products are found below:

KBPC10/15/2506WP WIFI-RT5392-SB-R10 SX-PCEAN2C-SP 849WM520100E WIFI-AT2350 7265.NGWG.SW HDG204-DN-3 FXX-3061-MIX EMIO-1533-00A2 7265.NGWWB.W PPC-WL-KIT02-R11 RC-CC2640-B HLK-7688A WH-NB73-BA NF-02-PA LSD4BT-E92ASTD001 EAR00364 3168.NGWG MY-WF003U AX210.NGWG.NV ESP-15F32Mbit ESP32-S32Mb TG-01M ESP-13 ESP-01F-2M ESP-01E-2M ESP-20 ESP32-SL ESP-12K-PSRAM ESP-12K-PSRAM-IPEX ESP-12H BW18 BW12-16Mb BW14 BW15 BW16 TG-12F SIM7600CE-L1S CB3S(tjrl) CB3S(hvk9) CB3S(qh6) WB2S(csyd) WB3S(ppty) WB3S(h238) WB3S(uvmz) 1005869 1012 QCA4004X-BL3B 32-2006-BU WT51822-S4AT