# **HPC-7280**

#### **2U Rackmount Chassis for EATX Server Board with 8 Hot-swap Drive Bays, Redundant PSU, and 3 Expansion Slots**



#### **Features**

- 2U rackmount chassis supports ATX/CEB/EATX motherboard
- Eight hot swap SAS/SATA drive bays
- Hot swap fan module design facilitates maintenance
- 800 W (1+1) redundant power supply
- Lockable front bezel prevents unauthorized access

Note: ASMB-RF3X8-21A1E riser card is built-in.


## **C**€ FCC

## **Specifications**

| Form Factor Support      |   | 2U chassis support for max. motherboard size  | - 12" x 13" FATX  |
|--------------------------|---|---|---|
| Expansion Slots          |   | 64bit PCI-X slot x 2 (When 1 slot is used, max. 133MHz is supported; when 2 slots are used, max. 100MHz<br>is supported)<br>PCIe x 8 slot x 1<br>* Note: Expansion slots are supported by built-in ASMB-RF3X8-21A1E riser card. |   |
| Drive Bay                | Slim ODD Bay<br>5.25" (front-accessible)<br>3.5" (hot-swappable)<br>3.5" (internal)<br>2.5" (front-accessible)<br>2.5" (internal) | 1 (ODD should be purchased separately)<br>-<br>8 (Lockable)<br>-<br>-<br>2  |   |
| Cooling                  | Chassis Fan<br>Air Filter   | 3 (8 cm / 90.04 CFM)  |   |
| System Monitoring        |   | Chassis intrusion switch  |   |
| Front I/O Interface      | USB<br>PS/2   | -   |   |
| Miscellaneous            | LED Indicators<br>Rear Panel  | Power, HDD activity, LAN<br>-   |   |
| Environment              | Temperature<br>Humidity<br>Vibration (5~500 Hz)<br>Shock  | Operating<br>0 ~ 40° C (32 ~ 104° F)<br>10 ~ 85% @ 40° C non-condensing<br>1 Grms<br>10 G<br>(with 11 ms duration, half sine wave)  | Non-Operating<br>-40 ~ 70° C (-40 ~ 158° F)<br>10 ~ 95% @ 40° C, non-condensing<br>2 Grms<br>30 G |
| Physical Characteristics | Dimensions (W x H x D)<br>Weight  | 482.6 x 88 x 700 mm (2U)<br>28 kg   |   |


### **Front View**

All product specifications are subject to change without notice



Last updated : 6-Oct-2015

#### HPC-7280



## **Ordering Information**

| Part Number    | Power Supply                     |
|----------------|----------------------------------|
| HPC-7280-R8A1E | 1+1 800 W Redundant Power Supply |

## **Packing List**

| Description   | Quantity |
|---|----------|
| 800W Redundant Power Supply Module (Pre-installed)  | x 2      |
| Hot-swap 3.5" HDD Trays (Pre-installed)   | x 8      |
| ASMB-RF3X8 Riser Card (Pre-installed)   | х1       |
| System Accessory (SATA Cable for Slim ODD x 1, Mini-SAS to 4 SATAs Cable x 2, Drive Bay Key x 2, Bezel Key x 2) | x 1      |
| Startup Manual  | x 1      |

## **Optional Accessories**

| Part Number   | Description                                  |  |  |
|---|--|--|--|
| 19Z0000215N000  | HPC-7280 Chassis Rail Kit                    |  |  |
| 96CB-SAS-SAS-0.8  | Mini-SAS cable kit for add-on SAS RAID card* |  |  |
| *Note: When using add-on RAID card with mini-SAS connector(s), purchasing |  |  |  |

96CB-SAS-SAS-0.8 cable is a MUST, single port RAID card needs 1 piece, dual port needs 2 pieces

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Modules Accessories category:

Click to view products by Advantech manufacturer:

Other Similar products are found below :

7010-0001 AX98219 A1UL8RISER F1UJPMICRISER FHW1U16RISER 20-101-0440 2828736-1 MBCDROM AX61221TM VM-105 EA CARREDIPTFT02 RK-210E-B E226171106 88606200030E SI-HDMI-EDID-EM MIC-75M13-00A1E FPM-1000T-SMKE AMK-R004E 96FMCF-ST2ADAPTER1 AHWKPTP12GBGB AXXSTCPUCAR FPK-07-R10 Mini Din 6P to 6P HARNESS FPF1320 POWER MULTIPLEXER CARRIER 881261510A0E AXXP3SWX08080 conga-B7XD/CSP-Cu-B 881281021A0E HFT for mounting KIT FN928X\_FN929X BB-MH112-1A 15100600 9-5000-1116 BKCMCR1ABB 70763 98R3612003E 881261910A0E 106897 48222R BREAK OUT BOARD 20 4D ARDUINO ADAPTOR SHIELD II 20926110901 PYCASE GREEN PYCASE BLUE FP15072\_ZORYA-SC-HEKLA 20952000004 20953000007 DP-DVI-R10 575-BBIS RACK-220GW/A130B 492-BBKM