

PSD-A60W Series

60 Watts Compact Size DIN-Rail Power Supply



Features

- Extra slim design with 60 watts output
- High power density: 3.41 watts per inch³
- Input range 85 ~ 264 V_{AC}/ 110 ~ 375 V_{DC}
- Power boost with 150% peak load
- Full protection with auto recovery function
- Full load output up to 60°C
- Adjustable output




Specifications

Output	Model	PSD-A60W12	PSD-A60W24	PSD-A60W48
	Output Voltage	12V _{DC}	24V _{DC}	48V _{DC}
	Output Voltage Adjustment Range	12V _{DC} to 14V _{DC}	22V _{DC} to 27V _{DC}	46V _{DC} to 50V _{DC}
	Rated Current	5.00A	2.50A	1.25A
	Peak Current (Max Output Current, 3 seconds)	7.50A	3.75A	1.87A
	Efficiency (typical)	88%	89%	89%
	Output Power	60 Watts		
	Accuracy (%)	±1%		
	Max. Ripple & Noise (mVp-p)	120 mVp-p		
	Line Regulation	±1%		
	Load Regulation	±1%		
	Hold-up Time	115V/60Hz: 16ms Minimum; 230V/50Hz: 20ms. Minimum		
	Input	Input Voltage	85 ~ 264 V _{AC} ; 110 ~ 375 V _{DC}	
Input Frequency		47 ~ 63 Hz		
Input Current		< 1.40 A @ 115V _{AC} , < 0.80 A @ 230V _{AC}		
Max. Inrush Current		60A @ 230V _{AC} , cold start @ 25°C and full load		
Leakage Current		< 1 mA when power supply is connected to 240V _{AC} /60Hz		
Protection	OVP (Over Voltage Protection)	16V max	35V max	55V max
	OCP (Output Peak Current Protection, 3~5 sec.)	7.50A	3.75A	1.87A
	SCP (Short Circuit Protection)	< 0.1 ohm		
	OTP (Over Temperature Protection)	100 ± 10%		
Environment	Operating Temperature	-25 ~ 70°C		
	Power Derating	Full load to 60°C; output power derated 2.5% per °C		
	Operating Humidity	95% RH, non-condensing		
	Storage Temperature	-40 ~ 85 °C		
	Operating Altitude	5,000 m		
	Shock Test (Non-Operating)	IEC60068-2-27, 30G (300m/S ²) for a duration of 18ms		
Insulation	Vibration Test (Non-Operating)	IEC60068-2-6, 10Hz to 150Hz @ 50m/S ² (5G peak); 90 min per axis for all X, Y, Z direction		
	Dielectric Strength	AC input - DC output/FG: 1500 V _{AC} for 1 minute		
Safety	Insulation Resistance	AC input - DC output/FG; DC output - FG: 50MΩ min.		
	CB/UL/TUV/CCC	IEC60950-1/GB4943.1		
Mechanical	Case Cover / Chassis	Metal chassis		
	Input Connector	3 Pins (300V/ 20A)		
	Output Connector	4 Pins (300V/ 20A)		
	Terminal Type	Screw terminal (screw torque: 5.5 lb. per inch)		
	Wire	AWG22-16		
	Mounting Rail	Standard TS35 DIN-Rail in accordance with EN60715		
	Cooling System	Conventional		
	Dimensions (W x H x D)	32 x 100 x 90.2 mm / 1.26 x 3.94 x 3.54 inch		
	Weight	315±5 g / 0.671 lb.		
Reliability and Warranty	MTBF (hours)	500,000 (based on SR-332) Issue 2		
	Warranty	3 Years		


Dimensions

Unit: mm [inch]



Derating Curve

- PSD-A60W series full load to 60°C, with 2.5% derating per °C



Ordering Information

Part Number	Description
PSD-A60W12	12 V _{DC} / 60 Watts DIN-Rail Power Supply
PSD-A60W24	24 V _{DC} / 60 Watts DIN-Rail Power Supply
PSD-A60W48	48 V _{DC} / 60 Watts DIN-Rail Power Supply

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [DIN Rail Power Supplies](#) category:

Click to view products by [Advantech](#) manufacturer:

Other Similar products are found below :

[PS-S6024](#) [DVP01PU-S](#) [DVP06AD-S](#) [DVP06XA-S](#) [DVDPNET-SL](#) [DVPDT01-S](#) [DVPPS01](#) [PS-6012](#) [PS9Z-5R1G](#) [PS-C24024](#)
[DVP08ST11N](#) [DVPACAB530](#) [DVPCOPM-SL](#) [DVPEN01-SL](#) [DVPPF01-S](#) [ADNB008-48-1PM-C](#) [ADNB017-24-1PM-C](#) [ADNB034-12-1PM-C](#) [SS14011524](#) [PS-UPS40](#) [PSC-6024](#) [PSD-A60W12](#) [96PS-A120WDIN](#) [PSD-A60W48](#) [PSD-A40W12](#) [PSD-A40W24](#) [SMP21-L20-DC24V-5A](#) [PSD-A40W48](#) [S8T-DCBU-02](#) [PS-S4024](#) [NTPS-24-1.3](#) [ZI-20](#) [PST-96024](#) [S82YVSC4P](#) [PS-S4005](#) [PS-10024](#) [PS-S10024](#) [PS-C12024](#) [PSP-480S24](#) [PS-C48024](#) [PSC-2024](#) [PSC-4012](#) [PSC-4048](#) [PSC-9615](#) [PSC-15124](#) [PSC-15148](#) [PSC-24148](#) [PSC-48148](#) [TRIO-PS-2G/1AC/12DC/5/C2LP](#) [QUINT4-PS/1AC/12DC/15](#)