


RSB-4680

Rockchip ARM Cortex-A17 RK3288 3.5" SBC



Features

- Rockchip ARM Cortex-A17 RK3288 Quad Core 1.6GHz
- Onboard 2GB DDR3L memory and 8GB eMMC
- HDMI 3840x2160 at 60Hz, VGA 1920x1200 at 60Hz, Dual Channel 18/24/30 bit LVDS
- Support 4K H.264/H.265 Video decoder
- 6 UART, 6 USB2.0, 1 GbE, 8 GPIO, 1 SPI
- M.2 for WIFI/BT support, mini-PCIe for 3G/4G support
- Support Linux and Android




Introduction

RSB-4680 is a RISC 3.5" single board computer (SBC) powered by a high-performance Rockchip ARM Cortex-A17 RK3288 processor which supports 4K display from HDMI. It offers rich interfaces such as 6 USB2.0, 6 UART, 1 VGA, 1 LVDS, 1 GbE and 8 GPIO. RSB-4680 also features Mini-PCIe, M.2, and SIM card slots for integrating Wi-Fi, Bluetooth, and 3G/4G modules. It is an ideal solution for Kiosk, POS, and Vending machine application.

Specifications

Form Factor		3.5" SBC
Processor	CPU	Rockchip ARM Cortex-A17 RK3288 Quad Core up to 1.6GHz
	Technology	DDR3L 1333MHz
	Capacity	On-board DDR3L 2GB
Memory	Flash	8GB of eMMC NAND Flash for OS and Advantech's boot loader 4MB of SPI NOR Flash
	LVDS	1 x 18/24/30-bit LVDS with 1920 x 1080 for dual channels at 60Hz
	HDMI	1 HDMI, up to 3840 x 2160 at 60 Hz
Graphics	VGA	1 VGA, up to 1920 x 1200 at 60Hz
	Graphics Engine	OpenGL ES 1.1/2.0/3.0, OpenCL 1.1, DirectX 11
	H/W Video Codec	Decoder: MPEG-1, MPEG-2, MPEG-4, H.263, H.264, AVS, VC-1, VP8, MVC, HEVC/H.265 decoder, 4k@60FPS Encoder: H.264 (BP@level4.0, MP, HP@level4.0), MVC and VP8
	Chipset	TI DP83867
	Speed	1 x 10/100/1000 Mbps
Ethernet		Yes
WatchDog Timer		Yes
I/O	SATA	-
	SATA Power	-
	USB	1 x USB OTG, 2 x USB Type A, and 3 x USB pin headers
	Audio	1 x Line out, 1 x Mic-in, 1 x Speaker out via a pin header
	SPDIF	-
	SDIO	-
	Serial Port	1 x 4-wire RS-232/485, DB9 1 x 2-wire RS-232/Debug port, pin header selected by jumper 4 x 4-wire RS-232, pin header
	SPI	1
	CAN	-
	GPIO	8 x GPIO via pin header (3.3V TTL level)
	I ² C	1
	System Bus	-
	Touch	-
	MIPI CSI	-
	Button	1 x Reset button, 1 x Power button via a pin header
Expansion	Mini PCIe	1 x Mini PCIe slot
	SD Socket	1 x Micro SD slot
	SIM Slot	1 x SIM slot
	M.2 Socket	1 x M.2 2230 Key E slot
	Power Supply Voltage	12 V
Power	Power Type	DC-in
	Power Consumption	-
	Operating Temperature	0 - 60 °C
Environment	Operating Humidity	5 - 95% relative humidity, non-condensing
	Dimensions (W x D)	146 x 102 mm
Mechanical		Linux and Android
Operation System		CE/FCC Class B
Certifications		

Block Diagram



Ordering Information

Part Number	CPU	Memory	Flash	HDMI	VGA	LVDS	LAN	Serial Port	SATA	USB	System Bus	SD	CAN Bus	Operating Temperature
RSB-4680CQ-XNA1E	Rockchip RK3288 Quad core, 1.6GHz	2 GB	8 GB	1	1	1	1	1 x 4-wire RS-232/485 1 x 2-wire RS-232/Debug port 4 x 4-wire RS-232	-	5 x USB Host 1 x USB OTG	-	1	-	0 - 60 °C

Packing List


Part Number	Description
RSB-4680	RSB-4680 3.5" SBC

Optional Accessories


Part Number	Description
96PSA-A60W12W6	ADP A/D 100-240V 60W 12V C14 LOCKABLE DC PLUG
1702002605	Power Cord 3P EU 10A 250V 183cm
1702031801	Power Cord 3P UK 10A 250V 183cm
1702002600	Power Cord UL 3P 10A 125V 183cm
1700009652	Power Cord CCC 3P 10A 250V 187cm
1700021565-01	Debug cable
EWM-W167M201E	WiFi BT4.0 Module RTL8723BS SDIO
1750007965-01	Antenna Cable R/P SMA (M) to MHF4, 300mm
1750008671-01	Dipole Ant.SMA/M-R 2.4/5G 2.5/4dBi BLK 109mm
968AD00081*	Quectel EC20CEFA Mini-PCIe 4G module for China
1750006264	Antenna cable SMA(F)/MHF 15cm
1750007990-01	Antenna 4G/LTE full band L=11 cm 50 Ohm
SQF-MSDM1-8G-21C	SQF MICRO SD C10 MLC 8G (-25 ~ 85 °C)
IDK-1107WR-40WVA1E	7" LED PANEL 2.5A/3A 250V 1.83cm400N with 4WR touch, 800 x 480 (G)
1700028571-01	LVDS cable for IDK-1107WR
1700028572-01	LCD backlight cable for IDK-1107WR

* Please contact us to get suitable cellular module for your region.

Dimensions



External I/O



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Single Board Computers](#) category:

Click to view products by [Advantech](#) manufacturer:

Other Similar products are found below :

[MANO882VPGGA-H81](#) [SSD3200W-S-SLC-INN 20-101-0738](#) [MVME61006E-2173R](#) [SHB230DGGGA-RC](#) [IMB210VGGA](#) [IB915F-3955](#)
[MI958F-16C](#) [S2600WFT](#) [S2600STB](#) [BBS2600BPS](#) [BLKNUC7I3DNHNC1978015](#) [DEV-17745](#) [BEAGLEBOARD POCKET](#) [MICROSOM](#)
[I2 + WIFI/BT](#) [HUMMINGBOARD-I2EX](#) [BASE + WIFI/BT](#) [HUMMINGBOARD-I4 PRO + WIFI/BT](#) [VAB-600-B](#) [RT5350F-OLINUXINO-](#)
[EVB](#) [MITX-440-DVI-2E](#) [ATCA-7365-D-24GB](#) [NITX-315-DEVKIT](#) [A13-SOM-512](#) [NITX-315](#) [BANANA PI BPI-M1+](#) [A13-SOM-WIFI-](#)
[4GB](#) [AM3359-SOM-EVB-IND](#) [UPS-APLC2-A10-0432](#) [DFR0419](#) [UPS-APLP4-A10-0864](#) [UPS-APLP4-A10-0432](#) [UPS-APLP4-A10-08128](#)
[MI977F-Q27](#) [BBBLUE](#) [IB811F-I30](#) [DFR0470-ENT](#) [Nit6Q_i](#) [M2M \(TELIT\)](#) [RELAY](#) [PROFESSIONAL](#) [GCS22.2.080.2.2.I](#)
[GCS22.8.100.4.2.I](#) [GLS11.2.053.2.2.E](#) [A20-OLINUXINO-LIME-E16GS16M](#) [A20-OLINUXINO-LIME-S16M](#) [A20-OLINUXINO-LIME2-](#)
[E16GS16M](#) [A20-OLINUXINO-MICRO-E16GS16M](#) [A20-OLINUXINO-MICRO-S16M](#) [BANANA PI BPI-W2](#) [T2-OLINUXINO-LIME2-](#)
[S16M-IND](#)