

SQF-PDM

PATA Disk Module

SQF-P25

2.5" PATA SSD



Features

- Capacity 1GB ~ 16GB
- Supports SLC (single level cell) NAND Flash Memory
- Supports for PIO Mode 4 / Multi Word DMA Mode 2 / Ultra DMA Mode 4
- GUI Management Tool & Software API Package

Specifications

Capacity	1 to 16GB
Flash Type	SLC
Compatibility	ATA command set
Connector Type	40-pin 2.54 mm pitch/44-pin 2.0 mm pitch Receptacle Housing Connector
Voltage	3.3 V / 5.0 V
Data Transfer Mode	PIO Mode 4 MWDMA Mode 2 UDMA Mode 4
Sustained R/W Performance (*)	40/29 MB/sec
Operation Temperature	Commercial Grade : 0 to +70° C Extended Grade : -40 to +85° C
Host interface	8/16 bit access
ECC (BCH)	Correct up to 6/12 random bits/sector
Endurance	> 2,000,000 program/erase cycles
Shock Resistance	1,500 G (0.5 msec)
Vibration Resistance	20 G, Peak / 80 ~ 2000 Hz

(*)The values are for reference only; they may change according to the flash memory used.

Ordering Information

Part No.	Product Description
SQF-PDMS2-XG-HACE	Advantech SQFlash PDM 44-pin Hor. 2/4/8/16 GB, (0 ~ 70° C)
SQF-PDMS2-XG-HAEE	Advantech SQFlash PDM 44-pin Hor. 2/4/8/16 GB, (-40 ~ 85° C)
SQF-PDMS2-XG-VACE	Advantech SQFlash PDM 44-pin Vert. 2/4/8/16 GB, (0 ~ 70° C)
SQF-PDMS2-XG-VAEE	Advantech SQFlash PDM 44-pin Vert. 2/4/8/16 GB, (-40 ~ 85° C)
SQF-PDMS2-XG-HBCE	Advantech SQFlash PDM 40-pin Hor. Top 2/4/8/16 GB, (0 ~ 70° C)
SQF-PDMS2-XG-HBEE	Advantech SQFlash PDM 40-pin Hor. Top 2/4/8/16 GB, (-40 ~ 85° C)
SQF-PDMS2-XG-HCCE	Advantech SQFlash PDM 40-pin Hor. Bottom 2/4/8/16 GB, (0 ~ 70° C)
SQF-PDMS2-XG-HCEE	Advantech SQFlash PDM 40-pin Hor. Bottom 2/4/8/16 GB, (-40 ~ 85° C)
SQF-PDMS2-XG-VBCE	Advantech SQFlash PDM 40-pin Vert. 2/4/8/16 GB, (0 ~ 70° C)
SQF-PDMS2-XG-VBEE	Advantech SQFlash PDM 40-pin Vert. 2/4/8/16 GB, (-40 ~ 85° C)
SQF-PDMS1-1G-44CE	Advantech SQFlash PDM 44-pin Vert. 1 GB, Housing, (0 ~ 70° C)
SQF-PDMS2-XG-44CE	Advantech SQFlash PDM 44-pin Vert. 2/4/8/16 GB, Housing, (0 ~ 70° C)
SQF-PDMS1-1G-44EE	Advantech SQFlash PDM 44-pin Vert. 1 GB, Housing, (-40 ~ 85° C)
SQF-PDMS2-XG-44EE	Advantech SQFlash PDM 44-pin Vert. 2/4/8/16 GB, Housing, (-40 ~ 85° C)

Note: X stands for different capacities



Features

- Capacity SLC 4 GB ~ 256 GB / MLC 16 GB ~ 512 GB
- Supports SLC (single level cell) and MLC (multi level cell) NAND Flash memory
- Supports PIO mode 4 / multi word DMA mode 2 / ultra DMA mode 4
- GUI Management Tool & Software API Package

Specifications

Capacity	SLC: 4 to 256GB MLC: 16 to 512GB
Compatibility	ATA command set
Voltage	3.3 V / 5.0 V
Data Transfer Mode	PIO Mode 4 MWDMA Mode 2 UDMA Mode 4
Sustained R/W Performance (*)	SLC: 65/55 MB/sec MLC: 60/25 MB/sec
Operating Temperature	Commercial Grade : 0 to +70° C Industrial Grade: -40 to +85° C
Host Interface	8/16 bit access
ECC (BCH)	Correct up to 68 bit per 1K Byte
Endurance	> 2,000,000 program/erase cycles
Shock Resistance	2,500 G (0.5 msec)
Vibration Resistance	20 G, Peak / 80 ~ 2000 Hz

(*)The values are for reference only; they may change according to the flash memory used.

Ordering Information

Part No.	Product Description
SQF-P25S4-XG-P9C	Advantech SQFlash 2.5" PATA SSD SLC, DMA, 4/8/16/32/64/128/256 GB (0 ~ 70° C)
SQF-P25S4-XG-P9E	Advantech SQFlash 2.5" PATA SSD SLC, DMA, 4/8/16/32/64/128/256 GB (-40 ~ 85° C)
SQF-P25M4-XG-P9C	Advantech SQFlash 2.5" PATA SSD MLC, DMA, 16/32/64/128/256/512 GB (0 ~ 70° C)
SQF-P25M4-XG-P9E	Advantech SQFlash 2.5" PATA SSD MLC, DMA, 16/32/64/128/256/512 GB (-40 ~ 85° C)

Note: X stands for different capacities

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Solid State Drives - SSD category](#):

Click to view products by [Advantech manufacturer](#):

Other Similar products are found below :

[ATCA7360-MMOD-SATA2](#) [ASD25-MLC064G-CT-160-1](#) [SQF-SM4V2-256G-SBC](#) [SD7SN6S-128G-1122](#) [MTFDDAA120MBB-2AE1ZABYY](#) [SDSDQAD-128G](#) [SM668GXB-ACS O1118](#) [SDINADF4-64G-H](#) [SQF-S25V4-240G-SCC](#) [SQF-SDMM2-256G-S9E](#) [SFSA016GQ1BJ8TO-I-DT-226-STD](#) [MTFDDAK060MBD-1AH12ITYY](#) [VSF202PC016G-100](#) [AF512GSMEL-VABIP](#) [SSDPEKKA020T801](#) [MTFDDAK064MBD-1AH12ITYY](#) [EP-SSMSF128AACS](#) [APS297F064G-4BTM1GWF](#) [HBRPEKNX0202A01](#) [SSDPE21D015TAX1](#) [SSDPED1D015TAX1](#) [SSDPEKKF020T8X1](#) [SSDPEKKR256G7XN](#) [SSDPEKKW020T8X1](#) [SSDPEKKW512G801](#) [SSDPEKNW020T801](#) [SSDPEKNW020T9X1](#) [SSDPEL1D380GAX1](#) [SM2280S3G2/120G](#) [MTFDDAK1T9QDE-2AV1ZABYY](#) [MTFDDAK3T8QDE-2AV1ZABYY](#) [MTFDDAT128MBD-1AK12ITYY](#) [MTFDDAV256TDL-1AW12ABYY](#) [MTFDDAK2T0TDL-1AW1ZABYY](#) [MTFDDAK1T0TDL-1AW12ABYY](#) [MTFDDAV512TDL-1AW1ZABYY](#) [MTFDDAV256TDL-1AW1ZABYY](#) [MTFDHAL11TATCW-1AR1ZABYY](#) [MTFDHAL12T8TDR-1AT1ZABYY](#) [MTFDHAL1T6TCU-1AR1ZABYY](#) [MTFDHAL1T9TCT-1AR1ZABYY](#) [MTFDHAL3T8TCT-1AR1ZABYY](#) [MTFDHAL3T8TDP-1AT1ZABYY](#) [MTFDHAL6T4TCU-1AR1ZABYY](#) [MTFDHAL6T4TDR-1AT1ZABYY](#) [MTFDHAL7T6TCT-1AR1ZABYY](#) [MTFDHAL7T6TDP-1AT1ZABYY](#) [MTFDHAL8TATCW-1AR1ZABYY](#) [MTFDHBA2T0QFD-1AX1AABYY](#) [MTFDHBA512TCK-1AS15ABYY](#)