# **SQF-SM8 830** SATA III (6.0Gb) M.2 2280 SSD

# **SQF-S25 910S** SATA III (6.0Gb) 2.5" SSD



#### Features

- NGFF M.2 2280 SSD Module
- Compliant with SATA III and SATA v3.2 standard
- Supports 120 bit ECC correct per 2K Byte data
- Quad core processor with stable throughput
- Preserved pin for Voltage Stabilizer support
- GUI management tool & software API package
- GPIO preserved for security function control

### **Specifications**

Connector Type	NGFF B + M key
Flash type	SLC / Ultra MLC / MLC
Capacity	SLC: 64 to 128 GB Ultra MLC: 64 to 512 GB MLC: 64 GB to 1TB
Transfer Mode	SATA III (6.0 Gbps)
Max. Power Consumption	2A
Sustained R/W Performance (*)	Up to 540/520 MB/sec
Operating Temperature	Commercial grade: 0 to +70° C
Shock Resistance	1,500 G, peak / 0.5 ms
Vibration Resistance	20 G, peak / 80 ~ 2000 Hz
Dimensions (mm)	80.8 x 22.0 x 3.8

(\*) These values are for reference only; they may change according to the flash memory used.

### **Ordering Information**

PN	Description
SQF-SM8S8-xG-SAC	SQFlash 830 series M.2 2280 SATA SSD 64/128 GB SLC (0 ~ 70° C)
SQF-SM8U8-xG-SAC	SQFlash 830 series M.2 2280 SATA SSD 64/128/256/512 GB Ultra MLC (0 ~ 70° C)
SQF-SM8M8-xx-SAC	SQFlash 830 series M.2 2280 SATA SSD 64/128/256/512 GB / 1TB MLC (0 ~ 70° C)

Note: X stands for different capacities



#### **Features**

- 2.5" SATA SSD
- Compliant with SATA III and SATA v3.2 standard
- Supports 120 bit ECC correct per 2K Byte data
- Quad core processor with stable throughput
- Support Voltage Stabilizer
- GUI management tool & software API package
- GPIO preserved for security function control

#### **Specifications**

Connector Tune	Ctandard 7, 1E nin CATA connector
Connector Type	Standard 7+15-pin SATA connector
Flash type	SLC / Ultra MLC / MLC
Capacity	SLC: 50 to 400 GB Ultra MLC: 50 to 800 GB MLC: 100 to 1600 GB
Transfer Mode	SATA III (6.0 Gbps)
Max. Power Consumption	2A
Sustained R/W Performance (*)	Up to 540/520 MB/sec
Operating Temperature	Commercial grade: 0 to +70° C
Shock Resistance	1,500 G, peak / 0.5 ms
Vibration Resistance	20 G, peak / 80 ~ 2000 Hz
Dimensions (mm)	100.00 x 69.85 x 7

(\*) These values are for reference only; they may change according to the flash memory used.

### **Ordering Information**

	PN	Description
	SQF-S25S8-xG-VAC	SQFlash 910S series 2.5" SATA SSD 50/100/200/400 GB SLC (0 $\sim$ 70 $^{\circ}$ C)
	SQF-S25U8-xG-VAC	SQFlash 910S series 2.5" SATA SSD 50/100/200/400/800 GB Ultra MLC (0 ~ 70° C)
	SQF-S25M8-xG-VAC	SQFlash 910S series 2.5" SATA SSD 50/100/200/400/800/1600 (1K6) GB MLC (0 ~ 70° C)
Note: V stands for different canasities		

Note: X stands for different capacities

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Solid State Drives - SSD category:

Click to view products by Advantech manufacturer:

Other Similar products are found below :

ATCA7360-MMOD-SATA2 ASD25-MLC064G-CT-160-1 SQF-SM4V2-256G-SBC SD7SN6S-128G-1122 MTFDDAA120MBB-2AE1ZABYY SDSDQAD-128G SM668GXB-ACS O1118 SDINADF4-64G-H SQF-S25V4-240G-SCC SQF-SDMM2-256G-S9E SFSA016GQ1BJ8TO-I-DT-226-STD MTFDDAK060MBD-1AH12ITYY VSF202PC016G-100 AF512GSMEL-VABIP SSDPEKKA020T801 MTFDDAK064MBD-1AH12ITYY EP-SSMSF128AACS APS297F064G-4BTM1GWF HBRPEKNX0202A01 SSDPE21D015TAX1 SSDPED1D015TAX1 SSDPEKKF020T8X1 SSDPEKKR256G7XN SSDPEKKW020T8X1 SSDPEKKW512G801 SSDPEKNW020T801 SSDPEKNW020T9X1 SSDPEL1D380GAX1 SM2280S3G2/120G MTFDDAK1T9QDE-2AV1ZABYY MTFDDAK3T8QDE-2AV1ZABYY MTFDDAT128MBD-1AK12ITYY MTFDDAV256TDL-1AW12ABYY MTFDDAK1T0TDL-1AW12ABYY MTFDDAV512TDL-1AW1ZABYY MTFDDAV256TDL-1AW1ZABYY MTFDHAL11TATCW-1AR1ZABYY MTFDHAL12T8TDR-1AT1ZABYY MTFDHAL1T6TCU-1AR1ZABYY MTFDHAL1T9TCT-1AR1ZABYY MTFDHAL3T8TCT-1AR1ZABYY MTFDHAL3T8TDP-1AT1ZABYY MTFDHAL6T4TCU-1AR1ZABYY MTFDHAL7T6TCT-1AR1ZABYY MTFDHAL3T8TDP-1AT1ZABYY MTFDHAL6T4TCU-1AR1ZABYY MTFDHAL7T6TCT-1AR1ZABYY MTFDHAL3T8TDP-1AT1ZABYY MTFDHAL6T4TCU-1AR1ZABYY MTFDHAL7T6TCT-1AR1ZABYY MTFDHAL512TCK-1AS1AABYY SDAPMUW-128G-1022