

# SQF-SMS 640

## SATA III (6.0Gb) mSATA

# SQF-SM8 640

## SATA III (6.0Gb) M.2 2280

NEW



RoHS COMPLIANT 2002/95/EC CE FCC



### Features

- MO-300 mSATA Module
- Compliant with SATA III and SATA v3.2 standard
- Support LDPC of ECC correct
- Shock resistance, anti-vibration and low power consumption
- GUI management tool & software API package

### Specifications

Connect Type	Mini PCIe 52pin connector with SATA pin-out
Flash type	Ultra MLC / MLC
Capacity	Ultra MLC: 8 to 512GB MLC: 16 to 512GB, 1TB
Transfer Mode	SATA III (6.0 Gbps)
Max. Power Consumption	Read: 520 mA, Write: 800 mA
Sustained R/W Performance (*)	Ultra MLC and MLC up to 560/495 MB/sec
Operating Temperature	Commercial grade: 0 to +70° C Industrial grade: -40 to +85° C
Shock Resistance	1,500 G, peak / 0.5 ms
Vibration Resistance	20 G, peak / 80 ~ 2000 Hz
Dimensions (mm)	50.8 x 30 x 4.2


(\*) These values are for reference only; they may change according to the flash memory used.

### Ordering Information

PN	Description
SQF-SMSM2-XXG-SBC	SQFlash 640 series mSATA MLC 16/32/64 GB, 2-CH (0 ~ 70° C)
SQF-SMSM2-XXG-SBE	SQFlash 640 series mSATA MLC 16/32/64 GB, 2-CH (-40 ~ 85° C)
SQF-SMSM4-XX-SBC	SQFlash 640 series mSATA MLC 128/256/512 GB, 1TB, 4-CH (0 ~ 70° C)
SQF-SMSM4-XX-SBE	SQFlash 640 series mSATA MLC 128/256/512 GB, 1TB, 4-CH (-40 ~ 85° C)
SQF-SMSU2-XXG-SBC	SQFlash 640 series mSATA Ultra MLC 8/16/32 GB, 2-CH (0 ~ 70° C)
SQF-SMSU2-XXG-SBE	SQFlash 640 series mSATA Ultra MLC 8/16/32 GB, 2-CH (-40 ~ 85° C)
SQF-SMSU4-XX-SBC	SQFlash 640 series mSATA Ultra MLC 64/128/256/512 GB, 4-CH (0 ~ 70° C)
SQF-SMSU4-XX-SBE	SQFlash 640 series mSATA Ultra MLC 64/128/256/512 GB, 4-CH (-40 ~ 85° C)

Note: X stands for different capacities

NEW



RoHS COMPLIANT 2002/95/EC CE FCC



### Features

- NGFF M.2 2280 SSD
- Interface: SATA III (6.0 Gbps)
- Support LDPC of ECC correct
- Shock resistance, anti-vibration and low power consumption
- GUI management tool & software API package
- Support hardware write protect

### Specifications

Connect Type	NGFF B+M key
Flash type	Ultra MLC / MLC
Capacity	Ultra MLC: 8 to 512GB MLC: 16 to 512GB, 1TB
Transfer Mode	SATA III (6.0 Gbps)
Max. Power Consumption	Read: 520 mA, Write: 800 mA
Sustained R/W Performance (*)	Ultra MLC and MLC up to 560/495 MB/sec
Operating Temperature	Commercial grade: 0 to +70° C Industrial grade: -40 to +85° C
Shock Resistance	1,500 G, peak / 0.5 ms
Vibration Resistance	20 G, peak / 80 ~ 2000 Hz
Dimensions (mm)	80.0 x 22.0 x 3.8

(\*) These values are for reference only; they may change according to the flash memory used.

### Ordering Information

PN	Description
SQF-SM8M2-XXG-SBC	SQFlash 640 series M.2 2280 16/32/64 GB MLC, 2-CH (0 ~ 70° C)
SQF-SM8M2-XXG-SBE	SQFlash 640 series M.2 2280 16/32/64 GB MLC, 2-CH (-40 ~ 85° C)
SQF-SM8M4-XX-SBC	SQFlash 640 series M.2 2280 128/256/512 GB, 1TB MLC, 4-CH (0 ~ 70° C)
SQF-SM8M4-XX-SBE	SQFlash 640 series M.2 2280 128/256/512 GB, 1TB MLC, 4-CH (-40 ~ 85° C)
SQF-SM8U2-XXG-SBC	SQFlash 640 series M.2 2280 8/16/32 GB Ultra MLC, 2-CH (0 ~ 70° C)
SQF-SM8U2-XXG-SBE	SQFlash 640 series M.2 2280 8/16/32 GB Ultra MLC, 2-CH (-40 ~ 85° C)
SQF-SM8U4-XX-SBC	SQFlash 640 series M.2 2280 64/128/256/512 GB Ultra MLC, 4-CH (0 ~ 70° C)
SQF-SM8U4-XX-SBE	SQFlash 640 series M.2 2280 64/128/256/512 GB Ultra MLC, 4-CH (-40 ~ 85° C)

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Solid State Drives - SSD category](#):*

*Click to view products by [Advantech manufacturer](#):*

Other Similar products are found below :

[ATCA7360-MMOD-SATA2](#) [ASD25-MLC064G-CT-160-1](#) [SQF-SM4V2-256G-SBC](#) [SD7SN6S-128G-1122](#) [MTFDDAA120MBB-2AE1ZABYY](#) [SDSDQAD-128G](#) [SM668GXB-ACS O1118](#) [SDINADF4-64G-H](#) [SQF-S25V4-240G-SCC](#) [SQF-SDMM2-256G-S9E](#) [SFSA016GQ1BJ8TO-I-DT-226-STD](#) [MTFDDAK060MBD-1AH12ITYY](#) [VSF202PC016G-100](#) [AF512GSMEL-VABIP](#) [SSDPEKKA020T801](#) [MTFDDAK064MBD-1AH12ITYY](#) [EP-SSMSF128AACS](#) [APS297F064G-4BTM1GWF](#) [HBRPEKNX0202A01](#) [SSDPE21D015TAX1](#) [SSDPED1D015TAX1](#) [SSDPEKKF020T8X1](#) [SSDPEKKR256G7XN](#) [SSDPEKKW020T8X1](#) [SSDPEKKW512G801](#) [SSDPEKNW020T801](#) [SSDPEKNW020T9X1](#) [SSDPEL1D380GAX1](#) [SM2280S3G2/120G](#) [MTFDDAK1T9QDE-2AV1ZABYY](#) [MTFDDAK3T8QDE-2AV1ZABYY](#) [MTFDDAT128MBD-1AK12ITYY](#) [MTFDDAV256TDL-1AW12ABYY](#) [MTFDDAK2T0TDL-1AW1ZABYY](#) [MTFDDAK1T0TDL-1AW12ABYY](#) [MTFDDAV512TDL-1AW1ZABYY](#) [MTFDDAV256TDL-1AW1ZABYY](#) [MTFDHAL11TATCW-1AR1ZABYY](#) [MTFDHAL12T8TDR-1AT1ZABYY](#) [MTFDHAL1T6TCU-1AR1ZABYY](#) [MTFDHAL1T9TCT-1AR1ZABYY](#) [MTFDHAL3T8TCT-1AR1ZABYY](#) [MTFDHAL3T8TDP-1AT1ZABYY](#) [MTFDHAL6T4TCU-1AR1ZABYY](#) [MTFDHAL6T4TDR-1AT1ZABYY](#) [MTFDHAL7T6TCT-1AR1ZABYY](#) [MTFDHAL7T6TDP-1AT1ZABYY](#) [MTFDHAL8TATCW-1AR1ZABYY](#) [MTFDHBA2T0QFD-1AX1AABYY](#) [MTFDHBA512TCK-1AS15ABYY](#)