

USB-4750

USB-4761

32-Ch Isolated Digital I/O USB Module

8-Ch Relay, 8-Ch Isolated Digital Input USB Module



USB-4750



Features

- Compatible with USB 1.1/2.0
- Bus powered
- 16 x isolated digital input and 16 x digital output channels
- High voltage isolation on all channels (2,500 V_{DC})
- High sink current on isolated output channels (200 mA/channel)
- Supports 5 ~ 60 V_{DC} isolated input channels
- Interrupt handling capability
- Timer/counter capability
- Suitable for DIN rail mounting
- 1 x Lockable USB cable included for connection security

Specifications

Isolated Digital Input

- Channels** 16
- Input Voltage** Logic 0: 2 V max.
Logic 1: 5 V min. (60 V max.) or dry contact
- Interruptible Channels** 2
- Isolation Protection** 2,500 V_{DC}

Isolated Digital Output

- Channels** 16
- Output Type** Sink (NPN)
- Isolation Protection** 2,500 V_{DC}
- Output Voltage** 5 ~ 40 V_{DC}
- Sink Current** 200 mA max. per channel

Isolated Counter

- Channels** 2
- Resolution** 32 bit
- Max. Input Frequency** 1 kHz
- Isolation Protection** 2,500 V_{DC}

General

- Bus Type** USB 1.1/2.0
- I/O Connector** Onboard screw terminal
- Dimensions (L x W x H)** 132 x 80 x 32 mm (5.2" x 3.15" x 1.26")
- Power Consumption** Typical: 5 V @ 300 mA
Max.: 5 V @ 600 mA
- Operating Temperature** 0 ~ 60 °C (32 ~ 140 °F)
- Storage Temperature** -20 ~ 70 °C (-4 ~ 158 °F)
- Storage Humidity** 5 ~ 95% RH, non-condensing

Ordering Information

- USB-4750-CE** 32-ch isolated digital I/O USB module

Accessories

- 1960004544** Wall mount bracket
- 1960005788** VESA mount bracket



USB-4761



Features

- Compatible with USB 1.1/2.0
- Portable
- Bus powered
- 8 x Relay output and 8 x isolated digital input channels
- LED indicators to show activated relays
- 8 x Form C-type relay output channels
- High-voltage isolation on input channels (2,500 V_{DC})
- High ESD protection (2,000 V)
- Wide input range (5 ~ 30 V_{DC})
- Interrupt handling capability
- Detachable screw terminal on modules
- Suitable for DIN rail mounting
- 1 x Lockable USB cable included for connection security

Specifications

Isolated Digital Input

- Channels** 8
- Input Voltage** Logic 0: 2 V max.
Logic 1: 5 V min. (30 V max.)
- Isolation Protection** 2,500 V_{DC}
- Opto-Isolator Response** 50 μs

Relay Output

- Contact Rating** 0.25 A @ 240 V_{AC}, 1 A @ 30 V_{DC}
- Max. Switching Power** 62.5 VA, 60 W
- Max. Switching Voltage** 250 V_{AC}, 220 V_{DC}
- Max. Switching Current** 5 A
- Operate/Release Time** max. 5 / 4 ms
- Life Expectancy (Electrical)** 5 x 10⁷ cycles typ. @ 10 mA/12 V
2 x 10⁶ cycles typ. @ 2000 mA/30 V

General

- Bus Type** USB 1.1/2.0
- I/O Connector** Onboard screw terminal
- Dimensions (L x W x H)** 132 x 80 x 32 mm (5.2" x 3.15" x 1.26")
- Power Consumption** Typical: 5 V @ 60 mA
Max.: 5 V @ 400 mA
- Operating Temperature** 0 ~ 60 °C (32 ~ 140 °F)
- Storage Temperature** -20 ~ 70 °C (-4 ~ 158 °F)
- Storage Humidity** 5 ~ 95% RH, non-condensing

Ordering Information

- USB-4761-CE** 8-ch relay/isolated digital input USB module

Accessories

- 1960004544** Wall mount bracket
- 1960005788** VESA mount bracket

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [I/O Modules](#) category:

Click to view products by [Advantech](#) manufacturer:

Other Similar products are found below :

[70L-OAC-L](#) [G21960000700](#) [G34960002700](#) [G88104401](#) [IDC-5B](#) [OACU](#) [C4SWOUT](#) [FC6A-T32K3](#) [SNAP-OAC5MA](#) [FC6A-N16B3](#)
[FC6A-N32B3](#) [FC6A-T16P3](#) [G3TAOD201SDC24](#) [PB32HQ](#) [PB16T](#) [PB8](#) [PB8H](#) [C200H-OD211](#) [GT1-AD04CST](#) [GT1-DA04](#) [70GRCQ24-](#)
[HS](#) [M-OAC5](#) [G4OAC24AMA](#) [2736505](#) [6202](#) [6402](#) [IL MOD BK DI8 DO4-PAC](#) [FC6A-J2C1](#) [FC6A-KC1C](#) [FC6A-N08A11](#) [FC6A-M24BR1](#)
[FC6A-K4A1](#) [FC6A-T32P3](#) [9-1393028-2](#) [GP32900003700](#) [641-480-5022](#) [PB16H](#) [WISE-4050/LAN-B](#) [WISE-S614T-A](#) [ADAM-4068-C](#)
[56475](#) [ADAM-4017+-F](#) [ADAM-4118-C](#) [AMAX-4856-B](#) [WISE-4050-B](#) [ADAM-4051-C](#) [ADAM-4053-F](#) [GT1-AD08MX](#) [TM5SDO6TBFS](#)
[70Q3446](#)