
Specify **FIEL**



HC-49/U Standard Height Crystal



HC-49/U

FEATURES

- Wide Frequency Range
- Additional EMI Protection
- Custom Manufacturing Capability
- Fast Turnaround Options

APPLICATIONS

- Microprocessor Systems
- Datacommunications
- Consumer Electronics
- Automotive Electronics

STANDARD SPECIFICATION

Frequency Range: 300 kHz to 225 MHz Adjustment Tolerance at 25°C: \pm 30PPM Max.

Frequency Stability: ± 50 PPM Max.

Operating Temperature Range: -10° C to $+60^{\circ}$ C

Load Capacity: 30pF

E.S.R: See Table

Drive level: 500 MicroWatt

Ageing: ±5PPM 1st Year Max.

Frequenc	y Ran	ge	E.S.R		
300kHz	~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~	800 kHz	3000 Ω		
800kHz		1.3 MHz	5000 Ω		
1.8 MHz		2.0 MHz	800 Ω		
2.0MHz		2.4 MHz	300 Ω		
2.4MHz		3.0 MHz	250 Ω		
3.0MHz		3.2 MHz	120 Ω		
3.2MHz		4.0 MHz	90 Ω		
4.0MHz		4.2 MHz	100 Ω		
4.2MHz	~ ~ ~ ~ ~ ~	6.0 MHz	50 Ω		
6.0MHz		8.0 MHz	40 Ω		
8.0MHz		36 MHz	25 Ω		
36MHz		64 MHz	40 Ω		
64MHz		125 MHz	80 Ω		
125MHz		200 MHz	140 Ω		

AVAILABLE OPTIONS

Frequency Range: 300 kHz \sim 225 MHz \pm 5PPM \sim \pm 100PPM Load Capacity: Series or 9pF \sim 50pF Shunt Capacity (C0): 4.5pF \sim 7pF (Typ.) Dynamic Capacity (C1): 18fF \sim 20fF (Typ.)

Frequency Stability vs Operating Temperature Range

Operating Temperature Range	Temperature Sability						
	+/ -5 PPM	+/ -10 PPM	+/-20PPM	+/-30PPM	+/-40PPM	+/-50PPM	
-10 to +60 -20 to +70 -40 to +90 -55 to +105 -55 to +125		i	i	i	į		

Value Added Services

In addition, AEL Crystals Ltd are able to offer our customers the following value added services:-

- Fitted InsulatorsRadial Taping
- Lead CroppingEarth Lead
- Lead Pre-Forming
- Bar-Coding



vaelcrystals.co.uk quartz based frequency control components

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for ael manufacturer:

Other Similar products are found below:

O16M000000L021 X9M830400L035 O25M000000L684 O100M000000L010 O16M000000L682 O20M000000L046 O64M000000L153

E3SB16.0000F09G11AE O25M000000L063 O3M686400L120 X14M000000L001 X32K768L102 O25M0000000L059 X5M0000000L001

X9M830400L152 X4M194304L056 X50M000000L001 X12M000000L188 X4M608000L075 O32M000000L097 O40M000000L125

O40M000000L126 O4M000000L638 X15M000000L002 O4M000000L134 O20M000000L676 O8M000000L166 X307K200L001

X40M000000L104 O8M000000L642 C8M000000L004 X32K768S021 X1M843200L010 C4M000000L001 X19M660800L307

X20M000000L010 X32K768S019 X7M372800L027 O10M000000S023 X32K768L009 C8M000000S014 C16M000000L003

X32K768L104