

AT53AL SERIES

40V 250mA Ultralow-Quiescent-Current LDO

Input Voltage: up to 40V Output: 2.5-5.0V

General Description

The AT53AL Series ultra-low quiescent current regulator features low dropout voltage and low current in the standby mode. With less than 1.5 μ A quiescent current at no load, the AT53AL Series is ideally suited for standby micro-control-unit systems, especially for always-on applications like E-meters, fire alarms, smoke detectors and other battery operated systems. The AT53AL Series retains all of the features that are common to low dropout regulators including a low dropout PMOS pass device, short circuit protection, and thermal shutdown.

The AT53AL Series has a 40V maximum operating voltage limit, -40°C to 125°C operating temperature range, and \pm 2% output voltage tolerance over the entire output current, input voltage, and temperature range. The AT53AL Series is available in SOT23-5 and SOT-89 surface mount packages.


Features

- ◆ Vin Range up to 40V
- ◆ Output Voltage Tolerances of \pm 2%
- ◆ Output Current of 250mA
- ◆ Ultra Low Quiescent Current(IQ=1.5 μ A)
- ◆ Dropout Voltage Typically 1200 mV at I_{OUT} = 250 mA
- ◆ Internal Thermal Overload Protection
- ◆ Internal Short-Circuit Current Limit
- ◆ Ceramic Capacitor Stable

Applications



- ◆ E-meters, Water Meters and Gas Meters
- ◆ Fire Alarm, Smoke Detector
- ◆ Appliances and White Goods

Pin Configuration



AT53ALXXESE
SOT23-5



AT53ALXXSE
SOT23-5



AT53ALXXSQB
SOT-89

AT53ALXXSQ
SOT-89

Typical Application Circuit




AT53AL SERIES

Pin Assignment


Pin Name	SOT23-5		SOT-89		Pin Function
	AT53ALXXESE	AT53ALXXSE	AT53ALXXSQB	AT53ALXXSQ	
V _{OUT}	5	5	3	1	Output Voltage Pin
GND	2	2	1	2,4	Ground
V _{IN}	1	1	2,4	3	Input Voltage Pin
EN	3	---	---	---	Enable
CN	4	3,4	---	---	/

Function Block Diagram



Selection Guide

AT 53AL XX XX



AT53AL SERIES

Electrical Characteristics (Ratings at 25°C ambient temperature unless otherwise specified)

Parameter	Value	Unit
V _{OUT} to GND Voltage	-0.3~7	V
V _{IN} to GND Voltage	-0.3~45	V
EN Pin to GND Voltage	-0.3~45	V
Power Dissipation	SOT-89	1
	SOT23-5L	0.5
Thermal Resistance, Junction-to-Ambient	SOT-89	100
	SOT23-5L	200
Operating temperature range	-40~125	°C

Electrical Characteristics (V_{IN}=12V, I_{OUT}=1mA, C_{IN}=C_{OUT}=1uF, T_J=25°C, unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Units
Output Voltage Range	V _{OUT}		1.5		5.5	V
Output Voltage Accuracy	ΔV _{OUT}		-2		2	%
Line Regulation	ΔV _{LINE}	V _{IN} = V _{OUT} + 1V to 40V, or V _{IN} = 5V to 40V, if V _{OUT} < 4V		2	10	mV
Load Regulation	ΔV _{LOAD}	I _{OUT} = 1mA to 100mA		0.25		%
		I _{OUT} = 1mA to 250mA		1		
Dropout Voltage	V _{DROP}	I _{OUT} = 100mA		400		mV
		I _{OUT} = 250mA		1200		mV
Quiescent Current	I _Q	T _J = 25°C		1.5	2.5	uA
Current Limit	I _{CL}		270	320		mA
Enable high level	V _{ENHI}		0.9			V
Enable low level	V _{ENLO}				0.4	V
Enable pin pull high	I _{EN}			0.3		uA
Thermal Shutdown	T _{SD}			140		°C
Thermal Shutdown	T _{HY}			20		°C
Power-supply rejection ratio	PSRR	f = 1kHz		80		dB
		f = 10kHz		60		dB
Human body model	HBM		3			KV
Charged device model	CDM		200			V

AT53AL SERIES

Typical Characteristics ($V_{IN}=12V$, $I_{OUT}=1mA$, $V_{OUT}=3.3V$, $C_{IN}=C_{OUT}=1\mu F$, $T_J=25^\circ C$, unless otherwise specified)




Fig 1 Vout vs Vin




Fig 2 Vout vs Load




Fig 3 Iq vs Vin




Fig 4 Dropout vs Load




Fig 5 Iq vs Vout




Fig 6 Vout(3.3V) vs Temperature

AT53AL SERIES




Fig 7 Vout Load transient(0 to 50mA)




Fig 8 Vout Load Transient(50 to 250mA)




Fig 9 Vout Load Transient(1 to 250mA)




Fig 10 Vout short to GND



Fig 11 Vin Start up





Fig 12 PSRR vs. Frequency(Vin=9V,Vout=3.3V)

AT53AL SERIES


PACKAGE OUTLINE

SOT23-5



DIM	Millimeters		Inches	
	Min	Max	Min	Max
A	1.05	1.45	0.0413	0.0571
A1	0	0.15	0.0000	0.0059
A2	0.9	1.3	0.0354	0.0512
A3	0.6	0.7	0.0236	0.0276
b	0.25	0.5	0.0098	0.0197
c	0.1	0.23	0.0039	0.0091
D	2.82	3.05	0.1110	0.1201
e1	1.9(TYP)		0.0748(TYP)	
E	2.6	3.05	0.1024	0.1201
E1	1.5	1.75	0.0512	0.0689
e	0.95(TYP)		0.0374(TYP)	
L	0.3	0.6	0.0118	0.0236
L1	0.59(TYP)		0.0232(TYP)	
θ	0	8°	0.0000	8°
C1	0.2(TYP)		0.0079(TYP)	

SOT-89



DIM	Millimeters		Inches	
	Min	Max	Min	Max
A	1.4	1.6	0.0551	0.0630
b	0.32	0.52	0.0126	0.0205
b1	0.4	0.58	0.0157	0.0228
c	0.35	0.45	0.0138	0.0177
D	4.4	4.6	0.1732	0.1811
D1	1.55(TYP)		0.061(TYP)	
D2	1.75(TYP)		0.0689(TYP)	
e1	3.0(TYP)		0.1181(TYP)	
E	2.3	2.6	0.0906	0.1023
E1	3.94	4.4	0.1551	0.1732
E2	1.9(TYP)		0.0748(TYP)	
e	1.5(TYP)		0.0591(TYP)	
L	0.8	1.2	0.0315	0.0472
θ	45°		45°	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Linear Voltage Regulators](#) category:

Click to view products by [Agertech](#) manufacturer:

Other Similar products are found below :

[LV56831P-E](#) [LV5684PVD-XH](#) [MCDTSA6-2R](#) [L7815ACV-DG](#) [PQ3DZ53U](#) [LV56801P-E](#) [TLE42794G](#) [L78L05CZ/1SX](#) [L78LR05DL-MA-E](#) [636416C](#) [714954EB](#) [ZMR500QFTA](#) [LV5680P-E](#) [L78M15CV-DG](#) [L79M05T-E](#) [TLS202A1MBVHTSA1](#) [L78LR05D-MA-E](#) [NCV317MBTG](#) [NTE7227](#) [MP2018GZD-33-P](#) [MP2018GZD-5-P](#) [LV5680NPVC-XH](#) [LT1054CN8](#) [MP2018GZD-5-Z](#) [MP2018GZD-33-Z](#) [AT55EL50ESE](#) [APL5934DKAI-TRG](#) [78L05U](#) [78L05](#) [CL9193A15L5M](#) [CL9036A30F4M](#) [CL9036A18F4M](#) [CL9036A25F4M](#) [CL9036A28F4M](#) [CL9036A33F4M](#) [CL9906A18F4N](#) [CL9906A30F4N](#) [CL9908A30F4M](#) [CL9908A33F4M](#) [CL9908A18F4M](#) [CL9908A28F4M](#) [TL431ACM/TR](#) [TL431AIM/TR](#) [LM78L05ACM/TR](#) [HT7812ARMZ](#) [HT7805ARMZ](#) [HT317LRHZ](#) [HXY6206I-3.0](#) [HXY6206I-3.3](#) [XC6206P252MR](#) [XC6206P282MR](#)