

# Product Data Sheet

## Vaseline Oil



Means applied for lubrication of machine parts and precise mechanisms in automotive, textile and telecommunication industry. Non-staining, odour-free, colourless, neutral in contact with plastics. Reduces friction, preserves the components exposed to weather conditions and prevents plastic or rubber components from adhesion to moulds.

**Designed for:**

- ◆ preparation reduces and diminishes friction
- ◆ lubrication of machines and all precise mechanisms
- ◆ efficiently eliminates squeaks and grinds
- ◆ facilitates sliding

**Application:**

- preparation reduces and diminishes friction,
- ideal for lubrication of machines, devices and all precise mechanisms,
- efficiently eliminates squeaks and grinds, facilitates sliding,
- protects and preserves rubber and plastic

**Package:**

Capacity	Package	Symbol
50 ml (oiler)	20	AGT-017
100 ml (oiler)	20	AGT-018
300 ml (aerosol)	40	AGT-019
1000 ml (bottle)	18	AGT-099



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Chemicals](#) category:*

*Click to view products by [AG Termopasty](#) manufacturer:*

Other Similar products are found below :

[DP-605NS](#) [3045-QT](#) [3125-9S](#) [3748-Q-58"x8"](#) [FO-25DT](#) [S1009-KIT-A-CS8606](#) [DP100-200ML](#) [1743-2FP](#) [152-KA-NC](#) [VERSIL406](#) [826-450G](#) [3789-Q](#) [9729](#) [9223](#) [9945](#) [7000000275](#) [1601](#) [8330-19G](#) [841AR-150ML](#) [842AR-P](#) [843WB-15ML](#) [8462-85ML](#) [4352-1L](#) [4354-1L](#) [838AR-P](#) [838AR-15ML](#) [419D-P-BK](#) [419D-P-GR](#) [419D-P-WH](#) [8MT-450](#) [8MT-25](#) [832HD-25ML](#) [8616-25ML](#) [832FX-450ML](#) [834ATH-375ML](#) [832HD-400ML](#) [843AR-340G](#) [843ER-800ML](#) [9310-300ML](#) [4228-225ML](#) [419D-55ML](#) [8800-375ML](#) [8810-375ML](#) [8820-2.55L](#) [419E-340G](#) [842UR-12ML](#) [419D-1L](#) [CW3300WHITE](#) [CW2205](#) [10447](#)