

Product Data Sheet

Silicone Paste N

The silicone paste provides insulation and protection against weathering. The product prevents from breakdowns, preserves rubber, plastic and, what is important, features a wide range of operating temperatures: from -50°C to 200°C , a very good chemical resistance to oxidation, aqueous solutions of acids, bases and salts, sulfur dioxide, and ammonia.

Properties:

- ◆ Density: $1.02 \div 1.04 \text{ g/cm}^3$
- ◆ Operating temperature: $-40 \div 200^{\circ}\text{C}$
- ◆ Weight loss within 24h at 200°C : 5%
- ◆ Specific heat: $0.3 \text{ kcal/kg} \cdot ^{\circ}\text{C}$
- ◆ Water extract: $4 \div 6 \text{ pH}$
- ◆ Penetration, before processing, after processing: $180 \div 220$ to 270mm ,
- ◆ Dielectric constant 100 Hz: 2.9
- ◆ Loss tangent 100 Hz, max.: 0.003
- ◆ Cross-through resistance, min.: $1015 \text{ Ohm} \times \text{cm}$,
- ◆ Breakdown voltage: $\sim 30 \text{ kV/mm}$

Package:

Weight	Package	Symbol
3,5 g (metal tube)	10	AGT-052
60 g (jar)	6 or 36	AGT-053
1000 g (plastic can)	1	AGT-054



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Thermal Interface Products](#) category:

Click to view products by [AG Termopasty](#) manufacturer:

Other Similar products are found below :

[63072-2-4013](#) [64442-1-7612](#) [FGN80-2](#) [PFM-172-60](#) [95778-1-5171](#) [A-40](#) [ACDIN4001-01-S](#) [APA502-80-001](#) [188761F00000G](#) [95779-1-5171](#) [9601-7](#) [9614-2-4013](#) [189790F00000](#) [189951F00000G](#) [2103-4-7320](#) [CN9565-000](#) [31570-2-4013](#) [LZ24-1](#) [4103G](#) [450-20-0025](#) [5300AC](#) [1.500G](#) [53-77-13ACG](#) [450-20-0017](#) [4949G](#) [08121](#) [08133](#) [08151](#) [08188](#) [08196](#) [10637-4-1040](#) [54476-2-4013](#) [71883-2-4053](#) [188651F00000G](#) [64445-1-7612](#) [66786-4-7320](#) [TP0001](#) [4952G](#) [4860](#) [450-20-0148](#) [88601-2-2929](#) [SC80-W2](#) [09450-M45](#) [09362-M45](#) [V6516C](#) [A17713-05](#) [A17690-06](#) [A17690-10](#) [A17690-05](#) [A17690-03](#) [A17775-05](#)