

Product Data Sheet

Rosin

A flux with activators added to facilitate soldering; it is almost as active as soldering paste.

Used as a base for the flux calibration (25% solution in isopropyl alcohol).

Application:

- very good flux when soldering tin-lead alloy
- used to rub the hair of string instruments in order to increase roughness and thereby increase its adhesion to the strings
- as a binder in printing inks, which simultaneously improves its properties
- component lacquers, varnishes, soaps, lacquer, plastics, rubber

Package:

| Weight | Package | Symbol |
|-------------------|---------|---------|
| 20g (metal can) | 5 or 50 | AGT-033 |
| 35g (metal can) | 5 or 50 | AGT-034 |
| 100g (metal can) | 5 or 50 | AGT-035 |
| 500g (string bag) | 1 | AGT-094 |



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Soldering Flux](#) category:

Click to view products by [AG Termopasty](#) manufacturer:

Other Similar products are found below :

[24-6337-9727](#) [8351-1L](#) [051-0008](#) [051-0009](#) [051-0010](#) [053-1000](#) [053-1001](#) [053-1002](#) [053-1003](#) [CW8700](#) [CW8300](#) [SMD4300TF10](#)
[SMD291/30CC](#) [CQ2LF](#) [CQ4LF](#) [8342-50G](#) [CW8100](#) [CW8400](#) [CW8500](#) [CQ4LF-0.5](#) [CQ4LF-1.0](#) [SMD291](#) [SMD291150G](#) [SMD29175G](#)
[SMD291AX](#) [SMD291AX10](#) [SMD291AX250T3](#) [SMD291AX250T5](#) [SMD291ST2CC6](#) [SMD291ST8CC](#) [SMD4300TF](#) [CW8100](#) [CW8200](#)
[SSS500ML](#) [63-0000-0951](#) [63-0000-0977](#) [63-0000-1544](#) [83-1000-0186](#) [83-1097-2331](#) [NF372-TB](#) [760089](#) [8341-10ML](#) [8341-10ML](#) [835-](#)
[100ML](#) [837-P](#) [SF-01](#) [SF-02](#) [2506-N](#) [2507-N](#)