

### NB Series


- High reliability high temperature
- Endurance: +130°C 2,000 to 5,000 hours
- RoHS Compliant



#### ◆ SPECIFICATIONS


Items	Characteristics								
Category	-40 to +130°C								
Temperature Range									
Rated Voltage Range	10 to 100V <sub>dc</sub>								
Capacitance Tolerance	±20%(M) (at 20°C, 120Hz)								
Leakage Current	I ≅ 0.01CV or 3μA, whichever is greater. Where, I : Max. leakage current (μA), C : Nominal capacitance (μF), V : Rated voltage (V) (at 20°C after 2 minutes)								
Dissipation Factor (tanδ)	Rated voltage (V <sub>dc</sub> )	10	16	25	35	50	63	100	(at 20°C, 120Hz)
	tanδ (Max.)	0.20	0.16	0.14	0.12	0.10	0.09	0.08	
Low Temperature Characteristics (Max. Impedance Ratio)	Rated voltage (V <sub>dc</sub> )	10	16	25	35	50	63	100	
	Z(-25°C)/Z(+20°C)	3	2						
	Z(-40°C)/Z(+20°C)	6	4	3					
Endurance	The following specifications shall be satisfied when the capacitors are restored to 20°C after subjected to DC voltage with the rated ripple current is applied at 130°C.								
	Capacitance change	≤ ±30% of the initial value					Case Dia		Lifetime (hours)
	D.F. (tanδ)	≤ 300% of the initial specified value					ØD = 8		2,000
	Leakage current	≤ The initial specified value					ØD = 10		3,000
Shelf Life	The following specifications shall be satisfied when the capacitors are restored to 20°C after exposing them for 1000 hours at 130°C without voltage applied.								
	Capacitance change	≤ ±30% of the initial value					ØD ≥ 12.5		5,000
	D.F. (tanδ)	≤ 300% of the initial specified value							
	Leakage current	≤ 500% The initial specified value							

#### ◆ DIMENSIONS [mm]



ØD	8	10	12.5	16	18
Ød	0.5	0.6	0.6	0.6	0.8
F	3.5	5.0	5.0	7.5	7.5
ØD'	ØD+0.5max.				
L'	L+2max.				

#### ◆ PART NUMBER SYSTEM



※ Sleeve Code and Terminal Code should follow the part number system

#### ◆ RATED RIPPLE CURRENT MULTIPLIERS

Frequency correction factor for ripple current (Hz)

Cap. (μF) \ Freq. (Hz)	50/60	120	1k	10k	100k
Cap. < 10	0.35	0.42	0.60	0.80	1.00
10 ≤ Cap. < 47	0.45	0.55	0.75	0.90	1.00
47 ≤ Cap. < 470	0.60	0.70	0.85	0.95	1.00
470 ≤ Cap. < 2200	0.65	0.75	0.90	0.98	1.00
Cap. ≥ 2200	0.75	0.80	0.95	1.00	1.00

The endurance of capacitors is shortened with internal heating produced by ripple current at the rate of halving the lifetime with every 5°C rise. When long life performance is required in actual use, the rms ripple current has to be reduced.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Aluminium Electrolytic Capacitors - Radial Leaded](#) category:*

*Click to view products by [Aihua](#) manufacturer:*

Other Similar products are found below :

[LXY50VB4.7M-5X11](#) [RFO-100V471MJ7P#](#) [ECE-A1EGE220](#) [B41041A7226M8](#) [B41044A7157M6](#) [EKZM160ETD471MHB5D](#)  
[NCD681K10KVY5PF](#) [NEV1000M25EF-BULK](#) [NEV100M35DC](#) [NEV100M63DE](#) [NEV220M25DD-BULK](#) [NEV.33M100AA](#)  
[NEV4700M50HB](#) [NEV.47M100AA](#) [NEVH1.0M250AB](#) [NEVH3.3M250BB](#) [NEVH3.3M450CC](#) [KM4700/16](#) [KME50VB100M-8X11.5](#)  
[SG220M1CSA-0407](#) [ES5107M016AE1DA](#) [ESMG160ETD102MJ16S](#) [ESX472M16B](#) [227RZS050M](#) [476CKH100MSA](#) [477RZS050M](#)  
[UVX1V101KPA1FA](#) [UVX1V222MHA1CA](#) [KME25VB100M-6.3X11](#) [VTL100S10](#) [VTL470S10](#) [VTL470S16A](#) [511D336M250EK5D](#)  
[052687X](#) [ECE-A1CF471](#) [NRE-S560M16V6.3X7TBSTF](#) [RGA221M1CTA-0611G](#) [ERZA630VHN182UP54N](#) [UPL1A331MPH](#)  
[SK035M0100AZS-0611](#) [MAL214658821E3](#) [NEV1000M6.3DE](#) [NEV100M16CB](#) [NEV100M50DD-BULK](#) [NEV2200M16FF](#) [NEV220M50EE](#)  
[NEV2.2M50AA](#) [NEV330M63EF](#) [NEV4700M35HI](#) [NEV4.7M100BA](#)