

WK Series


- Standard series for general purpose
- Endurance: +85°C 2,000 hours
- RoHS Compliant



◆ SPECIFICATIONS


Items	Characteristics														
Category	-40 to +85°C (6.3 to 100V _{dc})						-25 to +85°C (160 to 450V _{dc})								
Temperature Range															
Rated Voltage Range	6.3 to 450V _{dc}														
Capacitance Tolerance	±20%(M) (at 20°C, 120Hz)														
Leakage Current	6.3 to 100V _{dc}			160 to 450V _{dc}			Where, I : Max. leakage current (μA), C : Nominal capacitance (μF), V : Rated voltage (V)								
	I ≅ 0.01CV or 3μA Whichever is greater			I ≅ 0.03CV+10μA			(at 20°C after 2minutes)								
Dissipation Factor (tanδ)	Rated voltage (V _{dc})	6.3	10	16	25	35	50	63	100	160	200	250	350	400	450
	tanδ (Max.)	0.24	0.20	0.16	0.14	0.12	0.10	0.09	0.08	0.08	0.20	0.20	0.24	0.24	0.24
When nominal capacitance exceeds 1,000 uF, add 0.02 to the value above for each 1,000 uF increase. (at 20°C, 120Hz)															
Low Temperature Characteristics (Max. Impedance Ratio)	Rated voltage (V _{dc})	6.3	10	16	25	35	50	63	100	160-250	350-400	450			
	Z(-25°C)/Z(+20°C)	5	4	3	2			3			6	6	(at 120Hz)		
	Z(-40°C)/Z(+20°C)	12	10	8	5	4	3			-	-	-			
Endurance	The following specifications shall be satisfied when the capacitors are restored to 20°C after the rated voltage is applied for 2,000hours at 85°C.														
	Capacitance change	≤±20% of the initial value													
	D.F. (tanδ)	≤200% of the initial specified value													
	Leakage current	≤The initial specified value													
Shelf Life	The following specifications shall be satisfied when the capacitors are restored to 20°C after exposing them for 1,000 hours at 85°C without voltage applied.														
	Capacitance change	≤±20% of the initial value													
	D.F. (tanδ)	≤200% of the initial specified value													
	Leakage current	≤200%The initial specified value													

◆ DIMENSIONS [mm]



ØD	5	6.3	8	10	12.5	16	18
Ød	0.5	0.5	0.5	0.6	0.6	0.8	0.8
F	2.0	2.5	3.5	5.0	5.0	7.5	7.5
ØD'	ØD+0.5max.						
L'	L+2max.						

◆ PART NUMBER SYSTEM



※Sleeve code and Terminal Code should follow the part number system

◆ RATED RIPPLE CURRENT MULTIPLIERS

Frequency correction factor for ripple current Φ5 to Φ18

Freq. (Hz)	50	120	300	1k	10k	100k
Cap. <10	0.65	1.00	1.35	1.75	2.30	2.50
10 ≤ Cap. <100	0.75	1.00	1.25	1.50	1.75	1.80
100 ≤ Cap. ≤1000	0.80	1.00	1.15	1.30	1.40	1.50
Cap. >1000	0.85	1.00	1.03	1.05	1.08	1.08

The endurance of capacitors is shorted with internal heating produced by ripple current at the rate of halving the lifetime with every 5°C rise. When long life performance is required in actual use, the rms ripple current has to be reduced.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Aluminium Electrolytic Capacitors - Radial Leaded](#) category:

Click to view products by [Aihua](#) manufacturer:

Other Similar products are found below :

[LXY50VB4.7M-5X11](#) [RFO-100V471MJ7P#](#) [ECE-A1EGE220](#) [B41041A2687M8](#) [B41041A7226M8](#) [B41044A7157M6](#)
[EKXG201EC3101ML20S](#) [EKZM160ETD471MHB5D](#) [NCD681K10KVY5PF](#) [NEV1000M25EF-BULK](#) [NEV100M35DC](#) [NEV100M63DE](#)
[NEV220M25DD-BULK](#) [NEV.33M100AA](#) [NEV4700M50HB](#) [NEV.47M100AA](#) [NEVH1.0M250AB](#) [NEVH3.3M250BB](#) [NEVH3.3M450CC](#)
[KM4700/16](#) [KME50VB100M-8X11.5](#) [SG220M1CSA-0407](#) [ES5107M016AE1DA](#) [ESMG160ETD102MJ16S](#) [ESX472M16B](#)
[SZ010M1500A5S-1015](#) [227RZS050M](#) [476CKH100MSA](#) [UVX1V101KPA1FA](#) [UVX1V222MHA1CA](#) [KME25VB100M-6.3X11](#)
[VTL100S10](#) [VTL470S10](#) [VTL470S16A](#) [511D336M250EK5D](#) [052687X](#) [ECE-A1CF471](#) [EKMA500ELL4R7ME07D](#) [NRE-](#)
[S560M16V6.3X7TBSTF](#) [RGA221M1CTA-0611G](#) [ERZA630VHN182UP54N](#) [UPL1A331MPH](#) [SK035M0100AZS-0611](#) [MAL214658821E3](#)
[NEV1000M6.3DE](#) [NEV100M16CB](#) [NEV100M50DD-BULK](#) [NEV2200M16FF](#) [NEV220M50EE](#) [NEV2.2M50AA](#)