

#### **Stencil Cleaner**

#### **Features:**

- Extends Paste Life
- Increases Wipe Cycle Times
- Enhances Paste Release
- Reduces Paste Dry-Out

- May be Used to Clean Solder Paste or Epoxy/Adhesive Residues
- 100% Compatible with AIM Paste Formulations
- Eliminates Double Wiping

## **Description:**

200AX is a glycol ether based stencil cleaner with a concentrated additive that is 100% compatible with all AIM solder pastes and epoxies. 200AX is formulated for application by hand. Where automatic application is desired, the use of AIM's DJAW Stencil Cleaner is recommended. Unlike other stencil cleaners, the AIM stencil cleaners help to reduce solder paste dry-out while enhancing its release from even the finest apertures, allowing for a greater number of print cycles between cleaning. For the cleaning of epoxy residues, 200AX will not dissolve the epoxy. In addition, 200AX will not degrade cured epoxy.

WARNING: THIS PRODUCT IS DEVELOPED FOR USE BY HAND APPLICATION ONLY AND IS NOT INTENDED FOR AUTOMATED DISPENSE SYSTEMS. CHANGING OF EQUIPMENT PUMP SEALS AND CIRCULATION HOSES MAY BE REQUIRED TO USE IN AUTOMATED DISPENSE EQUIPMENT. CONTACT AIM TECHNICAL SUPPORT FOR MORE INFORMATION.

## **Physical Properties:**

ITEM	SPECIFICATION
Appearance & Odor	Clear Liquid, Butyl Odor
Specific Gravity	.9536
Boiling Point	230.6° C (447.08° F)
Flash Point	77.7° C (171.86° F)
Auto Ignition	227.7° C (441.86° F)

## **Application:**

- 200AX is shipped ready to use. No mixing or thinning is required.
- Spray 200AX in small amounts on a lint-free cloth or rag and wipe the areas of paste or epoxy residue to be cleaned. It is not recommended that 200AX be applied directly to the stencil. Wipe clean any excess 200AX from the stencil before proceeding.
- PCBs and components can safely be immersed or cleaned with 200AX.

#### **Packaging:**

200AX is available in 1, 5 and 55 gallon containers.

## Handling:

- 200AX has a sealed shelf life of 2 years.
- Do not freeze this product.
- Do not store near fire or flame.
- Keep away from sunlight as it may degrade product.
- Do not mix used and unused chemical in the same container.
- Reseal any opened containers.

#### Safety:

- Use with adequate ventilation and proper personal protective equipment.
- Refer to the accompanying Material Safety Data Sheet for any specific emergency information.
- Do not dispose of any hazardous materials in non-approved containers.

Manufacturing and Distribution Worldwide

Americas +1-401-463-5605 · Europe +44-1737-222-258 · Asia-Pacific +86-755-2993-6487 · info@aimsolder.com · www.aimsolder.com AIM IS ISO9001:2008 & ISO14001:2004 CERTIFIED

The information contained herein is based on data considered accurate and is offered at no charge. Product information is based upon the assumption of proper handling and operating conditions. All information pertaining to solder paste is produced with 45-micron powder. Liability is expressly disclaimed for any loss or injury arising out of the use of this information or the use of any materials designated. Please refer to http://www.aimsolder.com/terms.cfm to review AIM's terms and conditions.

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Solder category:

Click to view products by AIM manufacturer:

Other Similar products are found below :

 600YSY
 701-2758
 707-0425
 707-1746
 707-1811
 707-1813
 707-1831
 707-1850
 707-1852
 13-217-3-01
 P10695

 SN63WRAP3-.022-1-LB
 24-6040-0007
 DAC-061
 599Z
 701-2089
 707-0285
 707-0366
 707-0441-26
 707-1774
 707-1810
 24-6337-9727

 601Y
 24-9574-7619
 24-4060-2437
 14-6040-0125
 04-0595-0000
 V5S35[42G]217
 V8B45[60G]138
 V5B45[42G]138
 V3B45[20G]138

 XGS20[20G]158
 631960
 S2626-O-T
 8055
 5760140
 TRWR-204
 1152
 EC2002M-1
 WPT17
 WS6016
 760-2028
 ART.AGT-030
 54068

 8S005
 4900-18G
 648107
 811008
 11008
 1152
 EC2002M-1
 WPT17
 WS6016
 760-2028
 ART.AGT-030
 54068