

Card Edge Mount to Cable

.050" 9 thru 100 Contacts

Rugged Card Edge Mount


MK

Rugged Metal

MM

MK-2F2-037-175-320S (METAL)

MM-222-037-261-41WQ (METAL)



PLUG RECEPTACLE

DIMENSIONS												
SIZE	CONTACT ROWS	А	B PLUG RCPT MAX MAX		С	D	E POTTING WELL MAX	Н	HARDWARE	MOUNTING HOLES	R	S
9		.775	.334	.400	.390	.565	.270 .298	200			.355	
15		.925	.484	.550	.540	.715					.505	
21	2	1.075	.634	.700	.690	.865					.655	
25		1.175	.734	.800	.790	.965		#2-56 UNC THD		.755	.519	
31		1.325	.884	.950	.940	1.115			#2 30 GNC 1110	#4-40 UNC THD	.905	.519
37		1.475	1.034	1.100	1.090	1.265				#+ +0 0110 1110	1.055	
51	3	1.425	.984	1.050	1.040	1.215	.310	.341			1.005	
69		1.725	1.284	1.350	1.340	1.515					1.309	
100	4	2.160	1.384	1.508	1.432	1.800	.360 .384 #4-40 UNC THD					.540



PLUG: MK-2F2-031-175-320S

RECEPTACLE: MM-222-031-261-41WQ-900

JG	RE	CEPTACLE	XX	XX-X	X-XXX	(-XX	(-XXXX-
SE	RIES						
		MM .050" Rugged Metal I/O Connector (MM mates with MK, ML, MM, MN plugs)					
В	ODY						
2-Row (Sizes 9 thru 37) 3-Row (Size 51 & 69) 4-Row (Size 100)	2 3 4	2-Row (Sizes 9 thru 37) 3-Row (Size 51 & 69) 4-Row (Size 100)					
BODY STYLE: Plug, straight, card edge, with mounting brackets	2	BODY STYLE: Receptacle, straight, with ears					
BODY MATERIAL: Polyphenylene Sulfide with electroless nickel shell Polyphenylene Sulfide with electrodeposited cadmium shell Polyphenylene Sulfide with hard anodized black shell	3 4	BODY MATERIAL: Polyphenylene Sulfide with electroless nickel shell Polyphenylene Sulfide with electrodeposite cadmium shell Polyphenylene Sulfide with hard anodized black shell	d				
S	SIZE						
009, 015, 021, 025, 031, 037, 051, 069, 100	xxx	(009, 015, 021, 025, 031, 037, 051, 069, 10	0				
CON	ITACTS	6					
TYPE CONTACTS/TERMINATIONS: Pin, surface mount, .062094 pcb thickness (.010 dia) Pin, surface mount, .109140 pcb thickness (.010 dia)	21 24 25 26	TYPE CONTACTS/TERMINATIONS: Socket, straight, solder cup Socket, straight, .500" pigtails (.018 dia) Socket, straight, 1.000" pigtails (.018 dia) Socket, straight, crimped wire					
PLATING OPTIONS: 50 µ" Au contacts; Sn/Pb alloy terminations 50 µ" Au contacts; Sn plated terminations	1 3 5 7				₹		
HAR	DWAR	E	Ť				
STYLE OF HARDWARE: Two fixed jacknut assemblies (72*) Two turning jackscrews, allen head, captivated** (86*)	00 22 41 42 43 44 45	STYLE OF HARDWARE: None Two fixed jacknut assemblies (62*) Two turning jackscrews, allen head, retaining ring (81*) Two long turning jackscrews, allen head, retaining ring (82*) Two turning jackscrews, slot head, retaining ring (83*) Two long turning jackscrews, slot head, retaining ring (84*) Two turning jackscrews, allen head,	_				
POLARIZATION / WIRING: Standard Body Polarization	00 XX	POLARIZATION / WIRING None For wiring codes, see page MA-3 & MA-4					
OP	TIONS		1				
	SIE .050" Rugged Metal Card Edge Mount Connector mates with MK, ML, MM, MN receptacles) B2-Row (Sizes 9 thru 37) 3-Row (Size 51 & 69) 4-Row (Size 100) BODY STYLE: Plug, straight, card edge, with mounting brackets BODY MATERIAL: Polyphenylene Sulfide with electroless nickel shell Polyphenylene Sulfide with electrodeposited cadmium shell ☑ Polyphenylene Sulfide with hard anodized black shell SE 009, 015, 021, 025, 031, 037, 051, 069, 100 CON TYPE CONTACTS/TERMINATIONS: Pin, surface mount, .062094 pcb thickness (.010 dia) Pin, surface mount, .109140 pcb thickness (.010 dia) PLATING OPTIONS: 50 μ" Au contacts; Sn/Pb alloy terminations ☑ 50 μ" Au contacts; Sn plated terminations HARE STYLE OF HARDWARE: Two fixed jacknut assemblies (72*) Two turning jackscrews, allen head, captivated** (86*) POLARIZATION / WIRING: Standard Body Polarization	## SERIES ## Job Standard Body Polarization SERIES ## Job Standard Body Polarization Month	SERIES .050" Rugged Metal Card Edge Mount Connector mates with MK, ML, MM, MN receptacles) BODY 2-Row (Sizes 9 thru 37) 3-Row (Size 51 & 69) 4-Row (Size 100) 50DY STYLE: Plug, straight, card edge, with mounting brackets Polyphernylene Sulfide with electroless nickel shell Polyphernylene Sulfide with electrodeposited cadmium shell ⊠ Polyphernylene Sulfide with hard anodized black shell SIZE 099, 015, 021, 025, 031, 037, 051, 069, 100 CONTACTS TYPE CONTACTS/TERMINATIONS: Pin, surface mount, .062094 pcb thickness (.010 dia) (.010 dia) Pin, surface mount, .109140 pcb thickness (.010 dia) 2 Socket, straight, 1.000" pigtalis (.018 dia) (.010 dia) PLATING OPTIONS: 50 µ" Au contacts; Sn/Pb alloy terminations ⊠ 50 µ" Au contacts; Sn/Pb alloy terminations (.50 µ" Au contacts; Sn/Pb alloy termination	SERIES .050" Rugged Metal Card Edge Mount Connector mates with MK, ML, MM, MN receptacles) BODY 2-Row (Sizes 9 thru 37) 3-Row (Size 51 & 69) 4-Row (Size 100) BODY STYLE: Plug, straight, card edge, with mounting brackets Polyphenylene Sulfide with electroless nickel shell Polyphenylene Sulfide with hard anodized black shell SIZE 099, 015, 021, 025, 031, 037, 051, 069, 100 CONTACTS TYPE CONTACTS/TERMINATIONS: Pin, surface mount, .109140 pcb thickness (.010 dia) PLATING OPTIONS: 50 μ" Au contacts; Sn/Pb alloy terminations (.010 dia) PLATING OPTIONS: 50 μ" Au contacts; Sn plated terminations STYLE OF HARDWARE: Two fixed jacknut assemblies (72") Two turning jackscrews, allen head, retaining ring (84") Two turning jackscrews, allen head, retaining ring (82") POLARIZATION / WIRING: For wiring codes, see page MA-3 & MA-4 POSODY MM d. 0.50" Rugged Metal I/O Connector (MM mates with MK, ML, MM, MN plugs) MM .050" Rugged Metal I/O Connector (MM mates with MK, ML, MM, MN plugs) BMM .050" Radged Metal I/O Connector (MM mates with MK, ML, MM, MN plugs) BADY MATERIAL: PROPY STYLE: PROPY MATERIAL: Polyphenylene Sulfide with eacro (Size 9 thru 37) Polyphenylene Sulfide with eacr	SERIES	SERIES	SERIES .050" Rugged Metal Card Edge Mount Connector mates with MK, ML, MM, MM receptacles) BODY 2-Row (Sizes 9 thru 37)

^{* =} Use number in parenthesis when ordering size 100.

900 Interfacial sealing gasket

^{** =} Captive hardware is factory installed and non-removable.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub MIL Spec Connectors category:

Click to view products by AirBorn manufacturer:

Other Similar products are found below:

M85049/50-5F MDM-9SH006A 850-056-0812 1218697-4 D38999/26WJ61PC L/C 1484349-1 17D25HV 1996840-1 243082-15 1757682-1 17D-E51218-1 17SDA15S 1883533-1 1883886-1 1883889-1 192900-0377 M24308/8-347 M83513/03-E09C 443961-3 5-1218949-1 550-031NF1R6K 3-1236089-2 550E001NF1R3J0L 550T001NF1R6K0L 557T283NF5B08 DC121073157 443869-3 443869-4 443869-5 550S004NF1R1B0F03 557E283NF1A06 527-019NF0303R2K1F 5-446405-1 550-031NF1R2E 550E003M2R9J0F04 550E003M3R9J0F05 550E024M104R9J0 550E024NF102R3J0B 550E039NF1R3J1-02 550S003M3R9B0F05 550S004M4R7M0F04 550S004NF1R1B1F02 550S008M3F0K0F04 550S086M5R3J0L 550S100NF3F0E 550T001M2R7E0L 550T001NF1F0B1L 550T001NF1R1K0G 550T001NF1R3K0G 550T001NF1R4K0L