

|          |   |          | PLUG:<br>RECEPTACLE:  | NK-1E2-009-325-TH00<br>NM-122-009-261-JCAC<br>XX-XXX-XXX-XXX-XXXX<br> |
|----------|---|----------|---|---|
| PLU      | G   | REC      | EPTACLE   |   |
|          | SEF   |          |   |   |
| NK       | .025" Metal PC Board Mounted Connector  | NM       | .025" Metal I/O Connector   |   |
|          | BODY  |          |   |   |
| 1        | 1-Row   | 1        | 1-Row   |   |
| E        | BODY STYLE:<br>Plug, right angle, plated thru hole (PTH)  | 2        | BODY STYLE:<br>Receptacle, straight   |   |
| 2<br>3   | BODY MATERIAL:<br>Liquid Crystal Polymer w/ electroless nickel shell<br>Liquid Crystal Polymer w/ electrodeposited<br>cadmium shell 🗵 | 2<br>3   | BODY MATERIAL:<br>Liquid Crystal Polymer w/ electroless nickel s<br>Liquid Crystal Polymer w/ electrodeposited<br>cadmium shell 🗵 | shell   |
|          | SL  |          |   |   |
| xxx      | Number of contacts (009, 015, 021, 025, 031,<br>037 or 051)   | XXX      | Number of contacts (009, 015, 021, 025, 031, 037 or 051)  | ,   |
|          | CONT  |          |   |   |
| 33       | TYPE CONTACTS/TERMINATIONS:<br>Pin, right angle, .109"<br>Pin, right angle, .140"<br>Pin, right angle, .172"                          | 26       | TYPE CONTACTS/TERMINATIONS:<br>Socket, straight, crimped wire   |   |
| 5<br>8   | PLATING OPTIONS:<br>50 u" Au contacts; Sn/Pb alloy terminations<br>50 u" Au contacts; Tin plated terminations                         | 1        | PLATING OPTIONS:<br>50 u'' Au contacts  |   |
|          | HARD  |          |   |   |
| 00<br>TH | STYLE OF HARDWARE:<br>None<br>Threaded hole, #0-80 UNF  | 00<br>JC | STYLE OF HARDWARE:<br>None<br>Turning jackscrews, captivated #0-80 UNF*   |   |
| 00       | WIRING OPTIONS:<br>None   | xx       | WIRING OPTIONS:<br>See wiring codes, Page NA-2  |   |

\* = Recommended torque value 1.0 inch-lbs. max.

Ball end hex wrench not recommended Hex wrench key/bit conforming to the requirements of ASME / ANSI-B-18.3 is recommended. .050" hex L-key long arm wrench - order AirBorn p/n CDG14148.

⊠ = Option not RoHS compliant

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub MIL Spec Connectors category:

Click to view products by AirBorn manufacturer:

Other Similar products are found below :

M85049/50-5F 850-056-0812 1218697-4 1484349-1 17D25HV 1996840-1 243082-15 1757682-1 17D-E51218-1 17SDA15S 1883533-1 1883886-1 1883889-1 192900-0377 M24308/8-347 M83513/03-E09C 443961-3 5-1218949-1 550-031NF1R6K 3-1236089-2 550E001NF1R3J0L 550T001NF1R6K0L 557T283NF5B08 DB121073-56 DC121073157 443869-3 443869-4 443869-5 550S004NF1R1B0F03 557E283NF1A06 527-019NF0303R2K1F 5-446405-1 550-031NF1R2E 550E003M2R9J0F04 550E003M3R9J0F05 550E024M104R9J0 550E024NF102R3J0B 550E039NF1R3J1-02 550S003M3R9B0F05 550S004M4R7M0F04 550S004NF1R1B1F02 550S008M3F0K0F04 550S086M5R3J0L 550S100NF3F0E 550T001M2R7E0L 550T001NF1F0B1L 550T001NF1R1K0G 550T001NF1R3K0G 550T001NF1R4K0L 550T001NF2R2K0L