

PLUG: RM332-035-111-5500

PLUG RECEPTACLE

	S	ERIES	
RM	.075" Screw Machine PC Connector	RM	.075" Screw Machine PC Connector
		BODY	
3	3-Row	3	3-Row
1 3	BODY STYLE: Plug, straight, with mounting ears Plug, straight, without mounting ears	6 8	BODY STYLE: Receptacle, right angle, with mounting ears Receptacle, right angle, without mounting ears
2	BODY MATERIAL: Polyphenylene sulfide (PPS)	2	BODY MATERIAL: Polyphenylene sulfide (PPS)
		SIZE	
	011, 023, 035, 047, 059, 071, 080, 092, 104, 122, 140, 152, 182, 206		011, 023, 035, 047, 059, 071, 080, 092, 104, 122, 140, 152, 182, 206

CONTACTS					
TYPE CONTACTS/TERMINATIONS:	1	TYPE CONTACTS/TERMINATIONS:			
10 Pin, straight, dip solder, .109" x .020" dia	44	Socket, right angle, dip solder, .109" x .020" dia			
11 Pin, straight, solder cup	45	Socket, right angle, dip solder, .140" x .020" dia			
12 Pin, straight, dip solder, .140" x .020" dia	46	Socket, right angle, dip solder, .172" x .020" dia			
13 Pin, straight, dip solder, .172" x .020" dia	47	Socket, right angle, dip solder, .250" x .020" dia			
14 Pin, straight, dip solder, .250" x .020" dia					
5 Pin, straight, flex, .093" x .017 dia					
PLATING OPTIONS:	I	PLATING OPTIONS:			
Gold plated termination	1	Gold plated termination			
Pre-tinned termination, SnPb alloy (dip solder	2	Pre-tinned termination, SnPb alloy ☒			
options only) ⊠	3	Pre-tinned termination, SAC305 alloy			
Pre-tinned termination, SAC305 alloy (dip		•			
solder options only)					

HARDWARE

OPTIONS					
	(To be keyed by customer)		(To be keyed by customer)		
70	Same configuration as 01 without Loctite [®]	70	Same configuration as 01 without Loctite [®]		
01	thru 68 are special identifiers, see R-38	01	thru 68 are special identifiers, see R-38		
00	None	00	None		
	POLARIZATION:	1	POLARIZATION		
67	Two turning jacksockets, 490"	67	Two turning jacksockets, .490"		
66	Two turning jackscrews, .490"	66	Two turning jackscrews, .490"		
65	Turning jackset, reversed, .490"	65	Turning jackset, reversed, .490"		
64	Turning jackset, 490"	64	Turning jackset, 490"		
62	Two hex turning jacksockets, .200"	62	Two hex turning jacksockets, .200"		
61	Two hex turning jackscrews, .200"	61	Two hex turning jackscrews, .200"		
60	Hex turning jackset, reversed, .200"	60	Hex turning jackset, reversed, .200"		
59	Hex turning jackset, 200"	59	Hex turning jackset, 200"		
20	Two fixed jacksockets	20	Two fixed jacksockets		
19	Two fixed jackscrews	19	Two fixed jackscrews		
30	Fixed jackset, reversed	30	Fixed jackset, reversed		
29	Fixed jackset	29	Fixed jackset		
58	Two guide sockets	58	Two guide sockets		
57	Two guide pins	57	Two guide pins		
55	Guide set	55	Guide set		
(See R-41 & R-42 for all options) 0256 None		005	(See R-41 & R-42 for all options) 0256 None		
	STYLE OF HARDWARE:		STYLE OF HARDWARE:		

076 PWB mounting holes, .100" dia (cross drilled)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Rectangular MIL Spec Connectors category:

Click to view products by AirBorn manufacturer:

Other Similar products are found below:

M32139/03-B06ST 65002-062 CY4602-000 77058-22-55PN 86.030.0053.0 GMCT26M0E100JC 1241346-1 MSO34MPK1E1

BACC65CAMA HSB-D4S03DM222X 2217548-1 890-009-31SA2-BRT1T 27963-20T12 SIM2N40NC3 SIM2S100A 1604996-2

SMD25PN90L-4055 22628-10-6P-791 GMCT66F0T0000 M32139/03-G05SN CTD160E01F-6148 CTJ112E03B CTJ122E02D-8000 CTJ
3D-12 CTJ920E06N-513 CTL-16-090 CY4600-000 CY4601-000 38111-14-15SN 38112-14-15PN TMN2N037PC2DM018S

TMN2N051SC2DM018T MMA23-0111R1 MMD25-0071P1 33516062020 33526M11-08PE 33526M11-08PN 3355-5869-000 DMC-M99
01AN Y59113WE20PNV00300 ZPF000000000106310 105979-31 MTCPK1PJC02S SIM2N40NC1 SIM2N40NC2 SIM2S110A

SIME2022PNR 787-0015-02 TMN2N009SC2DM018T TMN2N025PC2DM018S