



## Z Series


### Vertical Compression (Z-axis), Open-Pin Field

Contact spacing: 0.050" (1.27 mm)

A high-density, open-field, vertically-compressed connector utilizing a patented z-axis contact system configured for between-board (board-to-board) compression applications.

### DIMENSIONS

COLUMNS	C	D
10	0.952	0.742
15	1.202	0.992
20	1.452	1.242
25	1.702	1.492
ROWS	E	F
2	0.210	0.105
3	0.260	0.105
4	0.310	0.155
5	0.360	0.155
6	0.410	0.205
7	0.460	0.205



HARDWARE HEIGHT (A)	CONTACT HEIGHT (B)
0.100	0.120
0.150	0.170
0.200	0.230
0.250	0.280
0.300	0.330
0.350	0.380

### Sample Part Number Format: RZ250-320-115-1000



**SERIES**  
 Vertical (Z-Axis)  
 Compression  
 Multi-Rows  
 0.050" Spacing  
 Open-Field



**HEIGHT**  
 100 - 0.100"  
 150 - 0.150"  
 200 - 0.200"  
 250 - 0.250"  
 300 - 0.300"  
 350 - 0.350"



**ROWS**  
 2 - 2 Rows  
 3 - 3 Rows  
 4 - 4 Rows  
 5 - 5 Rows  
 6 - 6 Rows  
 7 - 7 Rows



**COLUMNS**  
 10 - 10 Columns  
 15 - 15 Columns  
 20 - 20 Columns  
 25 - 25 Columns



**CONTACT**  
 11 - Double compression



**PLATING**  
 5 - 50 μ" Au  
 3 - 30 μ" Au




**HARDWARE**  
 10 - Ø.090" Thru-hole  
 20 - Ø.050" Guide pin



**TYPE**  
 00 - No polarization





**VARIATION**  
 Blank - None  
 XXX - Consult factory



PLEASE CONSULT THE AIRBORN WEBSITE FOR THE LATEST REVISION OF THIS DOCUMENT PRIOR TO BEGINNING ANY DESIGN WORK.

### MATED HEIGHT

Mated height is defined as the space between the hardware clamping surfaces (top hardware surface to bottom hardware surface.) See Table 1.



### SI DATA - Differential 100 Ohm

1	Diff. Insertion Loss	3.0 GHz @ -3 dB
2	Diff. Return Loss	1.0 GHz @ -20 dB
3	NEXT	2.0 GHz @ -50 dB
4	FEXT	2.0 GHz @ -48 dB

### MATERIALS and FINISHES

Contact: ..... BeCu C17200 per ASTM B194 (brush alloy 190)  
 Contact Finish: ..... Gold per ASTM B488 over nickel per SAE AMS-QQ-N-290  
 Molded Insulator: ..... Glass-filled polyphenylene sulfide (PPS) per MIL-M-24519  
 Hardware: ..... Stainless steel per ASTM A582/582M, passivated per SAE AMS-2700

**NOTE: AirBorn can manufacture special configurations to your exact specifications.**

### PERFORMANCE

Contact Compression: ..... 0.010 inches per side (nominal) for 0.100" and 0.150" connector heights; 0.015" per side (nominal) for 0.200", 0.250", 0.300" and 0.350" connector heights  
 Compression Force: ..... 25-40 grams per contact having a 0.010" deflection  
 35-50 grams per contact having a 0.015" deflection  
 Contact Wipe: ..... ≈0.007" for 0.100" and 0.150" connector heights  
 ≈0.014" for 0.200", 0.250", 0.300" and 0.350" connector heights  
 Current Rating: ..... 0.5 amperes  
 Contact Resistance: ..... 0.025 ohms typical (contact height-dependent)  
 Operating Temperature: ..... -65° C to +125° C  
 Insulation Resistance: ..... 5,000 megaohms minimum @ 100 VDC  
 Durability: ..... 50 connector mating cycles  
 Dielectric Withstanding: ..... 250 VDC @ sea level, 100 VDC @ altitude

**NOTE: Performance values are estimates at this time. Actual values will be determined when final product testing is complete.**

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Board to Board & Mezzanine Connectors](#) category:*

*Click to view products by [AirBorn](#) manufacturer:*

Other Similar products are found below :

[589158040000018](#) [MDF7C-18P-2.54DSA\(55\)](#) [FCN-230C068-11](#) [FCN-268F012-G/BD](#) [FCN-268F036-G/BD](#) [FCN-268M012-G/0D](#) [FCN-268M024-G/1D](#) [FCN-723J004/1](#) [MIS-048-01-F-D-DP-K](#) [832-10-034-10-001000](#) [FX4C-80S-1.27DSA](#) [FCN-214Q030-G/0](#) [FCN-234P048-G/0](#) [FCN-235D050-G/C](#) [210-93-314-41-105000](#) [2-22603-0](#) [MDF7-40DP-2.54DSA\(55\)](#) [AXG720047](#) [5031084030](#) [MIT-114-03-F-D-K](#) [55323-1519](#) [DF33-2P-3.3DSA\(24\)](#) [YFT-20-05-H-03-SB-K](#) [503308-3040](#) [026-6203-PDB](#) [027-6203-PDB](#) [069159702701000](#) [10123981-102LF](#) [101A10019X](#) [55650-0588-C](#) [68684-306](#) [75140-7012](#) [589159005003045](#) [194261-1](#) [FCN-268F024-G0D](#) [10124054-515LF](#) [68685-603](#) [8-1616154-3](#) [MIS-019-01-F-D](#) [589159005002045](#) [541371078](#) [IL-WX-10PB-HF-B-E1000E](#) [FCN-268M024-G/3D](#) [20021832-06016C1LF](#) [KX15-20KLDL-E1000E](#) [MDF7-16DP-2.54DSA\(55\)](#) [AXE810124](#) [FCN-214J100-G/0](#) [FCN-230C068-E/S](#) [AXE812124](#)