



Smart Control and Display SoC

for Automotive and Industrial Products

Overview

T113-S3 is an advanced application processor designed for the automotive and industrial control markets. It integrates dual-core Cortex™-A7 CPU and single-core HiFi4 DSP to provide the high efficient computing power. T113-S3 supports full format decoding such as H.265, H.264, MPEG-1/2/4, JPEG, VC1, and so on. The independent hardware encoder can encode in JPEG or MJPEG. Integrated multi ADCs/DACs and I2S/PCM/DMIC/OWA audio interfaces can provide the perfect voice interaction solution. T113-S3 comes with extensive connectivity to facilitate product expansion, such as USB, SDIO, EMAC, TWI, UART, SPI, PWM, GPADC, IR TX&RX, and so on.


Highlights

- T113-S3 integrates dual-core Cortex™-A7, single-core HiFi4 DSP, SIP 128 MB DDR3, 3 ADCs, 2 DACs, 2 I2S/PCM, and 8 digital microphones, which provides the perfect voice interaction solution.
- The 1080p full format decoding and Allwinner SmartColor 2.0 display enhancement technologies provide excellent video experience for users.
- Rich display output interfaces such as RGB/LVDS/DSI/CVBS OUT meet the requirements of the screen display in differentiated markets.
- The advanced process design with lower voltage and lower leakage, the power optimization design for typical scenes, and the enhanced heat dissipation package, improve the heating experience of the product.
- Industrial level working temperature, 10-years chip life.

Features


CPU	<ul style="list-style-type: none">• Dual-core ARM Cortex™-A7• 32 KB L1 I-cache + 32 KB L1 D-cache per core, and 256 KB L2 cache
DSP	<ul style="list-style-type: none">• Single-core HiFi4• 32 KB I-cache + 32 KB D-cache• 64 KB I-ram + 64 KB D-ram
Memory	<ul style="list-style-type: none">• SIP 128 MB DDR3• SD3.0/eMMC 5.0, SPI Nor/NAND Flash
Video Engine	<p>Video decoding</p> <ul style="list-style-type: none">• H.265 up to 1080p@60fps• H.264 up to 1080p@60fps• MPEG-1/2/4, JPEG, VC1 up to 1080p@60fps <p>Video encoding</p> <ul style="list-style-type: none">• JPEG/MJPEG up to 1080p@60fps• Supports input picture scaler up/down
Display Engine	<ul style="list-style-type: none">• Allwinner SmartColor2.0 post processing for an excellent display experience• Supports de-interlacer (DI) up to 1080p@60fps• Supports G2D hardware accelerator including rotate, mixer, lbc decompression functions
Video OUT	<ul style="list-style-type: none">• CVBS OUT interface, supporting NTSC and PAL format• RGB LCD output interface up to 1920 x 1080@60fps• Dual link LVDS interface up to 1920 x 1080@60fps• 4-lane MIPI DSI interface up to 1920 x 1200@60fps
Video IN	<ul style="list-style-type: none">• 8-bit parallel CSI interface• CVBS IN interface, supporting NTSC and PAL format
Audio	<ul style="list-style-type: none">• 2 DACs and 3 ADCs• Analog audio interfaces: MICIN3P/N, LINEINL/R, FMINL/R, HPOUTL/R• Digital audio interfaces: I2S/PCM, DMIC, OWA IN/OUT
Security Engine	<ul style="list-style-type: none">• AES, DES, 3DES encryption and decryption algorithms• RSA signature verification algorithm• MD5/SHA and HMAC tamper proofing• Hardware random number generator• Integrated 2 Kbits OTP storage space
Connectivity	<ul style="list-style-type: none">• USB2.0 DRD, USB2.0 Host• SDIO 3.0, SPI x 2, UART x 6, TWI x 4• PWM (8-ch), GPADC (1-ch), TPADC (4-ch), IR TX&RX• 10/100/1000M EMAC with RMII and RGMII interfaces
Connectivity	<ul style="list-style-type: none">• eLQFP128, 14 mm x 14 mm

Block Diagram




Application Diagram


Car MP5 Solution




Car Instrument Solution



Industrial Control HMI Solution



Industrial Control PLC Solution



ABOUT ALLWINNER

Allwinner Technology is a leading fabless design company dedicated to smart application processor SoCs and smart analog ICs. Its product line includes multi-core application processors for smart devices and smart power management ICs used by brands worldwide.

With its focus on cutting edge UHD video processing, high performance multi-core CPU/GPU integration, and ultra-low power consumption, Allwinner Technology is a mainstream solution provider for the global tablet, internet TV, smart home device, automotive in-dash device, smart power management, and mobile connected device markets. Allwinner Technology is headquartered in Zhuhai, China.

CONTACT US

For more product info, please contact service@allwinnertech.com, or scan the QR code to follow us on Wechat.

This brief is for reference only and has no commitment. All content contained herein is subject to changes without notice.

©2021 Allwinner Technology Co., Ltd.



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [32-bit Microcontrollers - MCU category](#):

Click to view products by [Allwinner Tech manufacturer](#):

Other Similar products are found below :

[MCF51AC256AVFUE](#) [MCF51AC256BCFUE](#) [MCF51AC256BVFUE](#) [MB91F464AAPMC-GSE2](#) [R5S726B0D216FP#V0](#) [MB91F248PFV-GE1](#) [MB91243PFV-GS-136E1](#) [SAK-TC1782F-320F180HR BA](#) [TC364DP64F300WAAKXUMA1](#) [R5F566NNDDFP#30](#)
[R5F566NNDDFC#30](#) [R5F566NNDDBD#20](#) [MC96F8216ADBN](#) [A96G181HDN](#) [A96G140KNN](#) [A96G174FDN](#) [A31G213CL2N](#)
[A96G148KNN](#) [A96G174AEN](#) [AC33M3064TLBN-01](#) [V3s](#) [T3](#) [A40i-H](#) [V526](#) [A83T](#) [R11](#) [V851s](#) [A133](#) [V833](#) [F1C100S](#) [T3L](#) [T507](#) [A33](#)
[A63](#) [T113-i](#) [H616](#) [V853](#) [V533](#) [R16-J](#) [V536-H](#) [A64-H](#) [V831](#) [V3LP](#) [T113-S3](#) [F1C200S](#) [F133-A](#) [R128-S2](#) [D1-H](#) [ADUCM360BCPZ128-TR](#)
[APT32S003F8PT](#)