

Alpha Wire | 711 Lidgerwood Avenue, Elizabeth, NJ 07207 Tel: 1-800-52 ALPHA (25742), Web: www.alphawire.com

# Customer Specification PART NO. 1857

#### Construction

		Diameters (In)
1) Component 1	1 X 1 HOOKUP	
a) Conductor	18 (7/26) AWG TC	0.048
b) Insulation	0.010" Wall, Nom. PVC	0.068+/- 0.002
(1) Color(s)	WHITE, BLACK, RED, GREEN, YELLOW, BLUE, BROWN ORANGE, SLATE, VIOLET, WHITE/BLACK, WHITE/RED WHITE/GREEN, WHITE/YELLOW, WHITE/BLUE WHITE/BROWN, WHITE/ORANGE, WHITE/SLATE WHITE/VIOLET	

#### **Applicable Specifications**

1) Military	MIL-W-16878E/1	105°C / 600 V <sub>RMS</sub>
-------------	----------------	------------------------------

## Environmental

1) EU Directive 2011/65/EU(RoHS2):		
	All materials used in the manufacture of this part are in compliance with European Directive 2011/65/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment. Consult Alpha Wire's web site for RoHS C of C.	
2) REACH Regulation (EC 1907/2006):		
	This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item. For up-to-date information, please see Alpha's REACH SVHC Declaration.	
3) California Proposition 65:	The outer surface materials used in the manufacture of this part meet the requirements of California Proposition 65.	

### Properties

Physical & Mechanical Properties		
1) Temperature Range	-55 to 105°C	
2) Bend Radius	10X Cable Diameter	
3) Pull Tension	13.9 Lbs, Maximum	
Electrical Properties	(For Engineering purposes only)	
1) Voltage Rating	<sup>600</sup> V <sub>RMS</sub>	
2) Inductance	0.04 μH/ft, Nominal	
3) Conductor DCR	6.3 Ω/1000ft @20°C, Nominal	

#### Other

Packaging	Flange x Traverse x Barrel (inches)	
a) 1000 FT	6.5 x 4 x 2.5 Continuous length	
b) 100 FT	2.75 x 2 x 1.125 Continuous length	
	[Spool dimensions may vary slightly]	
Notes:		
a) Certain colors and put-up combinations may only be available by special order, minimums may apply.		

#### www.alphawire.com

Alpha Wire | 711 Lidgerwood Avenue, Elizabeth, NJ 07207

Tel: 1-800-52 ALPHA (25742)

Although Alpha Wire ("Alpha") makes every reasonable effort to ensure there accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha had been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.



#### **EU/China ROHS CERTIFICATE OF COMPLIANCE**

To Whom It May Concern:

Alpha Wire Part Number: 1857

1857, RoHS-Compliant Commencing With 1/1/2005 Production

Note: all colors and put-ups

This document certifies that the Alpha part number cited above is manufactured in accordance with Directive 2011/65/EU of the European Parliament, better known as the RoHS Directive (commonly known as RoHS 2), with regards to restrictions of the use of certain hazardous substances used in the manufacture of electrical and electronic equipment. This certification extends to amending Directive 2015/863/EU which expanded the list of restricted substances to 10 items (commonly known as RoHS 3) The reader is referred to these Directives for the specific definitions and extents of the Directives. **No Exemptions are required for RoHS Compliance on this item**. Additionally, Alpha certifies that the listed part number is in compliance with China RoHS "Marking for Control of Pollution by Electronic Information Products" standard SJ/T 11364-2014.

Substance	Maximum Control Value
Lead	0.1% by weight (1000 ppm)
Mercury	0.1% by weight (1000 ppm)
Cadmium	0.01% by weight (100 ppm)
Hexavalent Chromium	0.1% by weight (1000 ppm )
Polybrominated Biphenyls (PBB)	0.1% by weight (1000 ppm)
Polybrominated Diphenyl Ethers (PBDE),	
Including Deca-BDE	0.1% by weight (1000 ppm)
Bis(2-ethylhexyl) phthalate (DEHP)	0.1% by weight (1000 ppm)
Butyl benzyl phthalate (BBP)	0.1% by weight (1000 ppm)
Dibutyl phthalate (DBP)	0.1% by weight (1000 ppm)
Diisobutyl phthalate (DIBP)	0.1% by weight (1000 ppm)

The information provided in this document and disclosure is correct to the best of Alpha Wire's knowledge, information and belief at the date of its release. The information provided is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it will become part of. The intent of this document is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Authorized Signatory for the Alpha Wire:

Dave Watson, Director of Engineering & QA Alpha Wire 711 Lidgerwood Ave. Elizabeth, NJ 07207 Tel: 1-908-925-8000 9/11/2020

#### **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Hook-up Wire category:

Click to view products by Alpha manufacturer:

Other Similar products are found below :

 8918-BRN-1000
 8920-DK-BLU-1000
 CR6328-000
 01776.38.01
 M22759/16-14-5-500FT
 7053-RED-1000
 7053-SLATE-1000
 F25935-000

 F60898-000
 8055
 81044/12-18-9CS3209
 82A0811-4-9-G110
 83004-ORG-1000
 83004-YEL-100
 83005-LT-BLU-1000
 83025-VIO-1000

 8523-RED-100
 8524-WHT-100
 8525-ORG-1000
 8530-BLK-1000
 8530-LT-BLU-100
 8538-009-1000
 8597-LT-BLU-100
 8898-BLK-100

 138498-000
 E76065-000
 EPD50886A-20-9
 BFWUL3239-24-PINK
 C2015A.12.08
 C2015A.12.10
 C2016A.12.05

 C2016A.12.07
 C2065A.12.02
 C77653-000
 220368-001
 8916-GRY-500
 8918-RED-100
 8919-DK-BLU-1000
 8919-YEL-100
 8920-YEL-100

 9242833001
 933205-000
 282257-000
 2841/7-YELLOW-1000
 2842/7-ORANGE-100
 2842/7-RED-1000
 2843/19-BLUE-100
 2843/1 

 YELLOW-100
 2844/7-BLACK-1000
 100
 100
 100
 100
 100
 100
 100
 100
 100
 100
 100
 100
 100
 100
 100
 100
 100
 100
 100
 100
 100
 100
 100
 100