

Request a Sample

Customer Specification PART NO. 391640

Construction

		Diameters (In)		
1) Component 1	1 X 1 HOOKUP			
a) Conductor	16 (26/30) AWG TC	0.060		
b) Insulation	0.040" Wall, Nom. Silicone Rubber	0.140+/- 0.004		
(1) Print	16 AWG RU AWM STYLE 3239 150C 10	16 AWG RU AWM STYLE 3239 150C 10KVDC VW-1 EXXXXX		
(2) Color(s)	WHITE, BLACK, RED	WHITE, BLACK, RED		

Applicable Specifications

1) UL	AWM/STYLE 3239	150°C / 10K V _{DC}
-------	----------------	-----------------------------

Environmental

1) EU Directive 2011/65/EU(RoHS2), EU Directive 2015/863/EU (RoHS3):		
	All materials used in the manufacture of this part are in compliance with European Directive 2011/65/EU and the amending Directive 2015/863/EU of 4 June 2015 regarding the restriction of use of certain hazardous substances in electrical and electronic equipment.	
2) REACH Regulation (EC 1907/2006):		
	This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item.	

Properties

Physical & Mechanical Properties		
1) Temperature Range	-40 to 150°C	
2) Bend Radius	10X Cable Diameter	
3) Pull Tension	20.4 Lbs, Maximum	
Electrical Properties	(For Engineering purposes only)	
1) Voltage Rating	10000 V _{DC}	
2) Inductance	0.07 μH/ft, Nominal	
3) Conductor DCR	4.4 Ω/1000ft @20°C, Nominal	

Other

Packaging	Flange x Traverse x Barrel (inches)	
a) 1000 FT	12 x 4.5 x 3.5 Continuous length	
b) 500 FT	6.5 x 6 x 1.9 Continuous length	
c) 100 FT	6.5 x 2 x 1.9 Continuous length	
d) Bulk(Made-to-order)		
	[Spool dimensions may vary slightly]	
Notes:		
a) Certain colors and put-up combinations may only be available by special order, minimums may apply.		

www.alphawire.com

Alpha Wire | 711 Lidgerwood Avenue, Elizabeth, NJ 07207

Tel: 1-800-52 ALPHA (25742)

Although Alpha Wire ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha had been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

ALPHA WIRE - CONFIDENTIAL AND PROPRIETARY

Notice to persons receiving this document and/or technical information. This document is confidential and is the exclusive property of ALPHA WIRE, and is merely on loan and subject to recall by ALPHA WIRE at any time. By taking possession of this document, the recipient acknowledges and agrees that this document cannot be used in any manner adverse to the interests of ALPHA WIRE, and that no portion of this document may be copied or otherwise reproduced without the prior written consent of ALPHA WIRE. In the case of conflicting contractual provisions, this notice shall govern the status of this document. ©2013 ALPHA WIRE - all rights reserved.



EU/China ROHS CERTIFICATE OF COMPLIANCE

To Whom It May Concern:

Alpha Wire Part Number: 391640

391640, RoHS-Compliant Commencing With 7/1/2005 Production

Note: all colors and put-ups

This document certifies that the Alpha part number cited above is manufactured in accordance with Directive 2011/65/EU of the European Parliament, better known as the RoHS Directive (commonly known as RoHS 2), with regards to restrictions of the use of certain hazardous substances used in the manufacture of electrical and electronic equipment. This certification extends to amending Directive 2015/863/EU which expanded the list of restricted substances to 10 items (commonly known as RoHS 3) The reader is referred to these Directives for the specific definitions and extents of the Directives. **No Exemptions are required for RoHS Compliance on this item**. Additionally, Alpha certifies that the listed part number is in compliance with China RoHS "Marking for Control of Pollution by Electronic Information Products" standard SJ/T 11364-2014.

Substance	Maximum Control Value
Lead	0.1% by weight (1000 ppm)
Mercury	0.1% by weight (1000 ppm)
Cadmium	0.01% by weight (100 ppm)
Hexavalent Chromium	0.1% by weight (1000 ppm)
Polybrominated Biphenyls (PBB)	0.1% by weight (1000 ppm)
Polybrominated Diphenyl Ethers (PBDE) ,	
Including Deca-BDE	0.1% by weight (1000 ppm)
Bis(2-ethylhexyl) phthalate (DEHP)	0.1% by weight (1000 ppm)
Butyl benzyl phthalate (BBP)	0.1% by weight (1000 ppm)
Dibutyl phthalate (DBP)	0.1% by weight (1000 ppm)
Diisobutyl phthalate (DIBP)	0.1% by weight (1000 ppm)

The information provided in this document and disclosure is correct to the best of Alpha Wire's knowledge, information and belief at the date of its release. The information provided is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it will become part of. The intent of this document is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Authorized Signatory for the Alpha Wire:

Dave Watson, Director of Engineering & QA

Alpha Wire

711 Lidgerwood Ave. Elizabeth, NJ 07207 Tel: 1-908-925-8000 4/24/2020

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Hook-up Wire category:

Click to view products by ALPHA manufacturer:

Other Similar products are found below:

8918-BRN-1000 8920-DK-BLU-1000 CR6328-000 01776.38.01 M22759/16-14-5-500FT 7053-RED-1000 7053-SLATE-1000 F25935-000 F60898-000 8055 81044/12-18-9CS3209 82A0811-4-9-G110 83004-ORG-1000 83005-LT-BLU-1000 83025-VIO-1000 8523-RED-100 8524-WHT-100 8525-ORG-1000 8530-BLK-1000 8530-LT-BLU-100 8538-009-1000 8597-LT-BLU-100 8898-BLK-100 138498-000 E76065-000 EPD50886A-20-9 BFWUL3239-24-PINK C2015A.12.05 C2015A.12.08 C2015A.12.10 C2015A.12.19 C2016A.12.05 C2016A.12.07 C2065A.12.02 C77653-000 220368-001 8916-GRY-500 8918-RED-100 8919-DK-BLU-1000 8919-YEL-100 8920-YEL-100 9242833001 933205-000 2841/7-YELLOW-1000 2842/7-ORANGE-100 2842/7-RED-1000 2843/19-BLUE-100 2843/1-YELLOW-100 2844/7-BLACK-1000 2845/7-RED-100