

# Customer Specification PART NO. 391650

#### Construction

		Diameters (In)
1) Component 1	1 X 1 HOOKUP	
a) Conductor	16 (26/30) AWG TC	0.060
b) Insulation	0.050" Wall, Nom. Silicone Rubber	0.160+/- 0.006
(1) Print	16 AWG RU AWM STYLE 3239 150C 20KVDC VW-1 EXXXXX	
(2) Color(s)	WHITE, BLACK, RED	

# **Applicable Specifications**

1) UL	AWM/STYLE 3239	150°C / 20K V <sub>DC</sub>

### Environmental

1) EU Directive 2011/65/EU(RoHS2):		
	All materials used in the manufacture of this part are in compliance with European Directive 2011/65/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment. Consult Alpha Wire's web site for RoHS C of C.	
2) REACH Regulation (EC 1907/2006):		
	This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item. For up-to-date information, please see Alpha's REACH SVHC Declaration.	

## **Properties**

Physical & Mechanical Properties		
1) Temperature Range	-40 to 150°C	
2) Bend Radius	10X Cable Diameter	
3) Pull Tension	20.4 Lbs, Maximum	
Electrical Properties	(For Engineering purposes only)	
1) Voltage Rating	20000 V <sub>DC</sub>	
2) Inductance	0.07 μH/ft, Nominal	
3) Conductor DCR	4.4 Ω/1000ft @20°C, Nominal	

#### Other

Packaging	Flange x Traverse x Barrel (inches)		
a) 1000 FT	12 x 4.5 x 3.5 Continuous length		
b) 500 FT	12 x 4.5 x 3.5 Continuous length		
c) 100 FT	6.5 x 2 x 1.9 Continuous length		
d) Bulk(Made-to-order)			
	[Spool dimensions may vary slightly]		
Notes:			
a) Certain colors and put-up combinations may only be available by special order, minimums may apply.			

#### www.alphawire.com

Alpha Wire | 711 Lidgerwood Avenue, Elizabeth, NJ 07207

Tel: 1-800-52 ALPHA (25742)

Although Alpha Wire ("Alpha") makes every reasonable effort to ensure there accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha had been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

ALPHA WIRE - CONFIDENTIAL AND PROPRIETARYNotice to persons receiving this document and/or technical information. This document is confidential and is the exclusive property of ALPHA WIRE, and is merely on loan and subject to recall by ALPHA WIRE at any time. By taking possession of this document, the recipient acknowledges and agrees that this document cannot be used in any manner adverse to the interests of ALPHA WIRE, and that no portion of this document may be copied or otherwise reproduced without the prior written consent of ALPHA WIRE. In the case of conflicting contractual provisions, this notice shall govern the status of this document. <br/>
- Spr /> CD 19 ALPHA WIRE - all rights reserved.



### **EU/China ROHS CERTIFICATE OF COMPLIANCE**

To Whom It May Concern:

Alpha Wire Part Number: 391650

391650, RoHS-Compliant Commencing With 7/1/2005 Production

Note: all colors and put-ups

This document certifies that the Alpha part number cited above is manufactured in accordance with Directive 2011/65/EU of the European Parliament, better known as the RoHS Directive (commonly known as RoHS 2), with regards to restrictions of the use of certain hazardous substances used in the manufacture of electrical and electronic equipment. This certification extends to amending Directive 2015/863/EU which expanded the list of restricted substances to 10 items (commonly known as RoHS 3) The reader is referred to these Directives for the specific definitions and extents of the Directives. **No Exemptions are required for RoHS Compliance on this item**. Additionally, Alpha certifies that the listed part number is in compliance with China RoHS "Marking for Control of Pollution by Electronic Information Products" standard SJ/T 11364-2014.

Substance	Maximum Control Value
Lead	0.1% by weight (1000 ppm)
Mercury	0.1% by weight (1000 ppm)
Cadmium	0.01% by weight (100 ppm)
Hexavalent Chromium	0.1% by weight (1000 ppm )
Polybrominated Biphenyls (PBB)	0.1% by weight (1000 ppm)
Polybrominated Diphenyl Ethers (PBDE) ,	
Including Deca-BDE	0.1% by weight (1000 ppm)
Bis(2-ethylhexyl) phthalate (DEHP)	0.1% by weight (1000 ppm)
Butyl benzyl phthalate (BBP)	0.1% by weight (1000 ppm)
Dibutyl phthalate (DBP)	0.1% by weight (1000 ppm)
Diisobutyl phthalate (DIBP)	0.1% by weight (1000 ppm)

The information provided in this document and disclosure is correct to the best of Alpha Wire's knowledge, information and belief at the date of its release. The information provided is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it will become part of. The intent of this document is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Authorized Signatory for the Alpha Wire:

Dave Watson, Director of Engineering & QA

8/12/2020

Alpha Wire

711 Lidgerwood Ave. Elizabeth, NJ 07207

Tel: 1-908-925-8000

#### **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Hook-up Wire category:

Click to view products by Alpha manufacturer:

Other Similar products are found below:

002333-000 M81044/12-22-6 M81044/9-8-9 743094-001 81044/12-18-9CS3209 8538-009-1000 ATFC0311-20-5D EF5675-000
BFWUL3239-24-PINK 22759/34-16-9CS2621 22759/42-24-9CS2620 933205-000 284711-000 961473-000 30802-009-250 99M0111-20-2
A00594-000 190571-000 22759/41-12-9CS2620 22759/41-16-9CS2620 22759/43-10-9CS2873 265925-000 CM9524-000 31510-010-250
31514-009-500 32412-009-500 34401-010-250 34402-010-500 M81044/9-4-9 391441-BK007 400R0111-10-9 431660-000 ATFC0311-20-0
ATFC0311-20-3 44/7024-26-9-9 44A0112-22-9CS3184 456157-000 BFW-UL3239-24-WHITE 55/0312-26-6L-CS2570 55A0811-12-9
55A6087-20-9-9-9 55A6315-22-9-9CS2632 55A7400-22-9/96-9CS2275 55A9002-30-5 55PC0211-20-5CS2502 55PC0811-6-9CS2637
55PC1211-22-9-9CS3278 C07683-000 32820-009-5000 34020-008-2000