

# Customer Specification PART NO. 914-CN

#### Construction

Box Configuration			
Box Configuration	M12		
Body Style	Plastic		
Ports	6		
Channels Per Port	2		
LED	YES		
Code Type	А		
Housing	Orange TPU, flame retardant		
Contact	Copper Alloy, Gold Plated		
Receptacle Shell	Copper Alloy, Nickel Plated		
O-Ring	FKM		
Cable Construction			
Conductor Size			
Jacket Material			
OD			
Color			
C-Track Suitable			
DistBox Length	Connectorized		

# **Applicable Specifications**

Ingress Protection	IP67/NEMA 6P

## Environmental

All materials used in the manufacture of this part meet the requirements of European Directive 2011/65/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment. Exemption used; 6a.

This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item.

#### **Properties**

Operating Temperature	-15C (+5F)/ +80C (+176F)
Contact Resistance	≤ 5 mΩ
Voltage Rating	10-30V DC
Current Voltage Rating	4A per port/12A max. Total

#### Other

Accessories Included	2 Dust Covers for unused sockets 10 Attachable labels
Ordering Information	5M- 5 Meters 10M- 10 Meters CN- Connectorized
Quantity	Each

#### www.alphawire.com

Alpha Wire | 711 Lidgerwood Avenue, Elizabeth, NJ 07207

Tel: 1-800-52 ALPHA (25742)

Although Alpha Wire ("Alpha") makes every reasonable effort to ensure there accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha had been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

ALPHA WIRE - CONFIDENTIAL AND PROPRIETARYNotice to persons receiving this document and/or technical information. This document is confidential and is the exclusive property of ALPHA WIRE, and is merely on loan and subject to recall by ALPHA WIRE at any time. By taking possession of this document, the recipient acknowledges and agrees that this document cannot be used in any manner adverse to the interests of ALPHA WIRE, and that no portion of this document may be copied or otherwise reproduced without the prior written consent of ALPHA WIRE. In the case of conflicting contractual provisions, this notice shall govern the status of this document. <br/>
- Spr /> CD 19 ALPHA WIRE - all rights reserved.



## **EU/China ROHS CERTIFICATE OF COMPLIANCE**

To Whom It May Concern:

Alpha Wire Part Number: 914-CN

914-CN, RoHS-Compliant Commencing With 9/21/2016 Production

Note: all colors and put-ups

This document certifies that the Alpha part number cited above is manufactured in accordance with Directive 2011/65/EU of the European Parliament, better known as the RoHS Directive (commonly known as RoHS 2), with regards to restrictions of the use of certain hazardous substances used in the manufacture of electrical and electronic equipment. This certification extends to amending Directive 2015/863/EU which expanded the list of restricted substances to 10 items (commonly known as RoHS 3) The reader is referred to these Directives for the specific definitions and extents of the Directives. **No Exemptions are required for RoHS Compliance on this item**. Additionally, Alpha certifies that the listed part number is in compliance with China RoHS "Marking for Control of Pollution by Electronic Information Products" standard SJ/T 11364-2014.

Substance	Maximum Control Value
Lead	0.1% by weight (1000 ppm)
Mercury	0.1% by weight (1000 ppm)
Cadmium	0.01% by weight (100 ppm)
Hexavalent Chromium	0.1% by weight (1000 ppm )
Polybrominated Biphenyls (PBB)	0.1% by weight (1000 ppm)
Polybrominated Diphenyl Ethers (PBDE) ,	
Including Deca-BDE	0.1% by weight (1000 ppm)
Bis(2-ethylhexyl) phthalate (DEHP)	0.1% by weight (1000 ppm)
Butyl benzyl phthalate (BBP)	0.1% by weight (1000 ppm)
Dibutyl phthalate (DBP)	0.1% by weight (1000 ppm)
Diisobutyl phthalate (DIBP)	0.1% by weight (1000 ppm)

The information provided in this document and disclosure is correct to the best of Alpha Wire's knowledge, information and belief at the date of its release. The information provided is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it will become part of. The intent of this document is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Authorized Signatory for the Alpha Wire:

Dave Watson, Director of Engineering & QA

9/29/2020

Alpha Wire

711 Lidgerwood Ave. Elizabeth, NJ 07207

Tel: 1-908-925-8000

#### **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Power Outlet Strips category:

Click to view products by Alpha manufacturer:

Other Similar products are found below:

G20IG606 1301430288 1301430321 1447B163 UL602CB-6 UL7408-6 ULHC4-15 V20IG606 UL2063BD TSB 4748.03 4309 UL7208
15 3083 3050F 3090 1301350158 1301350173 3085-10 1583H8B1BKV 1589H77D1JV 1589H77G1JV 1589H8D1BKRRV

1589H8G1BKRRV DTEL2 TLP712B STRIKER TLM825SA UL620-15 3SP 1301370166 130143-0153 1301370216 602 6SP 1584B10

1589H48G1 1589T6D1 1301350185 1301350186 1301350187 1301350197 1301350233 1301350234 1301350201 1301350207

1301350209 1301350211 1301350213 1301350216