

Alpha Wire | 711 Lidgerwood Avenue, Elizabeth, NJ 07207 Tel: 1-800-52 ALPHA (25742), Web: www.alphawire.com

Customer Specification PART NO. FIT-600-7/8

Construction

1) Tubing Type	Heat Shrinkable Tubing
2) Tubing Material	Chlorinated Polyolefin
3) Minimum Supplied ID(In)	0.875
4) Maximum Recovered ID (In)	0.500
5) Nominal Recovered Wall Thickness(In)	0.065
6) Color(s)	BLACK

Applicable Specifications

1) Other	AMS-DTL-23053/1 Class 1 and 2	
	Flammability - Passes	

Environmental

1) EU Directive 2011/65/EU(RoHS2):			
	All materials used in the manufacture of this part are in compliance with European Directive 2011/65/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment. Consult Alpha Wire's web site for RoHS C of C.		
2) REACH Regulation (EC 1907/2006):			
	This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item. For up-to-date information, please see Alpha's REACH SVHC Declaration.		
3) California Proposition 65:	The outer surface materials used in the manufacture of this part meet the requirements of California Proposition 65.		

Properties

Physical & Mechanical Properties				
1) Temperature Range	-75 to 121°C			
2) Shrink Ratio	Approximately 2:1			
3) Full Recovery Temperature	130°C			
4) Minimum Shrink Temperature	130°C			
5) Tensile Strength	1500psi, Min	ASTM D638		
6) Elongation	250%, Min	ASTM D638		
7) Low Temperature Flex(-75°C)	no cracking	AMS-DTL-23053		
8) Heat Resistance(150°C,168hrs)	200% Elongation, Min	ASTM D638		
9) Heat Shock(200°C,4hrs)	no cracking	AMS-DTL-23053		
10) Longitudinal Change	+1%/-10%	AMS-DTL-23053		
11) Specific Gravity	1.30, Max	ASTM D792		
12) Shelf Life	1 Years @ 18 to 35°C			
Electrical Properties				
1) Dielectric Strength	300 V/mil, Min	ASTM D876		
2) Volume Resistivity	1x10 ¹¹ ohm-cm, Min	ASTM D876		
Chemical Properties				
1) Water Absorption	1.00%, Max	ASTM D570		
2) Corrosion(150°C,16hrs)	no corrosion	AMS-DTL-23053		
3) Fluid Resistance(23°C,24 Hrs)	1000 PSI, Min	AMS-DTL-23053		
4) Fungus Resistance	Pass	AMS-DTL-23053		
5) Halogen Free	No			
6) Lead Free	Yes			

Other

Packaging

www.alphawire.com Alpha Wire | 711 Lidgerwood Avenue, Elizabeth, NJ 07207

Tel: 1-800-52 ALPHA (25742)

Although Alpha Wire ("Alpha") makes every reasonable effort to ensure there accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha had been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.



EU/China ROHS CERTIFICATE OF COMPLIANCE

To Whom It May Concern:

Alpha Wire Part Number: FIT-600-7/8

FIT-600-7/8, RoHS-Compliant Commencing With 3/1/2006 Production

Note: all colors and put-ups

This document certifies that the Alpha part number cited above is manufactured in accordance with Directive 2011/65/EU of the European Parliament, better known as the RoHS Directive (commonly known as RoHS 2), with regards to restrictions of the use of certain hazardous substances used in the manufacture of electrical and electronic equipment. This certification extends to amending Directive 2015/863/EU which expanded the list of restricted substances to 10 items (commonly known as RoHS 3) The reader is referred to these Directives for the specific definitions and extents of the Directives. **No Exemptions are required for RoHS Compliance on this item**. Additionally, Alpha certifies that the listed part number is in compliance with China RoHS "Marking for Control of Pollution by Electronic Information Products" standard SJ/T 11364-2014.

Substance	Maximum Control Value
Lead	0.1% by weight (1000 ppm)
Mercury	0.1% by weight (1000 ppm)
Cadmium	0.01% by weight (100 ppm)
Hexavalent Chromium	0.1% by weight (1000 ppm)
Polybrominated Biphenyls (PBB)	0.1% by weight (1000 ppm)
Polybrominated Diphenyl Ethers (PBDE),	
Including Deca-BDE	0.1% by weight (1000 ppm)
Bis(2-ethylhexyl) phthalate (DEHP)	0.1% by weight (1000 ppm)
Butyl benzyl phthalate (BBP)	0.1% by weight (1000 ppm)
Dibutyl phthalate (DBP)	0.1% by weight (1000 ppm)
Diisobutyl phthalate (DIBP)	0.1% by weight (1000 ppm)

The information provided in this document and disclosure is correct to the best of Alpha Wire's knowledge, information and belief at the date of its release. The information provided is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it will become part of. The intent of this document is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Authorized Signatory for the Alpha Wire:

Dave Watson, Director of Engineering & QA Alpha Wire 711 Lidgerwood Ave. Elizabeth, NJ 07207 Tel: 1-908-925-8000 9/29/2020

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Heat Shrink Tubing and Sleeves category:

Click to view products by Alpha manufacturer:

Other Similar products are found below :

 5685710001
 CR9960-000
 5734012004
 607381P039
 611112-000
 6284592002
 CX4711-000
 CZ1420-000
 D-306-38
 770-006S302
 770

 010Y106W1
 770-018S103
 770-018S202W1
 770-018S205W1
 770-020S705
 MFP-1/4"-Clear
 MFP-3/64"-Clear
 790-3012

 MHHT-4-15K2-G-104
 8003012003
 MIL-LT-1/2-4-SP
 MIL-LT-1/2-9-STK
 MIL-LT-3/-2-STK
 MIL-LT-3/-0-SP
 MIL-LT-3/32-0-SP

 MIL-LT-3/32-6-SP
 MIL-LT-3/4-4-STK
 MIL-LT-3/4-6-SP
 839602-000
 8423-6
 FP301-116-48"-Clear
 FP301-12-6"-Clear
 FP301-1/4-48"

 White-Hdr
 FP301-18-48"-Black-Hdr
 FP301-1/8-6"-Black
 FP301-18-6"-Black-Bulk
 FP301-316-48"-Blue-Hdr
 FP301-34-48"-Green-Hdr

 912229N002
 R280637030
 HDT-0300-48A-BLACK
 HDT-0400-48A-Black
 HDT-0800-48A-RED
 HDT1100-48A-BLK
 HDT1500-48A-BLK

 HDT-2000-48A-Black
 RHW-70/20-1200/ADH-0
 DWP-125-0.450-4-55MM-CS879
 156082-000
 156082-000