## ALPHA WIRE COMPANY CUSTOMER PRODUCT SPECIFICATION

| Part Numbers:   | PPS7-PPS16 |
|-----------------|------------|
| Spec Number:    | PPS        |
| Page 1 of 1 Pag | jes        |

## Issue: 1 Issue Date: 11/01/2017

Effective Date: 11/13/2017

### A. Technical Details

| 1) | Material   |                         |          |      |
|----|--|-------------------------|----------|------|
|    | a) Body  | PA 6 (Polyamide 6)      |          |      |
|    | b) Cap   | PA 6 (Polyamide 6)      |          |      |
|    | c) Seal  | CR (Chloroprene Rubber) |          |      |
| 2) | Color  |                         |          |      |
|    | a) Gray, RAL 7001                                |                         | 5        |      |
| 3) | Protection Class                                 |                         |          |      |
|    | a) IP 68   | 5 Bar, 30 min           |          |      |
|    | b) IP 66   |                         |          |      |
| 4) | Flammability                                     |                         |          | Cap  |
|    | a) V2  | (According to UL94)     |          |      |
| 5) | Temperature Rating                               |                         |          |      |
|    | a) Permanent                                     | -20°C to +100°C         |          |      |
|    | b) Intermittent                                  | -30°C to +150°C         | Chall In |      |
| 6) | Thread Type                                      |                         |          |      |
|    | <ul> <li>a) PG according to DIN 40430</li> </ul> |                         |          | SW   |
| 7) | Approvals  |                         |          | Body |
|    | a) UL  | UL 514                  |          |      |
|    | b) CSA   | CSA C22.2               | π        |      |
|    |  |                         |          |      |
|    |  |                         | TD       |      |

| Size    | Clamping Range<br>Ø min-max |             | Thread LengthThread ØTLTD |       |      | Spanner Width<br>SW CAP SW BODY |    |       | Outer Ø<br>D |       | Max. Height<br>H |       | Part<br>Number |       |       |
|---------|-----------------------------|-------------|---------------------------|-------|------|---------------------------------|----|-------|--------------|-------|------------------|-------|----------------|-------|-------|
|         | mm                          | inch        | mm                        | inch  | mm   | inch                            | mm | Inch  | mm           | Inch  | mm               | inch  | mm             | inch  |       |
| PG 7    | 3,0-6,5                     | 0.118-0.256 | 8,0                       | 0.315 | 12,5 | 0.492                           | 15 | 0.591 | 15           | 0.591 | 17,2             | 0.677 | 57,5           | 2.264 | PPS7  |
| PG 9    | 4,0-8,0                     | 0.157-0.315 | 8,0                       | 0.315 | 15,2 | 0.598                           | 19 | 0.748 | 19           | 0.748 | 21,8             | 0.858 | 69,4           | 2.732 | PPS9  |
| PG 11   | 5,0-10,0                    | 0.197-0.394 | 8,0                       | 0.315 | 18,6 | 0.732                           | 22 | 0.866 | 22           | 0.866 | 25,3             | 0.996 | 81,6           | 3.213 | PPS11 |
| PG 13.5 | 6,0-12,0                    | 0.236-0.473 | 10,0                      | 0.394 | 20,4 | 0.803                           | 24 | 0.945 | 24           | 0.945 | 27,6             | 1.087 | 93,5           | 3.681 | PPS13 |
| PG16    | 10,0-14,0                   | 0.394-0.551 | 10,0                      | 0.394 | 22,5 | 0.886                           | 27 | 1.063 | 27           | 1.063 | 31,1             | 1.224 | 106,0          | 4.173 | PPS16 |

#### **B.** Packaging Requirements

1) Standard Package

10 glands per package

Although Alpha Wire ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

711 Lidgerwood Ave Elizabeth, NJ 07207-0711

Toll Free 1-800-52 ALPHA • T: 1-908-925-8000 • F: 908-925-5411 • Email: info@alphawire.com

www.alphawire.com

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Cable Glands, Strain Reliefs & Cord Grips category:

Click to view products by Alpha manufacturer:

Other Similar products are found below :

 1218
 1300980012
 1300980105
 DBZM-6828
 1498
 915
 300623
 5632NM
 1124
 1151
 561-MP6P4WH
 5534M
 9000005073
 5315817
 N16

 025
 0112
 1
 N16
 020
 0112
 1
 M6106
 7422
 NG-9516
 Gasket
 N16
 016
 0112
 1
 NG-9514
 Gasket
 52001894
 53018160
 APGPG36BA

 1300990004
 02A242
 4136
 SR2
 SR1
 M3249
 THA.450.A0E
 THA.450.B1E
 THA.451.C0E
 THA.451.C1E
 THA.452.B1E

 1427NCGM40G
 GCL1001-H
 GCL1001-J
 GC1001-C
 GC1001-D
 GC1001-E
 GC1001-G
 GC2000-D
 GC2000-E
 GC2000-F

 GC2000-H
 GC2000-L
 GC2000-L
 GC2000-L
 GC2000-L
 GC2000-L
 GC2000-L