

General Description




The AO4614B uses advanced trench technology MOSFETs to provide excellent $R_{DS(ON)}$ and low gate charge. The complementary MOSFETs may be used in H-bridge, Inverters and other applications.

Product Summary

| N-Channel | P-Channel |
|-----------------------------|----------------------------|
| V_{DS} (V) = 40V, | -40V |
| I_D = 6A (V_{GS} =10V) | -5A (V_{GS} =-10V) |
| $R_{DS(ON)}$ | |
| < 30mΩ (V_{GS} =10V) | < 45mΩ (V_{GS} = -10V) |
| < 38mΩ (V_{GS} =4.5V) | < 63mΩ (V_{GS} = -4.5V) |
| 100% UIS Tested | 100% UIS Tested |
| 100% R_g Tested | 100% R_g Tested |



SOIC-8



Absolute Maximum Ratings $T_A=25^\circ\text{C}$ unless otherwise noted

| Parameter | Symbol | Max n-channel | Max p-channel | Units |
|---|----------------|---------------|---------------|-------|
| Drain-Source Voltage | V_{DS} | 40 | -40 | V |
| Gate-Source Voltage | V_{GS} | ± 20 | ± 20 | V |
| Continuous Drain Current ^A | I_D | 6 | -5 | A |
| $T_A=70^\circ\text{C}$ | | 5 | -4 | |
| Pulsed Drain Current ^B | I_{DM} | 30 | -30 | |
| Avalanche Current ^B | I_{AR} | 14 | -20 | |
| Repetitive avalanche energy $L=0.1\text{mH}$ ^B | E_{AR} | 9.8 | 20 | mJ |
| Power Dissipation ^A | P_D | 2 | 2 | W |
| $T_A=70^\circ\text{C}$ | | 1.28 | 1.28 | |
| Junction and Storage Temperature Range | T_J, T_{STG} | -55 to 150 | -55 to 150 | °C |

Thermal Characteristics: n-channel and p-channel

| Parameter | Symbol | Device | Typ | Max | Units |
|--|-----------------|--------|-----|------|-------|
| Maximum Junction-to-Ambient ^A | $R_{\theta JA}$ | n-ch | 48 | 62.5 | °C/W |
| Steady-State | | n-ch | 74 | 110 | °C/W |
| Maximum Junction-to-Lead ^C | $R_{\theta JL}$ | n-ch | 35 | 50 | °C/W |
| Maximum Junction-to-Ambient ^A | $R_{\theta JA}$ | p-ch | 48 | 62.5 | °C/W |
| Steady-State | | p-ch | 74 | 110 | °C/W |
| Maximum Junction-to-Lead ^C | $R_{\theta JL}$ | p-ch | 35 | 50 | °C/W |

N Channel Electrical Characteristics ($T_J=25^\circ\text{C}$ unless otherwise noted)

| Symbol | Parameter | Conditions | Min | Typ | Max | Units |
|-----------------------------|---------------------------------------|---|-----|------|-----------|------------------|
| STATIC PARAMETERS | | | | | | |
| BV_{DSS} | Drain-Source Breakdown Voltage | $I_D=250\mu\text{A}, V_{GS}=0\text{V}$ | 40 | | | V |
| I_{DSS} | Zero Gate Voltage Drain Current | $V_{DS}=40\text{V}, V_{GS}=0\text{V}$ | | | 1 | μA |
| | | $T_J=55^\circ\text{C}$ | | | 5 | |
| I_{GSS} | Gate-Body leakage current | $V_{DS}=0\text{V}, V_{GS}=\pm 20\text{V}$ | | | ± 100 | nA |
| $V_{\text{GS(th)}}$ | Gate Threshold Voltage | $V_{DS}=V_{GS}, I_D=250\mu\text{A}$ | 1.7 | 2.5 | 3 | V |
| $I_{\text{D(ON)}}$ | On state drain current | $V_{GS}=10\text{V}, V_{DS}=5\text{V}$ | 30 | | | A |
| $R_{\text{DS(ON)}}$ | Static Drain-Source On-Resistance | $V_{GS}=10\text{V}, I_D=6\text{A}$ | | 24 | 30 | $\text{m}\Omega$ |
| | | $T_J=125^\circ\text{C}$ | | 36 | 45 | |
| g_{FS} | Forward Transconductance | $V_{DS}=5\text{V}, I_D=6\text{A}$ | | 19 | | S |
| V_{SD} | Diode Forward Voltage | $I_S=1\text{A}, V_{GS}=0\text{V}$ | | 0.76 | 1 | V |
| I_S | Maximum Body-Diode Continuous Current | | | | 2 | A |
| DYNAMIC PARAMETERS | | | | | | |
| C_{iss} | Input Capacitance | $V_{GS}=0\text{V}, V_{DS}=20\text{V}, f=1\text{MHz}$ | 410 | 516 | 650 | pF |
| C_{oss} | Output Capacitance | | | 82 | | pF |
| C_{rss} | Reverse Transfer Capacitance | | | 43 | | pF |
| R_g | Gate resistance | $V_{GS}=0\text{V}, V_{DS}=0\text{V}, f=1\text{MHz}$ | | 4.6 | | Ω |
| SWITCHING PARAMETERS | | | | | | |
| $Q_g(10\text{V})$ | Total Gate Charge | $V_{GS}=10\text{V}, V_{DS}=20\text{V}, I_D=6\text{A}$ | | 8.9 | 10.8 | nC |
| $Q_g(4.5\text{V})$ | Total Gate Charge | | | 4.3 | 5.6 | nC |
| Q_{gs} | Gate Source Charge | | | 2.4 | | nC |
| Q_{gd} | Gate Drain Charge | | | 1.4 | | nC |
| $t_{\text{D(on)}}$ | Turn-On Delay Time | $V_{GS}=10\text{V}, V_{DS}=20\text{V}, R_L=3.3\Omega, R_{\text{GEN}}=3\Omega$ | | 6.4 | | ns |
| t_r | Turn-On Rise Time | | | 3.6 | | ns |
| $t_{\text{D(off)}}$ | Turn-Off Delay Time | | | 16.2 | | ns |
| t_f | Turn-Off Fall Time | | | 6.6 | | ns |
| t_{rr} | Body Diode Reverse Recovery Time | $I_F=6\text{A}, dI/dt=100\text{A}/\mu\text{s}$ | | 18 | 24 | ns |
| Q_{rr} | Body Diode Reverse Recovery Charge | $I_F=6\text{A}, dI/dt=100\text{A}/\mu\text{s}$ | | 10 | | nC |

A: The value of $R_{\theta JA}$ is measured with the device mounted on 1 in² FR-4 board with 2oz. Copper, in a still air environment with $T_A=25^\circ\text{C}$. The value in any given application depends on the user's specific board design. The current rating is based on the $t \leqslant 10\text{s}$ thermal resistance rating.

B: Repetitive rating, pulse width limited by junction temperature.

C. The $R_{\theta JA}$ is the sum of the thermal impedance from junction to lead $R_{\theta JL}$ and lead to ambient.

D. The static characteristics in Figures 1 to 6 are obtained using <300 μs pulses, duty cycle 0.5% max.

E. These tests are performed with the device mounted on 1 in² FR-4 board with 2oz. Copper, in a still air environment with $T_A=25^\circ\text{C}$. The SOA curve provides a single pulse rating.

Rev2 : Nov. 2010

COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS: N-CHANNEL




Fig 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics


TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS: N-CHANNEL

Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note E)




Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note E)




Figure 11: Normalized Maximum Transient Thermal Impedance

P-Channel Electrical Characteristics ($T_J=25^\circ\text{C}$ unless otherwise noted)

| Symbol | Parameter | Conditions | Min | Typ | Max | Units |
|-----------------------------|---------------------------------------|---|------|-------|-----------|------------------|
| STATIC PARAMETERS | | | | | | |
| BV_{DSS} | Drain-Source Breakdown Voltage | $I_D = -250\mu\text{A}, V_{GS}=0\text{V}$ | -40 | | | V |
| I_{DSS} | Zero Gate Voltage Drain Current | $V_{DS} = -40\text{V}, V_{GS}=0\text{V}$ | | | -1 | μA |
| | | $T_J=55^\circ\text{C}$ | | | -5 | |
| I_{GSS} | Gate-Body leakage current | $V_{DS}=0\text{V}, V_{GS}=\pm 20\text{V}$ | | | ± 100 | nA |
| $V_{\text{GS(th)}}$ | Gate Threshold Voltage | $V_{DS}=V_{GS}, I_D = -250\mu\text{A}$ | -1.7 | -2 | -3 | V |
| $I_{\text{D(ON)}}$ | On state drain current | $V_{GS} = -10\text{V}, V_{DS} = -5\text{V}$ | -30 | | | A |
| $R_{\text{DS(ON)}}$ | Static Drain-Source On-Resistance | $V_{GS} = -10\text{V}, I_D = -5\text{A}$ | | 36 | 45 | $\text{m}\Omega$ |
| | | $T_J=125^\circ\text{C}$ | | 52 | 65 | |
| g_{FS} | Forward Transconductance | $V_{DS} = -5\text{V}, I_D = -5\text{A}$ | | 13 | | S |
| V_{SD} | Diode Forward Voltage | $I_S = -1\text{A}, V_{GS}=0\text{V}$ | | -0.76 | -1 | V |
| I_S | Maximum Body-Diode Continuous Current | | | | -2 | A |
| DYNAMIC PARAMETERS | | | | | | |
| C_{iss} | Input Capacitance | $V_{GS}=0\text{V}, V_{DS} = -20\text{V}, f=1\text{MHz}$ | 750 | 940 | 1175 | pF |
| C_{oss} | Output Capacitance | | | 97 | | pF |
| C_{rss} | Reverse Transfer Capacitance | | | 72 | | pF |
| R_g | Gate resistance | $V_{GS}=0\text{V}, V_{DS}=0\text{V}, f=1\text{MHz}$ | | 14 | | Ω |
| SWITCHING PARAMETERS | | | | | | |
| $Q_g(-10\text{V})$ | Total Gate Charge | $V_{GS} = -10\text{V}, V_{DS} = -20\text{V}, I_D = -5\text{A}$ | | 17 | 22 | nC |
| $Q_g(-4.5\text{V})$ | Total Gate Charge | | | 7.9 | 10 | nC |
| Q_{gs} | Gate Source Charge | | | 3.4 | | nC |
| Q_{gd} | Gate Drain Charge | | | 3.2 | | nC |
| $t_{\text{D(on)}}$ | Turn-On DelayTime | $V_{GS} = -10\text{V}, V_{DS} = -20\text{V}, R_L = 4\Omega, R_{\text{GEN}} = 3\Omega$ | | 6.2 | | ns |
| t_r | Turn-On Rise Time | | | 8.4 | | ns |
| $t_{\text{D(off)}}$ | Turn-Off DelayTime | | | 44.8 | | ns |
| t_f | Turn-Off Fall Time | | | 41.2 | | ns |
| t_{rr} | Body Diode Reverse Recovery Time | $I_F = -5\text{A}, dI/dt = 100\text{A}/\mu\text{s}$ | | 21 | 27 | ns |
| Q_{rr} | Body Diode Reverse Recovery Charge | $I_F = -5\text{A}, dI/dt = 100\text{A}/\mu\text{s}$ | | 14 | | nC |

A: The value of R_{BJA} is measured with the device mounted on 1 in² FR-4 board with 2oz. Copper, in a still air environment with $T_A=25^\circ\text{C}$. The value in any given application depends on the user's specific board design. The current rating is based on the $t \leq 10\text{s}$ thermal resistance rating.

B: Repetitive rating, pulse width limited by junction temperature.

C. The R_{BJA} is the sum of the thermal impedance from junction to lead R_{BJL} and lead to ambient.

D. The static characteristics in Figures 1 to 6,12,14 are obtained using <300 μs pulses, duty cycle 0.5% max.

E. These tests are performed with the device mounted on 1 in² FR-4 board with 2oz. Copper, in a still air environment with $T_A=25^\circ\text{C}$. The SOA curve provides a single pulse rating.

Rev1 : Jan 2010

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.


TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS: P-CHANNEL

Fig 12: On-Region Characteristics




Figure 13: Transfer Characteristics




Figure 14: On-Resistance vs. Drain Current and Gate Voltage




Figure 15: On-Resistance vs. Junction Temperature




Figure 16: On-Resistance vs. Gate-Source Voltage




Figure 17: Body-Diode Characteristics


TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS: P-CHANNEL

Figure 18: Gate-Charge Characteristics




Figure 19: Capacitance Characteristics




Figure 20: Maximum Forward Biased Safe Operating Area (Note E)




Figure 21: Single Pulse Power Rating Junction-to-Ambient (Note E)




Figure 22: Normalized Maximum Transient Thermal Impedance

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for MOSFET category:

Click to view products by Alpha & Omega manufacturer:

Other Similar products are found below :

[614233C](#) [648584F](#) [FDPF9N50NZ](#) [IRFD120](#) [IRFF430](#) [JANTX2N5237](#) [2N7000](#) [FCA20N60_F109](#) [FDZ595PZ](#) [2SK2267\(Q\)](#) [2SK2545\(Q,T\)](#)
[405094E](#) [423220D](#) [MIC4420CM-TR](#) [VN1206L](#) [614234A](#) [715780A](#) [SSM6J414TU,LF\(T\)](#) [751625C](#) [PSMN4R2-30MLD](#)
[TK31J60W5,S1VQ\(O\)](#) [2SK2614\(TE16L1,Q\)](#) [DMN1017UCP3-7](#) [EFC2J004NUZTDG](#) [FCAB21350L1](#) [P85W28HP2F-7071](#) [DMN1053UCP4-7](#)
[NTE2384](#) [NTE2969](#) [NTE6400A](#) [DMN61D9UWQ-13](#) [US6M2GTR](#) [DMN31D5UDJ-7](#) [SSM6P54TU,LF](#) [DMP22D4UFO-7B](#)
[IPS60R3K4CEAKMA1](#) [DMN1006UCA6-7](#) [DMN16M9UCA6-7](#) [STF5N65M6](#) [STU5N65M6](#) [C3M0021120D](#) [DMN13M9UCA6-7](#)
[BSS340NWH6327XTSA1](#) [MCM3400A-TP](#) [DMTH10H4M6SPS-13](#) [IPS60R1K0PFD7SAKMA1](#) [IPS60R360PFD7SAKMA1](#)
[IPS60R600PFD7SAKMA1](#) [IPS60R210PFD7SAKMA1](#) [DMN2990UFB-7B](#)