

### General Description

- Proprietary  $\alpha$ MOS5™ technology
- Low  $R_{DS(ON)}$
- Optimized switching parameters for better EMI performance
- Enhanced body diode for robustness and fast reverse recovery



### Applications

- SMPS with PFC, Flyback and LLC topologies
- Micro inverter with DC/AC inverter topology

### Product Summary

|                      |                 |
|----------------------|-----------------|
| $V_{DS} @ T_{j,max}$ | 700V            |
| $I_{DM}$             | 80A             |
| $R_{DS(ON),max}$     | < 0.19 $\Omega$ |
| $Q_{g,typ}$          | 34nC            |
| $E_{oss} @ 400V$     | 4.3 $\mu$ J     |

100% UIS Tested  
 100%  $R_g$  Tested



| Orderable Part Number | Package Type | Form | Minimum Order Quantity |
|-----------------------|--------------|------|------------------------|
| AOWF190A60            | TO-262F      | Tube | 1000                   |

### Absolute Maximum Ratings $T_A=25^\circ\text{C}$ unless otherwise noted

| Parameter  | Symbol         | AOWF190A60                       | Units            |
|--|----------------|----------------------------------|------------------|
| Drain-Source Voltage   | $V_{DS}$       | 600                              | V                |
| Gate-Source Voltage  | $V_{GS}$       | $\pm 20$                         | V                |
| Continuous Drain Current   | $I_D$          | $T_C=25^\circ\text{C}$           | 20*              |
|  |                | $T_C=100^\circ\text{C}$          | 12*              |
| Pulsed Drain Current <sup>C</sup>  | $I_{DM}$       | 80                               | A                |
| Avalanche Current <sup>C</sup>   | $I_{AR}$       | 5                                | A                |
| Repetitive avalanche energy <sup>C</sup>                                     | $E_{AR}$       | 12.5                             | mJ               |
| Single pulsed avalanche energy <sup>G</sup>                                  | $E_{AS}$       | 410                              | mJ               |
| MOSFET dv/dt ruggedness  | dv/dt          | 100                              | V/ns             |
| Peak diode recovery dv/dt  |                | 20                               |                  |
| Power Dissipation <sup>B</sup>   | $P_D$          | $T_C=25^\circ\text{C}$           | 27               |
|  |                | Derate above 25 $^\circ\text{C}$ | 0.22             |
| Junction and Storage Temperature Range                                       | $T_J, T_{STG}$ | -55 to 150                       | $^\circ\text{C}$ |
| Maximum lead temperature for soldering purpose, 1/8" from case for 5 seconds | $T_L$          | 300                              | $^\circ\text{C}$ |

### Thermal Characteristics

| Parameter                                  | Symbol          | AOWF190A60 | Units                     |
|--|-----------------|------------|---------------------------|
| Maximum Junction-to-Ambient <sup>A,D</sup> | $R_{\theta JA}$ | 65         | $^\circ\text{C}/\text{W}$ |
| Maximum Junction-to-Case                   | $R_{\theta JC}$ | 4.5        | $^\circ\text{C}/\text{W}$ |

\* Drain current limited by maximum junction temperature

**Electrical Characteristics (T<sub>J</sub>=25°C unless otherwise noted)**

| Symbol                             | Parameter   | Conditions  | Min | Typ  | Max  | Units |
|------------------------------------|---|---|-----|------|------|-------|
| <b>STATIC PARAMETERS</b>           |   |   |     |      |      |       |
| BV <sub>DSS</sub>                  | Drain-Source Breakdown Voltage                            | I <sub>D</sub> =250μA, V <sub>GS</sub> =0V, T <sub>J</sub> =25°C                      | 600 | -    | -    | V     |
|                                    |   | I <sub>D</sub> =250μA, V <sub>GS</sub> =0V, T <sub>J</sub> =150°C                     | -   | 700  | -    |       |
| BV <sub>DSS</sub> /ΔT <sub>J</sub> | Breakdown Voltage Temperature Coefficient                 | I <sub>D</sub> =250μA, V <sub>GS</sub> =0V  | -   | 0.59 | -    | V/°C  |
| I <sub>DSS</sub>                   | Zero Gate Voltage Drain Current                           | V <sub>DS</sub> =600V, V <sub>GS</sub> =0V  | -   | -    | 1    | μA    |
|                                    |   | V <sub>DS</sub> =480V, T <sub>J</sub> =125°C  | -   | -    | 10   |       |
| I <sub>GSS</sub>                   | Gate-Body leakage current                                 | V <sub>DS</sub> =0V, V <sub>GS</sub> =±20V  | -   | -    | ±100 | nA    |
| V <sub>GS(th)</sub>                | Gate Threshold Voltage                                    | V <sub>DS</sub> =5V, I <sub>D</sub> =250μA  | -   | 4    | -    | V     |
| R <sub>DS(ON)</sub>                | Static Drain-Source On-Resistance                         | V <sub>GS</sub> =10V, I <sub>D</sub> =7.6A  | -   | 0.17 | 0.19 | Ω     |
| g <sub>FS</sub>                    | Forward Transconductance                                  | V <sub>DS</sub> =10V, I <sub>D</sub> =10A   | -   | 16   | -    | S     |
| V <sub>SD</sub>                    | Diode Forward Voltage                                     | I <sub>S</sub> =10A, V <sub>GS</sub> =0V  | -   | 0.85 | 1.2  | V     |
| I <sub>S</sub>                     | Maximum Body-Diode Continuous Current                     |   | -   | -    | 20   | A     |
| I <sub>SM</sub>                    | Maximum Body-Diode Pulsed Current <sup>C</sup>            |   | -   | -    | 80   | A     |
| <b>DYNAMIC PARAMETERS</b>          |   |   |     |      |      |       |
| C <sub>ISS</sub>                   | Input Capacitance   | V <sub>GS</sub> =0V, V <sub>DS</sub> =100V, f=1MHz                                    | -   | 1935 | -    | pF    |
| C <sub>OSS</sub>                   | Output Capacitance  |   | -   | 55   | -    | pF    |
| C <sub>O(er)</sub>                 | Effective output capacitance, energy related <sup>H</sup> | V <sub>GS</sub> =0V, V <sub>DS</sub> =0 to 480V, f=1MHz                               | -   | 49   | -    | pF    |
| C <sub>O(tr)</sub>                 | Effective output capacitance, time related <sup>I</sup>   |   | -   | 213  | -    | pF    |
| C <sub>rSS</sub>                   | Reverse Transfer Capacitance                              | V <sub>GS</sub> =0V, V <sub>DS</sub> =100V, f=1MHz                                    | -   | 1.25 | -    | pF    |
| R <sub>g</sub>                     | Gate resistance   | f=1MHz  | -   | 5    | -    | Ω     |
| <b>SWITCHING PARAMETERS</b>        |   |   |     |      |      |       |
| Q <sub>g</sub>                     | Total Gate Charge   | V <sub>GS</sub> =10V, V <sub>DS</sub> =480V, I <sub>D</sub> =10A                      | -   | 34   | -    | nC    |
| Q <sub>gs</sub>                    | Gate Source Charge  |   | -   | 12   | -    | nC    |
| Q <sub>gd</sub>                    | Gate Drain Charge   |   | -   | 11   | -    | nC    |
| t <sub>D(on)</sub>                 | Turn-On DelayTime   | V <sub>GS</sub> =10V, V <sub>DS</sub> =400V, I <sub>D</sub> =10A, R <sub>G</sub> =25Ω | -   | 49   | -    | ns    |
| t <sub>r</sub>                     | Turn-On Rise Time   |   | -   | 40   | -    | ns    |
| t <sub>D(off)</sub>                | Turn-Off DelayTime  |   | -   | 115  | -    | ns    |
| t <sub>f</sub>                     | Turn-Off Fall Time  |   | -   | 26   | -    | ns    |
| t <sub>rr</sub>                    | Body Diode Reverse Recovery Time                          | I <sub>F</sub> =10A, di/dt=100A/μs, V <sub>DS</sub> =400V                             | -   | 341  | -    | ns    |
| I <sub>rm</sub>                    | Peak Reverse Recovery Current                             |   | -   | 28   | -    | A     |
| Q <sub>rr</sub>                    | Body Diode Reverse Recovery Charge                        |   | -   | 6.8  | -    | μC    |

A. The value of R<sub>θJA</sub> is measured with the device in a still air environment with T<sub>A</sub>=25° C.

B. The power dissipation P<sub>D</sub> is based on T<sub>J(MAX)</sub>=150° C, using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heatsinking is used.

C. Repetitive rating, pulse width limited by junction temperature T<sub>J(MAX)</sub>=150° C. Ratings are based on low frequency and duty cycles to keep initial T<sub>J</sub>=25° C.

D. The R<sub>θJA</sub> is the sum of the thermal impedance from junction to case R<sub>θJC</sub> and case to ambient.

E. The static characteristics in Figures 1 to 6 are obtained using <300μs pulses, duty cycle 0.5% max.

F. These curves are based on the junction-to-case thermal impedance which is measured with the device mounted to a large heatsink, assuming a maximum junction temperature of T<sub>J(MAX)</sub>=150° C. The SOA curve provides a single pulse rating.


G. L=60mH, I<sub>AS</sub>=3.7A, V<sub>DD</sub>=150V, R<sub>G</sub>=25Ω, Starting T<sub>J</sub>=25° C.

H. C<sub>O(er)</sub> is a fixed capacitance that gives the same stored energy as C<sub>OSS</sub> while V<sub>DS</sub> is rising from 0 to 80% V<sub>(BR)DSS</sub>.


I. C<sub>O(tr)</sub> is a fixed capacitance that gives the same charging time as C<sub>OSS</sub> while V<sub>DS</sub> is rising from 0 to 80% V<sub>(BR)DSS</sub>.

APPLICATIONS OR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN,FUNCTIONS AND RELIABILITY WITHOUT NOTICE.


**TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS**




**Figure 1: On-Region Characteristics**




**Figure 2: Transfer Characteristics**




**Figure 3: On-Resistance vs. Drain Current and Gate Voltage**



**Figure 4: On-Resistance vs. Junction Temperature**








**Figure 5: Break Down vs. Junction Temperature**



**Figure 6: Body-Diode Characteristics**

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS



**TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS**








Figure 12: Normalized Maximum Transient Thermal Impedance for AOWF190A60 (Note F)



Gate Charge Test Circuit & Waveform





Resistive Switching Test Circuit & Waveforms



Unclamped Inductive Switching (UIS) Test Circuit & Waveforms



Diode Recovery Test Circuit & Waveforms



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [MOSFET](#) category:*

*Click to view products by [Alpha & Omega](#) manufacturer:*

Other Similar products are found below :

[614233C](#) [648584F](#) [IRFD120](#) [JANTX2N5237](#) [2N7000](#) [FCA20N60\\_F109](#) [FDZ595PZ](#) [2SK2545\(Q,T\)](#) [405094E](#) [423220D](#)  
[TPCC8103,L1Q\(CM](#) [MIC4420CM-TR](#) [VN1206L](#) [614234A](#) [715780A](#) [NTNS3166NZT5G](#) [SSM6J414TU,LF\(T](#) [751625C](#) [IPP110N20N3GXX](#)  
[IPS70R2K0CEAKMA1](#) [DMN3404LQ-7](#) [NTE6400](#) [2SK2614\(TE16L1,Q\)](#) [DMN1017UCP3-7](#) [EFC2J004NUZTDG](#) [ECH8691-TL-W](#)  
[FCAB21350L1](#) [P85W28HP2F-7071](#) [DMN1053UCP4-7](#) [NTE221](#) [NTE2384](#) [NTE2903](#) [NTE2941](#) [NTE2945](#) [NTE2946](#) [NTE2960](#) [NTE2969](#)  
[NTE2976](#) [NTE455](#) [NTE6400A](#) [NTE2910](#) [NTE2916](#) [NTE2956](#) [NTE2911](#) [TK10A80W,S4X\(S](#) [SSM6P69NU,LF](#) [DMP22D4UFO-7B](#)  
[DMN1006UCA6-7](#) [DMN16M9UCA6-7](#) [STF5N65M6](#)