

RK39A 39mm Size LED Illuminated Ring Type

This LED illuminated ring potentiometer is best suited for knob design of various set devices



Typical Specifications



Items	Specifications
Contact resistance	±20%
Maximum operating voltage	50V AC, 30V DC
Total rotational angle	180°±5°, 220°±5°, 270°±5° (Customizable up to 290°)
Operating life	30,000 cycles
Operating temperature range	-40°C to +85°C

Product Line

Rotational angle	Number of positions	Detent torque (mN·m)	LED	Total resistance	Resistance taper	Minimum order unit (pcs.)		Product No.	Drawing No.
						Japan	Export		
220°±5°	17	40±16	Red	5kΩ	B	250	500	RK39A1A00007	2
180°±5°		50±20						RK39A1A00027	1
270°±5°	6	RK39A1A00028						2	

Notes

- Other varieties are also available. Please inquire.
- We can also provide LED colors other than the above mentioned. Please contact us if required.

Packing Specifications

Tray

	Number of packages (pcs.)		Export package measurements (mm)
	1 case / Japan	1 case / export packing	
	250	500	540×360×380

Dimensions





Unit:mm

No.	Style	PC board mounting hole dimensions (Viewed from mounting side)
1	RK39A1A00027 	
2	RK39A1A00007 RK39A1A00028 	

Refer to P.348 for soldering conditions.

Ring Type Potentiometers

List of Varieties

Type		39mm size	45mm size
Series		RK39A	RK45C
		Single-unit	Single-unit
Photo			
Features		LED illuminate	
Dimensions (mm)	W	39	45
	D	39.5	45.5
	H	8.5	9.5
Operating temperature range		-40°C to +85°C	
Operating life		30,000 cycles	
Automotive use		●	●
Life cycle			
Electrical performance	Total resistance (k Ω)	5	
	Resistance taper	B	
	Rated power	0.05W	
	Insulation resistance	10MΩ min. 50V DC	
	Voltage proof	50V AC for 1minute	
Mechanical performance	Detent torque	40±16mN·m 50±20mN·m	40±16mN·m
	Number of positions	6, 17	17
	Stopper strength	1N·m	
	Push-pull strength	100N (Push), 50N (Pull)	
	Vibration	10 to 55 to 10Hz/min., the amplitude is 1.5mm for all the frequencies, in the 3 direction of X, Y and Z for 2 hours respectively	
Terminal type		Insertion	
Page		346	347

- Rotary Potentiometers
- Slide Potentiometers
- Metal Shaft
- Insulated Shaft
- Knob Operating
- Through Shaft Type
- Ring Type

Ring Type Potentiometers Soldering Conditions	348
Potentiometers Cautions	384
Potentiometers Measurement and Test Methods	386
Potentiometers Resistance Taper	388

Note

● Indicates applicability to all products in the series.

Ring Type Potentiometers / Soldering Conditions

■ Reference for Manual Soldering

Series	Tip temperature	Soldering time	No. of solders
RK39A, RK45C	350°C max.	3s max.	1 time

■ Reference for Dip Soldering

Series	Preheating		Dip soldering		No. of solders
	Soldering surface temperature	Heating time	Soldering temperature	Soldering time	
RK39A, RK45C	100°C max.	2 min. max.	260°C max.	5s max.	2 time max.

Rotary Potentiometers

Slide Potentiometers

Metal Shaft

Insulated Shaft

Knob Operating

Through Shaft Type

Ring Type

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Potentiometers](#) category:

Click to view products by [ALPS](#) manufacturer:

Other Similar products are found below :

[58C2-2](#) [590SX1N32F103SS](#) [591SXJ48S252SC](#) [591SXP56S252SC](#) [591SXP56S503SC](#) [D31409](#) [70B1G048K502X-A](#) [70B1M032S502W](#)
[70B1N056S202W](#) [70B8N056F502W](#) [70J8N048S104U](#) [70L1N040P103W](#) [70L1N048P103X](#) [70L1N048S103W](#) [GA2L040S102UC](#)
[GA2L040S103UC](#) [GS1G044P103UA](#) [GS1N048P103UA](#) [GS1T032S103UA](#) [A43-1500](#) [A43-20K](#) [A47-200K](#) [A4720K](#) [RA20LASD251A](#)
[132-2-0-202](#) [RK14K1220-F25-C0-A103](#) [RK14K1220F25C0C104](#) [RK14K1220-F25-C1-B103](#) [14910FAGJSX10102KA](#)
[14910FBGLFY00103KA](#) [14910AABHSX10103KA](#) [14910FAGJSX10104KA](#) [152-01031](#) [C0342008 5K](#) [P270-109A](#) [J97589](#) [23M728](#)
[RV170F-10-15R1-B500K-0021](#) [RV8NAYS104A](#) [917523A](#) [A43-40](#) [A43-750](#) [A43S-5](#) [A47-15K](#) [A4750K](#) [SPPG048S103U](#)
[SPPG056P103U](#) [SWE-10](#) [GA2G040F103BA](#) [GS1G052F103UA-A](#)