


RKJXT1F 4-directional Stick Switch (with Encoder / Center-push Function)

A space-saving device with single shaft 4-directions/
push/encoder



Typical Specifications (Stick Switches)

Items		Specifications
Ratings (max.)(Resistive load)		10mA 5V DC
Contact resistance	4-direction Center-push	1Ω max.
Operating angle (4-direction)		Each direction 9° max.
Travel (Center push)		0.3±0.2mm
Operating life	Total with 4-direction	50,000 cycles
	Center-push	50,000 cycles

Typical Specifications (Encoders)

Items		Specifications
Ratings (max.)(Resistive load)		10mA 5V DC
Operating life		15,000 cycles


Product Line

Product No.	Stick Switches			Encoder			Minimum order unit (pcs.)	
	Maximum resolution	Operating force		Detent torque	Number of detent	Number of pulse	Japan	Export
Direction	Center-push							
RKJXT1F42001	4	40±25mN·m	5±2N	15±8mN·m	30	15	1,320	2,640

Packing Specifications Tray


Number of packages (pcs.)		Export package measurements (mm)
1 case / Japan	1 case / export packing	
1,320	2,640	555×375×333

Dimensions




■ Output Relation Chart Between Lever Position and ON Position.

Terminal	Operating Direction				
	A	B	C	D	Center push
Push-A	ON				
Push-B		ON			
Push-C			ON		
Push-D				ON	
Push-Com	ON	ON	ON	ON	ON




Operating direction of lever


■ Circuit Diagram



■ Test Circuit (Encoder)











■ Output Signal (Encoder)



Multi Control Devices

Variable Resistor Type

Switch Type

Type		Switch type			
Series		RKJXT1F	RKJXM	RKJXW	RKJXL
Photo					
Dimensions (mm)	W	17	11	36	13
	D			48.5	
	H	10.5	6.6	26.5	6.4
Shaft material		Metal			
Directional resolution		4-direction	8-direction		
Directional operating feeling (tactile feeling)		With			Without
Lever return mechanism		With			
Center-push switch		With			
Encoder		With	Without	With	Without
Operating temperature range		-40°C to +85°C			-30°C to +70°C
Operating life	Directional operation	Total with 4-direction 50,000 cycles	Total with 8-direction 100,000 cycles	30,000 cycles for each direction	8 directions total: 100,000 cycles
	Center-push			30,000 cycles	100,000 cycles
	Encoder	15,000 cycles	—	30,000 cycles	—
Automotive use		●	●	●	●
Life cycle (availability)					
Rating (max.) (Resistive load)		10mA 5V DC			
Electrical performance	Output voltage	—	—	—	—
	Encoder resolution	15pulses/360°	—	15pulses/360°	—
	Insulation resistance	100MQ min. 250V DC			
	Voltage proof	250V AC for 1min.		360V AC for 2s	300V AC for 1min. or 360V AC for 2s
Mechanical performance	Directional operating force	40±25mN·m	Direction A, B, C, D 30±20mN·m	2.5±1.5N	10±7mN·m
			Direction AB, BC, CD, DA 25±20mN·m		
	Push operating force	5±2N	3±1.5N		4.5±1N
	Encoder detent torque	15±8mN·m	—	30±20mN·m	—
	Terminal strength	5N for 1min.			
Actuator strength	Push / pull directions	100N (Push/Pull)	100N (Push), 50N (Pull)	100N (Push)	100N (Push), 50N (Pull)
	Operating direction	0.4N·m	0.3N·m	50N	100N
Environmental performance	Cold	-40°C 500h			
	Dry heat	85°C 500h			
	Damp heat	60°C, 90 to 95%RH 500h			
Page		398	400	402	404

Multi Control Devices

Variable Resistor Type

Switch Type

Switch Type Multi Control Devices Soldering Conditions	412
Switch Type Multi Control Devices Cautions	413

Note

● Indicates applicability to all products in the series.

Switch Type Multi Control Devices / Soldering Conditions

Reference for Manual Soldering


Series	Tip temperature	Soldering time	No. of solders
RKJXT1F, RKJXM, RKJXL, SLLB, SLLB5, SRBE, SKRH	350±5°C	3s max.	1 time

Reference for Dip Soldering

Series	Preheating		Dip soldering		No. of solders
	Soldering surface temperature	Heating time	Soldering temperature	Soldering time	
RKJXT1F, RKJXM	100°C max.	2 min. max.	260±5°C	5±1s	2 time max.
RKJXL	120°C max.	70s max.	260°C max.	6s max.	2 time max.

Example of Reflow Soldering Condition

1. Heating method: Double heating method with infrared heater.
2. Temperature measurement: Thermocouple $\phi 0.1$ to 0.2 CA (K) or CC (T) at soldering portion (copper foil surface).
A heat resisting tape should be used for fixed measurement.
3. Temperature profile



Series	A	B	C	D	E	F	G	H	I	No. of reflows
SLLB5	250°C	230°C	150°C	150°C	—	2 min.	—	30s	—	1 time
SLLB, SRBE	260°C	230°C	180°C	150°C	2 min.	—	—	40s	—	1 time
SKRH	260°C	230°C	180°C	150°C	2 min.	—	3s	40s	3-4 min.	2 times

Notes

1. The above temperature shall be measured on the mounting surface of a PC board. There are cases where the PC board's temperature greatly differs from that of the switch, depending on the material, size thickness of PC boards and others. The above-stated conditions shall also apply to switch surface temperatures.
2. Soldering conditions differ depending on reflow soldering machines. Prior verification of soldering condition is highly recommended.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Multi-Directional Switches](#) category:

Click to view products by [ALPS](#) manufacturer:

Other Similar products are found below :

[MJTP1109AL](#) [RA3CSH6A](#) [APTCFVTR](#) [SRBE210100](#) [T5-NH1118](#) [RKJXW1014002](#) [RKJXW2014001](#) [T4-TCN3332](#) [TSWA-3N-CUP2-LFS](#) [T2-0018](#) [T5-CK2212](#) [CS41001E](#) [RKJXK122000D](#) [RKJXK122400Y](#) [RKJXL100401V](#) [RKJXM2E13001](#) [RKJXM2E13004](#) [RKJXS1004001](#) [RKJXT1F42001](#) [RKJXV1224005](#) [RKJXY100000A](#) [SKRHAAE010](#) [SKRHABE010](#) [SKRHACE010](#) [SKRHADE010](#) [SLLB120100](#) [SLLB120200](#) [SLLB120300](#) [SLLB510100](#) [SLLB510200](#) [SLLB520100](#) [SRBE110301](#) [SRBE210200](#) [AMPTFP2VTR](#) [D16202](#) [PHAP4383V](#) [3302](#) [7G5002C0003](#) [QSA2S3.5NH3G7](#) [K1-1508SA-03](#) [PLJG2-G-V-T/R](#) [PLMG5-GH-V-T/R](#) [RKJXU1210006](#) [SKRHADE011](#) [2200-000301](#) [RKJXM1015004](#) [RKJXV1220001](#) [SLLB310300](#) [SLLB310500](#) [SLLB520200](#)