
LPS/ILPINE

Power Switch > SDDH Series > SDDHA10100

Water-proof Switch Compatible with 10mA to 4.5A SDDH Series

| Dimensions | Circuit Diagram | Packing Specifications |







Туре		Push
Circuit arrangement		SPST (normally closed)
Travel		3.7mm
Operating force		4.6N max.
Mounting method		Snap-in
Terminal type		Tab Terminal (#187)
Operating temperature range		-15°C to +80°C
Rating	Rating max.	4.5A 12V DC (lamp: 27W×2pcs.)
	Rating min.	10mA 12V DC (resistive load)
Electrical performance	Contact resistance	500mΩ max
	Insulation resistance	10MΩ min. 500V DC
	Voltage proof	500V AC for 1minute
Mechanical performance	Terminal strength	Slider pull-out strength: 100N MIN
Durability	Operating life	100,000 cycles
Environmental performance	Cold	-15°C 96h

	Dry heat	80°C 96h
	Damp heat	40°C, 90 to 95%RH 96h
Water resistance standard		IP68 equivalent
Minimum order unit (pcs.)	Japan	180
	Export	360

Dimensions



Circuit Diagram



Packing Specifications

Tray

Number of packages (pcs.)	1 case / Japan	180
	1 case / export packing	360

400×270×185

Notes are common to this series/models.

- 1. This site catalog shows only outline specifications. When using the products, please obtain formal specifications for supply.
- 2. Please place purchase orders per minimum order unit (integer).

Inquiries about Products

Inquiry

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Switch Bezels / Switch Caps category:

Click to view products by ALPS manufacturer:

Other Similar products are found below:

896809000 LW1A-B2-R LW2A-B1-G 704.604.4 704.955.3 7527 760203000 760503000 766601000 785105000 785106000 79211759

MG12KB MH11 MHU31 800C2BLK MJ1216 MJ33 MJ612 908-1634 92-343.200 92-343.400 95CAP-011 95CAP-112 11-932.7 99
901.9 99-902.9 99-909.5 99-920.8 A0261A 11-931.2 11-936 11-937 AKTSC22B AT496H AW-RF8 161006 1825068-6 184-1872 187
1872 188-1471 18-920.1 1DFBLK 1D-GRY 1DS30 1KBS1116 C159 C22404 1X02 1ZW00