


Safety Hinged Switches




SHS Series

Switching diagram

1 NC contact (Type B)



1 Changeover contact (Type C)




Setting point freely selectable in range from 0°... 225°


Tolerances:
 Switching angle (opening) +2.0°/-1.5°
 Positive opening torque 10 %
 Positive opening angle +0.5°/-3°

Switching angle hysteresis (closing of normally-closed contact -1.0°) from typical hinge switch-off point

Connection drawing




Connection variant 1




Cable, PVC

Connection variant 2




Cable, PVC

Connection variant 3




Connector M12 x 1, metal thread

Connection variant 4




Connector M12 x 1, metal thread

Connection variant 5



Connector M12 x 1

Connection variant 6



Connector M12 x 1

Product selection

Article number	Designation	Switching contact	Max. switching voltage	Type of voltage	Type of connection and direction radial	axial	Required cable coupling/type	Remarks
601.9261.011	SHS-A1Z-KA 5	1NC	230 V	AC/DC		Cable		BG approval
601.9261.014	SHS-A1Z-KR 5	1NC	230 V	AC/DC	Cable			BG approval
601.9261.017	SHS-A1Z-SA-BG	1NC	230 V	AC/DC		M12	A	BG approval
6019261018	SHS-A1Z-SR-BG	1NC	230 V	AC/DC	M12		A	BG approval
601.9261.009	SHS-A1Z-SA	1 Changeover contact	230 V	AC/DC		M12	C	
601.9261.010	SHS-A1Z-SR	1 Changeover contact	60 V	DC	M12		B	
601.9261.015	SHS-A1Z-SA	1 Changeover contact	60 V	DC		M12	B	
601.9261.016	SHS-A1Z-SR	1 Changeover contact	230 V	AC/DC	M12		C	
6019291013	SHS-OZ							Blank hinge

Technical data

Electrical data	
Rated insulation voltage	U _i 250 V
Rated surge voltage strength	U _{imp} 2.5 kV
Thermal current	I _{the} 3 A
Rated operating voltage	U _c 230 V AC; 60 V DC
Utilization category	AC-15, 230 V AC/1.5 A;
Positive opening	p conforming to IEC/EN 60947-5-1, Addendum K
Short-circuit protection	Fuse 4 A gL/gG
Mechanical data	
Switch	GD-Zn
Ambient temperature	-25°C to +70°C (Connection cable installed)
Mechanical service life	10 ⁹ switching cycles
B10d	2 mill.
Switching frequency	max. 1200 switching cycles/hour
Mounting	4x M6 screws DIN 7984 or DIN 6912
Type of connection	Fixed connection cable, 3 x 0.5 mm ² x 5 m (AWG20), minimum bending radius = 25 mm
Weight	approx. 0.7 kg (cable variant) approx. 0.4 kg (connector and blank hinge variant)
Installation position	Any
Protection class	IP67 as per IEC/EN 60529
Switching angle	± 3° from setting point
Positive opening angle	± 10° from setting point
Positive opening torque	1.5 Nm
Mechanical load	F _{R1} = max. 1000 N, F _{R2} = max. 500 N, F _A = max. 750 N
Standards	
VDE 0660 T100, DIN EN 60947-1, IEC 60947-1 VDE 0660 T200, DIN EN 60947-5-1, IEC 60947-5-1	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Control Switches](#) category:

Click to view products by [Altech](#) manufacturer:

Other Similar products are found below :

[80887-99](#) [80932-99](#) [86855-00](#) [88814-30](#) [1424293-1](#) [HW4S-2TC10](#) [89721-12](#) [89804-08](#) [SSN](#) [RL01801](#) [ASD2L20N-LVO](#) [50051857-17](#)
[50099156-001-05](#) [51.155R-15200](#) [50058920-26](#) [CP-FA51](#) [CP-FA49](#) [ACCU-SC/L-3000](#) [PP9M](#) [PP87G](#) [PP86GA](#) [PP74G](#) [PP73M](#) [PP73G](#)
[PP71G](#) [PP70G](#) [PP6G](#) [PP62G](#) [PP58BL](#) [PP56G](#) [PP86GB](#) [PP77GA](#) [PP76G](#) [PP4M](#) [PP47G](#) [PP46G](#) [PP41M](#) [PP40G](#) [PP32G](#) [RD-20](#) [PP23M](#)
[PP14M](#) [PP12G](#) [RD-40](#) [PORTAPRO](#) [POM-2708](#) [PNB-2005](#) [3057.0012](#) [CV-075](#) [CV-140SB](#)