### **Technical Data**

# Magnetic switch




#### **Series MA-02**

Type designation MAK-0214-P-3

Item number 6419402397

#### Wiring diagram





Electrical data				
Switching element function			bistable "N.ON.C."	
Reed contact:	max. switching voltage		250 V	
	max. switching current		5 A ( 2 ms )	
Max. permanent limiting current			2,5 Å	
	max. switching capacity		250 VA	
	mechanical lifetime		3 x 10 <sup>8</sup> switchings, however, according to load resetability	
Repeat accura	СУ	R	± 0,1mm	
			under same geometrical conditions at the same temperature	
Shock			10g (11ms, ½ Sine wave)	
Vibration			10g (10-55 Hz)	
Assured operating distance			10 mm	
Corresponding magnet			T-67	

Mechanical data	
Enclosure	PA 6.6, black; encapsulated reed contact
Ambient air temperature	-5 °C +70 °C
	-25°C +70°C (cable fixed mounted)
Type of protection	IP67 according to IEC 529, EN 60529
Termination type	cable 2 x 0,5 mm <sup>2</sup> x 3 m; PVC -outer jacket black;
Assembly position	optional (assembly on iron means reduction of switch distance)

This document will not become the contractual basis; the details included herein do not constitute any descriptions of expected conditions, so that warranties/claims for defects on account of possible variations of the actual from the here described condition are excluded. Subject to modifications and amendments.

Date of issue: 03.09.2007 / Page 1 of 1 Document: 6419402397\_en.doc / Last update: 1 / 0418-07

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Magnetic/Reed Switches category:

Click to view products by Altech manufacturer:

Other Similar products are found below:

59200-020 MDSR-4-12-23 MMRB20006 PSW-21 AMS-17-B AMS-20MG AMS-37-G\_W/Brk AMS-38S-I AMS-38SW AMS-39B-B AMS-39B-W HRB10030 2116900170 AMS-10S-B AMS-25B-B AMS-37BROWN AMS-38MG AMS-38SB AMS-9-B AMS-T10C(B) 4350238 505-171W WHITE 505-211B 505-391G 505-5114W WHITE 505-70B 507-382B BMC-33B HM00-01800 4350186 505-101-GC 505-101-GS 505-101-WS 505-172W 505-201W 505-392W 505-90G 505-90I 507-381BB RSW-21A-I ODC-56B FF6-21-DC-03-SS FF6-11-AC-06 FF6-21-AC-06 DRR-129(42-48) ODC-56A AMS-10MGW AMS-37B GRAY 649.0642.305