

(€

MST S WS 30 AU

2mm safety plug, spring loaded pin, gold plated, solder terminal 0.5mm2-1.0mm2, 1000V system.

2 mm (0.078") Pin diameter

973600100 973600101 2 mm (0.078")

- 975090700
- 975090701
- 975090702
- 975090703
- 975090704 975090705
- 975090706
- 975090707
- 975090709

Technical Data

PART NO. / Housing color

Contact Type stationary Connection Type jack Ø4mm 30 VAC / 60 VDC Voltage Rating

Measurement Category (IEC61010) CAT I Current Rating* 6A Contact Resistance 6 mOhm

Material Specifications

Plug nickel plated brass

Contact Spring Housing PP

Environmental Conditions

-20 °C to +60 °C (-4 to 140°F) Temperature range

Flamability Rating

Housing UL94 HB spring loaded pin solder terminal

AC/DC 1000V CAT III

10A 2 mOhm


gold plated copper-beryllium


gold plated brass Polyamide

-15°C to +70°C (-5 to 158°F)

Drawing

Measurements are shown in millimeters. Multiply by 0.03937 to convert to inches.





^{*} Please consider derating graph on page 80.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Test Plugs & Test Jacks category:

Click to view products by Altech manufacturer:

Other Similar products are found below:

579-0400 66000-7 R644543000 R921923000 R921930000 R941344000 R948161000 R999351000 1408-4 1533-1 174-R825B-EX

NYS508-BU NYS508-O 1680 174-R819B-EX R644543003 R644543004 R644543020 R644543021 R921926000 R921931000

R921932000 R921934000 R929991000 R941460000 R941461000 R941463600 R941920600 R948160000 31B-2-RED 032-0016-023 105
1106-001 108-1000-106 108-2301-621 66001-9 7013 1395080-1 930166100 NYS508-GR NYS508-V NYS508-W NYS508-Y NYS511-R

BP30-2BR10-B PKG BP30-10-WT BP30-2BR-B PKG BP30Y-1 PKG R941049000 R941340000 R948141029