

(€

## MST S WS 30 AU

2mm safety plug, spring loaded pin, gold plated, solder terminal 0.5mm2-1.0mm2, 1000V system.

2 mm (0.078") Pin diameter

973600100 973600101 2 mm (0.078")

- 975090700
- 975090701
- 975090702
- 975090703
- 975090704 975090705
- 975090706
- 975090707
- 975090709

## **Technical Data**

PART NO. / Housing color

Contact Type stationary Connection Type jack Ø4mm 30 VAC / 60 VDC Voltage Rating

Measurement Category (IEC61010) CAT I Current Rating\* 6A Contact Resistance 6 mOhm

**Material Specifications** 

Plug nickel plated brass

Contact Spring Housing PP

**Environmental Conditions** 

-20 °C to +60 °C (-4 to 140°F) Temperature range

Flamability Rating

Housing UL94 HB spring loaded pin solder terminal

AC/DC 1000V CAT III

10A 2 mOhm


gold plated copper-beryllium


gold plated brass Polyamide

-15°C to +70°C (-5 to 158°F)

## Drawing

Measurements are shown in millimeters. Multiply by 0.03937 to convert to inches.





<sup>\*</sup> Please consider derating graph on page 80.

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Test Plugs & Test Jacks category:

Click to view products by Altech manufacturer:

Other Similar products are found below:

01-2601-4-0210 01-2601-4-0212 01-2604-4-0212 01-2604-5-0210 01-2150-1-0312 01-2350-1-02 01-2352-1-02 01-2368-1-02 01-2604-4-0210 01-2604-5-0212 01-2606-5-0212 M39024/10-01G M39024/10-17G M39024/11-09G M39024/11-42 M39024/11-43 M39024/12-08 707-5311 707-5402-01-19 707-5410 923739-40-I R644543000 R948161000 R999351000 1408-4 1499-101 1533-1 1659559 1659567 1663921 1663939 1696-102 174-R825B-EX NYS508-BU NYS508-O 211-101 RS100GBL RS250GBL 251-102 25-2251-2-03 25-2259-2-03 923743-16-I 923743-24-I 923743-28-I 2854-BLU 2970-BLK 30-443G 1680