

Test Jacks 2 mm System



MSEB 2600 G M3 Au

2mm panel mount safety test jack, gold plated brass with M3 thread and solder terminal. max. installation wall thickness 8mm.

Pin Diameter

PART NO. / Housing color

2 mm

- 975454700
- 975454701
- 975454702
- 975454703
- 975454704
- 975454705
- 975454706
- O 975454707
- 975454709



MSEB 2610 F2.8 Au

2mm panel mount safety test jack, gold plated brass with flat 2.8x0.8mm DIN46244 terminal. max. installation wall thickness 8mm.

2 mm

- 975455700
- 975455701
- 975455702
- 975455703
- 975455704
- 975455705975455706
- 975455707
- 975455709





MSEB 2630 S1.9 Au

2mm panel mount safety test jack, gold plated brass with 1.9mm solder pin terminal. max. installation wall thickness 8mm.

2 mm

- 975459700
- 975459701
- 975459702
- 975459703
- 975459704
- 975459705
- 975459706
- 975459707975459709

Technical Data

Contact Type

Connection Type Voltage Rating

Measurement Category (IEC61010)

Current Rating*
Contact Resistance

Mounting Type

Material Specifications

Jack Body Contact Spring

Housing

Environmental Conditions

Temperature Range Flamability Rating

Housing

jack Ø 2 mm

M3 thread, solder terminal

AC/DC 1000V

CAT III

10 A 5 mOhm

screw thread M8

gold plated brass

_

Polyamide

-15°C to +70°C (5 to 158°F)

UL 94 V-2

jack Ø 2 mm

flat 2.8x0.8 mm push in tab

AC/DC 1000V

CAT III

10 A

5 mOhm

screw thread M8

gold plated brass

_

Polyamide

-15°C to +70°C (5 to 158°F)

UL 94 V-2

jack Ø 2 mm

solder terminal AC/DC 1000V

CAT III

10 A

5 mOhm

screw thread M8

gold plated brass

-


Polyamide


-15°C to +70°C (5 to 158°F)


UL 94 V-2

Drawing

Measurements are shown in millimeters. Multiply by 0.03937 to convert to inches.







^{*} Please consider derating graph on page 80.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Test Plugs & Test Jacks category:

Click to view products by Altech manufacturer:

Other Similar products are found below:

579-0400 66000-7 R644543000 R921923000 R921930000 R941344000 R948161000 R999351000 1408-4 1533-1 174-R825B-EX

NYS508-BU NYS508-O 1680 174-R819B-EX R644543003 R644543004 R644543020 R644543021 R921926000 R921931000

R921932000 R921934000 R929991000 R941460000 R941461000 R941463600 R941920600 R948160000 31B-2-RED 032-0016-023 105
1106-001 108-1000-106 108-2301-621 66001-9 7013 1395080-1 930166100 NYS508-GR NYS508-V NYS508-W NYS508-Y NYS511-R

BP30-2BR10-B PKG BP30-10-WT BP30-2BR-B PKG BP30Y-1 PKG R941049000 R941340000 R948141029