



### DOUBLE LEVEL TERMINAL BLOCKS

#### CPDL2.5




Double Level Terminal Jumpers / Marking on both levels

#### CPDL2.5(I.S)




Double Level Terminal Internally Shorted

#### CPDLG2.5



Top Level Feed-Through Bottom Level Grounding Circuit

#### CPDLG2.5(I.S)



4 Connection Ground Terminal

#### Dimensions & Weight

Width / Length	5 mm / 72.7 mm		5 mm / 72.7 mm		5 mm / 72.7 mm		5 mm / 72.7 mm	
Height w DIN Rail	35 x 7.5 mm 35 x 15 mm	49.6 mm 57.0 mm	49.6 mm 57.0 mm	49.6 mm 57.0 mm	49.6 mm 57.0 mm	49.6 mm 57.0 mm	49.6 mm 57.0 mm	49.6 mm 57.0 mm
Weight per piece	10.0 g		12.4 g		13.6 g		15.5 g	

#### Technical Data/Ratings

Approvals								
Wire Size (solid / stranded)	24-12 AWG	0.2-2.5 mm <sup>2</sup>	24-12 AWG	0.2-2.5 mm <sup>2</sup>	24-12 AWG	0.2-2.5 mm <sup>2</sup>	24-12 AWG	0.2-2.5 mm <sup>2</sup>
Voltage Rating	600 V	1000V AC/DC	600 V	1000V AC/DC	600 V	1000V AC/DC	600 V	1000V AC/DC
Current Rating	20 A	24 A	20 A	24 A	20 A (Top Level)	24 A (Top Level)	–	–
Insulation Material	Polyamide 66		Polyamide 66		Polyamide 66		Polyamide 66	

#### Installation Instructions

Wire Stripping Length	10 mm		10 mm		10 mm		10 mm	
Screwdriver	SCM0.5/3.0 (0.5 x 3.0 mm blade)		SCM0.5/3.0 (0.5 x 3.0 mm blade)		SCM0.5/3.0 (0.5 x 3.0 mm blade)		SCM0.5/3.0 (0.5 x 3.0 mm blade)	

Terminal Blocks	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
<b>Grey (standard)</b>	<b>CPDL2.5</b>	50	<b>CPDL2.5(I.S)</b>	50	–	–	–	–
Red R	CPDL2.5/R	50	CPDL2.5(I.S)/R	50	–	–	–	–
Blue BU	CPDL2.5/BU	50	CPDL2.5(I.S)/BU	50	–	–	–	–
Black BL	CPDL2.5/BL	50	CPDL2.5(I.S)/BL	50	–	–	–	–
Orange O	CPDL2.5/O	50	CPDL2.5(I.S)/O	50	–	–	–	–
Green G	CPDL2.5/G	50	CPDL2.5(I.S)/G	50	–	–	–	–
Yellow Y	CPDL2.5/Y	50	CPDL2.5(I.S)/Y	50	–	–	–	–
White W	CPDL2.5/W	50	CPDL2.5(I.S)/W	50	–	–	–	–
<b>Ground/ Earth</b>	–	–	–	–	<b>CPDLG2.5</b>	50	<b>CPDLG2.5(I.S)</b>	50
Yellow / Green	–	–	–	–	–	–	–	–

Jumpers	Cat. No.	Imax	Std. Pk.	Cat. No.	Imax	Std. Pk.	Cat. No.	Imax	Std. Pk.	Cat. No.	Imax	Std. Pk.	
Shorting Link/	2 pole	JX2.5/2	24A	100	JX2.5/2	24A	100	JX2.5/2	24A	100	JX2.5/2	24A	100
Jumpers	3 pole	JX2.5/3	24A	50	JX2.5/3	24A	50	JX2.5/3	24A	50	JX2.5/3	24A	50
	4 pole	JX2.5/4	24A	50	JX2.5/4	24A	50	JX2.5/4	24A	50	JX2.5/4	24A	50
	5 pole	JX2.5/5	24A	50	JX2.5/5	24A	50	JX2.5/5	24A	50	JX2.5/5	24A	50
	6 pole	JX2.5/6	24A	10	JX2.5/6	24A	10	JX2.5/6	24A	10	JX2.5/6	24A	10
	7 pole	JX2.5/7	24A	10	JX2.5/7	24A	10	JX2.5/7	24A	10	JX2.5/7	24A	10
	8 pole	JX2.5/8	24A	10	JX2.5/8	24A	10	JX2.5/8	24A	10	JX2.5/8	24A	10
	10 pole	JX2.5/10	24A	10	JX2.5/10	24A	10	JX2.5/10	24A	10	JX2.5/10	24A	10

Accessories	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
End Plate	EPCXDL2.5	50	EPCXDL2.5	50	EPCXDL2.5	50	EPCXDL2.5	50
Tree Marking Carrier	TM5	50	TM5	50	TM5	50	TM5	50
DIN Rail	2511120 CA701-15/S	20 20	2511120 CA701-15/S	20 20	2511120 CA701-15/S	20 20	2511120 CA701-15/S	20 20
End Stop	CA103 / CA104	50	CA103 / CA104	50	CA103 / CA104	50	CA103 / CA104	50
Test Plug	TX2.5	20	TX2.5	20	TX2.5	20	TX2.5	20
Marking Tag	MT5	1 Pk. (100 tags)	MT5	1 Pk. (100 tags)	MT5	1 Pk. (100 tags)	MT5	1 Pk. (100 tags)

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [DIN Rail Terminal Blocks](#) category:*

*Click to view products by [Altech](#) manufacturer:*

Other Similar products are found below :

[00110420202](#) [00175550302](#) [8WA1011-1BH23](#) [8WA1011-1EF20](#) [91.040](#) [9123140000](#) [RBO 5-T-B-HEX](#) [1333564](#) [DP25-GY-ND](#) [1431306](#)  
[HSL-TB64-DIN](#) [90.070](#) [90.202](#) [912314](#) [260-301\\_NR](#) [2757571](#) [280-331](#) [280-560](#) [280-564](#) [281-611/281-542](#) [281-673/281-411](#) [281-994](#)  
[283-317](#) [283-607](#) [2948995](#) [264-724](#) [264-726](#) [280-530](#) [280-555](#) [280-619](#) [281-610](#) [281-622/281-417](#) [284-317](#) [284-601](#) [2907033](#) [5542152](#)  
[35956](#) [USK 10](#) [102510](#) [5520682](#) [5607102](#) [EMH 25-ZE30](#) [591620-2](#) [UM 45-SEFE M.NUT BK](#) [1-591651-1](#) [8671050000](#) [264-706](#) [280-575](#)  
[281-664](#) [592814-1](#)