

# AMAX-4850

# AMAX-4860

## 16-ch IDI & 8-ch PhotoMOS EtherCAT Remote I/O module

## 8-ch IDI & 8-ch Relay EtherCAT Remote I/O module



AMAX-4850



AMAX-4860



### Features

- Suitable for EtherCAT networks
- 16-ch digital input and 8-ch PhotoMOS Relay output (Form A)
- 1500 V<sub>DC</sub> optical isolation for relay outputs
- Quick removable European type connector
- LED indicators for I/O status
- Supports EtherCAT Distributed Clock (DC) mode and SyncManager mode
- Two Rotary switches for up to 256 slave IDs

### Introduction

The AMAX-4850 is an industrial EtherCAT slave module equipped with the EtherCAT protocol. Its compact size and DIN-rail mount kit can install easily in a cabinet. Euro type pluggable terminal blocks and LED indicator help users to maintain and set up their system. All digital input and PhotoMOS Relay Output channels are protected by isolation circuits.

### Specifications

#### Communication

- **Interface** EtherCAT
- **Data transfer medium** Ethernet/EtherCAT cable (min. CAT 5), shielded
- **Distance between modules** Max. 100 m (100BASE-TX)
- **Communication Cycle Time** 200µs
- **Data transfer rates** 100 Mbps
- **Configuration** Not required

#### Digital Input

- **Channels** 16
- **Input voltage** Logic 0: 3 V max.; Logic 1: 10 V min. (30 V max.)
- **Isolation protection** 2,500 V<sub>DC</sub>

#### PhotoMOS Relay Output

- **Channels** 8
- **Relay type** PhotoMOS SPST(Form A)
- **Load Voltage** 60V (AC peak or DC)
- **Load current** 1.2A
- **Peak load current** 4A @100ms(1 pulse)
- **Isolation protection** 1,500 V<sub>DC</sub>
- **Turn-on time** 1 ms typical
- **Turn-off time** 0.6 ms typical

#### General

- **Connectors** 10-pin 3.81 mm terminal block \* 4 (I/O)  
3-pin 3.81 mm screw terminal block (power)  
RJ-45 \* 2 (EtherCAT)
- **Dimensions** 120 mm x 120 mm x 40 mm
- **Operating temperature** -20 ~ 60°C (32 ~ 140°F)
- **Storage temperature** -40 ~ 70°C (-40 ~ 158°F)
- **Storage humidity** 5 ~ 95% RH (non-condensing)
- **Power supply** 10 ~ 30 V<sub>DC</sub>
- **Power Consumption** Typical 85mA @24V; Max. 110mA @24V

### Ordering Information

- **AMAX-4850-AE** 16 IDI & 8 PhotoMOS EtherCAT Remote I/O module
- **96PSD-A40W24-MM** DIN RAIL A/D 100-240V 40W 24V

### Features

- Suitable for EtherCAT networks
- 8-ch Isolated Digital Input and 8-ch Form A-type Relay Output
- High-voltage isolation on input channel (2,500 V<sub>DC</sub>)
- Quick removable European type connector
- LED indicators for I/O status
- Supports EtherCAT Distributed Clock (DC) mode and SyncManager mode
- Two Rotary switches for up to 256 slave IDs

### Introduction

The AMAX-4860 is an industrial EtherCAT slave module equipped with the EtherCAT protocol. Its compact size and DIN-rail mount kit can install easily in a cabinet. Euro type pluggable terminal blocks and LED indicator help users to maintain and set up their system. All digital input channels are protected by 2,500 V<sub>DC</sub> isolation circuits.

### Specifications

#### Communication

- **Interface** EtherCAT
- **Data transfer medium** Ethernet/EtherCAT cable (min. CAT 5), shielded
- **Distance between modules** Max. 100 m (100BASE-TX)
- **Data transfer rates** 100 Mbps
- **Configuration** Not required
- **Communication Cycle Time** 200µs

#### Digital Input

- **Channels** 8
- **Input voltage** Logic 0: 3 V max.; Logic 1: 10 V min. (30 V max.)
- **Isolation protection** 2,500 V<sub>DC</sub>

#### Relay Output

- **Channels** 8
- **Relay Type** Form A
- **Contact Rating (resistive)** 2A@250V<sub>AC</sub>, 2A@30V<sub>DC</sub>
- **Max. Switching Power** 500VA, 60W
- **Max. Switching Voltage** 270V<sub>AC</sub>, 125V<sub>DC</sub>
- **Resistance** 30mΩ max.
- **Operating Time** Max. 10ms
- **Releasing Time** Max. 5ms
- **Life Expectancy** Mechanical 2 x 10<sup>7</sup> ops. at no load.  
Electrical 3 x 10<sup>4</sup> ops. @2A/250V<sub>AC</sub>

#### General

- **Connectors** 10-pin 3.81 mm terminal block \* 3 (I/O)  
3-pin 3.81 mm screw terminal block (power)  
RJ-45 \* 2 (EtherCAT)
- **Dimensions** 120 mm x 120 mm x 40 mm
- **Operating temperature** -20 ~ 60°C (32 ~ 140°F)
- **Storage temperature** -40 ~ 70°C (-40 ~ 158°F)
- **Storage humidity** 5 ~ 95% RH (non-condensing)
- **Power supply** 10 ~ 30 V<sub>DC</sub>
- **Power Consumption** Typical 85mA @24V; Max. 110mA @24V

### Ordering Information

- **AMAX-4860-AE** 8-ch IDI & 8-ch Relay EtherCAT Remote I/O module
- **96PSD-A40W24-MM** DIN RAIL A/D 100-240V 40W 24V

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Controllers](#) category:*

*Click to view products by [Advantech](#) manufacturer:*

Other Similar products are found below :

[CS1WCN223](#) [CS1WCN713](#) [CS1WKS001E](#) [61F-11NH](#) [61FGPN8DAC120](#) [61F-GP-NT AC110](#) [61F-GPN-V50-AC110](#) [70177-1011](#) [F03-03](#)  
[HAS B](#) [F03-03 HAS C](#) [F03-31](#) [81513201](#) [81513535](#) [81550401](#) [FT1A-C12RA-W](#) [88981106](#) [H2CAC24A](#) [R88A-CAGA005S](#) [R88A-](#)  
[CRGB003CR-E](#) [R88ARR080100S](#) [R88A-TK01K](#) [DCN1-1](#) [DTB4896VRE](#) [DTB9696CVE](#) [DTB9696LVE](#) [MR-50LF+](#) [E53-AZ01](#) [E53E8C](#)  
[E5CWLQ1TCAC100240](#) [B300LKL21](#) [NE1ASCPU02EIPVER11](#) [NE1SCPU01](#) [NE1SDRM21U](#) [NSCXDC1V3](#) [NSH5-232CW-3M](#)  
[NT20SST122BV1](#) [NV3Q-SW41](#) [NV4W-ATT01](#) [NV-CN001](#) [OAS-160-N](#) [K31S6](#) [K33-L1B](#) [K3TX-AD31A](#) [L595020](#) [SRS2-1](#) [G32X-V2K](#)  
[26546803](#) [26546805](#) [26546831](#) [CJ1W-OD204](#)