



ISO9001:2008 Certified

Mechanical Specifications (mm)

D:	38.0	± Max
T:	10.0	± Max
Lead Diameter	2.5	± Nom
S:	19.0	± Nom
L:	40.0	± Nom
Coating Lead Run Down (straight Leads)	7.0	± Max
B:		±
C:	7.50	± Nom



Electrical Specifications

Resistance:	5.0	Ω	± 25 %
Max Steady State Current upto 65°C:	25.00	A	
Max Rec. Energy Rating:	600	J	
Actual Failure Instantaneous Energy:	1200	J	
Maximum Capacitance @ 120 VAC:	41,250	μf	
Maximum Capacitance @ 240 VAC:	10,419	μf	
Maximum Capacitance @ 440 VAC:	2,408	μf	
Maximum Capacitance @ 680 VAC:	1,200	μf	
Resistance @ 100% Max Current:	0.03	Ω	
Resistance @ 50% Max Current:	0.08	Ω	
Body Temperature at 100% Max Current:	212.00	°c	
Dissipation Constant:	102.5	mw/°c	
Thermal Time Constant:	134	Sec.	
Material Type (for Beta and Curve):	H		

MS35 5R025	
Date: 08/15/2012	Drawn by: Erin Landi
Ametherm, Inc. 3111 N. Deer Run Road Carson City, Nevada USA 89701 www.ametherm.com	Approved By: Mehdi Samii
	Revision:

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Inrush Current Limiters](#) category:

Click to view products by [Ametherm](#) manufacturer:

Other Similar products are found below :

[B57364S2509A002](#) [SL1580003](#) [MS15 15004](#) [MT8950AC](#) [B57364S121M](#) [SL22 20005-B](#) [B57237S0330M00](#) [AS35 1R040](#)
[B57153S0809M000](#) [CL-120AB](#) [CL-130A](#) [CL-80AB](#) [CL-140AB](#) [B57235S0809M000](#) [TG2512A](#) [AS32 0R530-100](#) [AS32 5R020](#) [MS15](#)
[30004](#) [MS15 40004](#) [MS22 10008-B](#) [MS22 12103](#) [MS22 20005](#) [MS22 22103](#) [MS22 75004](#) [MS32 0R536](#) [MS32 0R540](#) [MS32 10015](#) [MS32](#)
[15012](#) [MS32 1R036](#) [MS32 20010](#) [MS32 2R025](#) [MS32 50006](#) [MS32 5R020](#) [MS32 5R020-B](#) [MS32 7R015](#) [MS35 3R725](#) [SG100](#) [SG110](#)
[SG140](#) [SG200](#) [SG220](#) [SG240](#) [SG250](#) [SG260](#) [SG301](#) [SG302](#) [SG303](#) [SG311](#) [SG313](#) [SG32](#)