

SPECIFICATIONS: RESISTANCE AT 25 DEG C = 10 DHMS +/- 15% MAX CONTINUOUS CURRENT (Imax) = 5 AMPS RESISTANCE AT Imax = 0.20 DHMS NOMINAL MAX VOLTAGE RATING = 265 VAC (RMS) MAX SURGE RATING = 44 JOULES ENCAPSULATION = SILICONE RESIN MARKING = DPTIONAL LEADS = RODAN P/N STL-209-35

DRAWN BY D. NGUYEN		<u>AMETHERM</u>
DATE 11/05/90	orig. F. Tised	Circuit Protection Thermistors
REV A	APP	SURGE-GARD INRUSH CURRENT LIMITER
Sheet 1 of 1		SG338

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Inrush Current Limiters category:

Click to view products by Ametherm manufacturer:

Other Similar products are found below :

 B57364S2509A002
 SL1580003
 MS15 15004
 MT8950AC
 B57364S121M
 SL22 20005-B
 B57237S0330M00
 AS35 1R040

 B57153S0809M000
 CL-120AB
 CL-130A
 CL-80AB
 CL-140AB
 B57235S0809M000
 TG2512A
 AS32 0R530-100
 AS32 0R536-100
 AS32

 10015
 AS32 5R020
 AS35 10018
 MS15 30004
 MS22 12103
 MS22 20005
 MS22 22103
 MS22 75004
 MS32 0R536
 MS32 0R540
 MS32

 10015
 MS32 15012
 MS32 1R036
 MS32 20010
 MS32 20010-B
 MS32 2R025
 MS32 5R020
 MS32 5R020-B
 MS32 7R015

 MS35 3R725
 SG100
 SG110
 SG16
 SG200
 SG220
 SG240
 SG250
 SG301
 SG303
 SG311