

NOTES:



- MATERIALS AND FINISHES:
SMP R/A PLUG - BeCu, GOLD PLATING
CABLE - 0.085" CONFORMABLE
- ELECTRICAL:
A. IMPEDANCE: 50 OHM
- PACKAGING:
A. QUANTITY: SINGLE PACK
B. MARKING: BAG TO BE MARKED
"AMPHENOL RF, 95-725-117-XXX AND DATE CODE".

THIRD ANGLE PROJ.

REVISIONS

REV	DESCRIPTION	DATE	ECO	APPR
A	RELEASE TO MFG.	--	--	VR

PRELIMINARY ISSUE



LENGTH TABLE		
PART NUMBER (IMPERIAL)	PART NUMBER (METRIC)	LENGTH AND TOLERANCE "L" IN INCHES [METERS]
-	95-725-117M005	1.97 [0.050]
95-725-117-003	-	3.00 [0.076]
-	95-725-117M010	3.94 [0.100]
95-725-117-004	-	4.00 [0.102]
95-725-117-005	-	5.00 [0.127]
-	95-725-117M015	5.91 [0.150]
95-725-117-006	-	6.00 [0.152]
95-725-117-007	-	7.00 [0.178]
-	95-725-117M020	7.87 [0.200]
95-725-117-008	-	8.00 [0.203]
95-725-117-009	-	9.00 [0.229]
-	95-725-117M025	9.84 [0.250]
95-725-117-010	-	10.00 [0.254]
95-725-117-011	-	11.00 [0.279]
-	95-725-117M030	11.81 [0.300]
95-725-117-012	-	12.00 [0.305]
95-725-117-018	-	18.00 [0.457]
-	95-725-117M050	19.69 [0.500]
95-725-117-024	-	24.00 [0.610]
-	95-725-117M075	29.53 [0.750]
95-725-117-036	-	36.00 [0.914]
-	95-725-117M100	39.37 [1.000]
-	95-725-117M200	78.74 [2.000]
-	95-725-117M400	157.48 [4.000]

TOLERANCE TABLE	
LENGTH IN INCHES/FT [METERS]	TOLERANCE
0" - 23.90" [0 - 0.607]	±0.25" [0.006]
24.00" - 59.00" [0.610 - 1.499]	±0.50" [0.013]
5.0' - 24.9' [1.524 - 7.617]	±2.5%
25.0' & UP [7.620 & UP]	±5.0%

DESIGN REQUIREMENTS:

- FREQUENCY: DC - 20 GHz CONTINUITY
- VSWR: ____ MAX. HI-POT: 500 VRMS
- INS. LOSS: ____ dB MAX. OTHER

CUSTOMER OUTLINE DRAWING
ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE: 2 PLACE DECIMAL 3 PLACE DECIMAL ANGLES ±.015 (0,381 mm) ±.005 (0,127 mm) ± 1°	MATERIAL	DRAWN	DATE	TITLE SMP RA PLUG TO SMP RA PLUG USING 0.085" CONFORMABLE CABLE VARIOUS LENGTH SCALE: 2.5:1.0 SHEET 2 OF 2		Amphenol RF www.amphenolrf.com
	SEE NOTES	VIJAY N M	14-Jan-19			
NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. the furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.	REFERENCE	ENGINEER	DATE	DRAWING NO.95-725-117-XXX ITEM NO.95-725-117-XXX		
	EAR # 8856	VIJAY N M	14-Jan-19			
	CONFIGURATION LEVEL: In Work	APPROVED	DATE		PART NO.95-725-117-XXX	
FINISH		CAD FILE		DWG SIZE	REV	
				B	A	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [RF Cable Assemblies](#) category:

Click to view products by [Amphenol](#) manufacturer:

Other Similar products are found below :

[73-6352-10](#) [73-6353-3](#) [73-6364-6](#) [R285001001](#) [R288940004](#) [R288940005](#) [145111-05-12.00](#) [1661-C-24](#) [1801171170914KE](#) [24P104C24J1-012](#) [24P104C24P1-006](#) [24P104C24P1-018](#) [24P204C24J1-003](#) [172-2150-EX](#) [1800920920914PJ](#) [FCB-3030-ALT](#) [21117-046](#) [21117-050](#) [PCX-24-50](#) [24P103C24P2-003](#) [25P203C25P2-003](#) [PTWY-24-78](#) [R284008001](#) [R285001021](#) [R285426000](#) [R288940003](#) [R288940008](#) [RF179-74BJ3-77RP1-0305](#) [4814-BB-24](#) [5260-72](#) [JT2N1-CL1-1F](#) [DLP-COAX1](#) [4814-K-48](#) [115101-09-06.00](#) [CCNTN2-MM-LL335-26](#) [73-6351-25](#) [73-6352-3](#) [73-6353-25](#) [1800920920610PJ](#) [GD0BQ0BQ024.0](#) [1-3636-600-5210](#) [TL8A-11SMA-11SMA-01500-51](#) [R284C0351060](#) [R288940009](#) [R284C0351028](#) [R288940002](#) [9702-1SL-1](#) [PT82NSMA](#) [73-6353-10](#) [R285020301W](#)