

# MINITEK® ACTIVE LATCH HOUSING FOR WIRE-TO-BOARD CONNECTIONS

#### **OVERVIEW**

Minitek® is FCI's brand for board to board and cable/wire to board connectors in 2.00mm (0.079 $\mu$ in.) pitch. It is fully modular system enabling all types of connections between PCBs, wires and flat cables. Its 2mm spacing allows up to 38% space saving compared to traditional modular systems.

FCI is the leading supplier of this type of modular system and continues to grow and expand it. We are now adding a new active latch housing for wire-to-board applications.

The latch ensures a secure mechanical connection in applications with high extraction forces or vibration. Unlike other systems on the market, the active latch housing mates with the standard headers from the Minitek® system. This ensures full modularity and interchangeability throughout the system.

The active latch housing is made with high temperature black plastic material which is able to withstand temperature up to 125°C. It is available in 15 versions from 2 x 3 to 2 x 25 positions.



# MINITEK® ACTIVE LATCH HOUSING FOR WIRE-TO-BOARD CONNECTIONS

# **APPLICATION**




Crimp the terminal onto the wire.



Insert the terminals into the active latch housing.



Mate the active latch housing with the headers. It locks with a click.



Unmating can be effected by pressing the latch and removing the housing from the header.

# MINITEK® ACTIVE LATCH HOUSING FOR WIRE-TO-BOARD CONNECTIONS

### **TECHNICAL INFORMATION**

#### **MATERIALS**

· Housing: Polyamide

· Colour: Black

• Flammability rating: UL94V-0

#### **ELECTRICAL PERFORMANCE**

• Insulation resistance:  $1000M\Omega$  min

· Dielectric withstanding voltage: 500V

#### **ENVIRONMENTAL**

• Operating temperature range: -55°C to +125°C

### **PART NUMBERS**

10073599



**TOTAL POSITIONS** 



06, 08, 10, 12, 14, 16, 18, 20, 24, 26, 30, 34, 40, 44, 48, 50

Description	Part Numbers
Shrouded headers	98414
Shrouded headers	98424
Shrouded headers	10075025
Crimp to wire contacts	77138

#### **MECHANICAL PERFORMANCE**

- Latching retention force 15 N min. (for 2x3 & 2x4)
- Latching retention force 25 N min. (for 2x5 & 2x25)

#### **RoHS INFORMATION**

 This product is RoHS compliant according to the European Union Directive 2002/95/IEC

#### **SPECIFICATIONS**

• , **\$1** File no. E66906

• **G**. File no. LR46923

• Product drawing: By 8-digit base part number

• Product specification: GS-12-415

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Headers & Wire Housings category:

Click to view products by Amphenol manufacturer:

Other Similar products are found below:

892-18-020-10-001101 58102-G61-06LF 582553-1 0009485154 009176003701906 0050291907 LY20-4P-DT1-P1E-BR 02.125.8002.8

609-3404 61062-3 622-0430 622-3653LF 63453-116 636-1030 636-1427 636-3427 636-4007 641938-9 641991-4 644827-2 65817-010LF

65817-015LF 65863-015LF 66207-023LF 67095-007LF 67601157 68648-049 70.362.1628.0 70-4210 70-4226B 70-4853B 707-5020 707
5028 71.350.2428.0 71918-208LF 71961-016LF 733-134 733-162 754199-000 760-3052 787-8014-00 79531-3000 FCN-360C032-B FCN
367T-T012/H FCN-723D010/2 80.063.4001.1 800-90-001-10-001000 800-90-010-10-002000 801-43-002-10-013000 801-43-006-10-002000