

# METRAL® HDXS

## OVERVIEW

Metral® HDXS is a cable-to-board connector designed for high-end telecom applications including Telecom Access Equipments (ADSL/VDSL) and Base Stations.

Metral® HDXS is designed with minimum guaranteed clearance and creepage distances to comply to ANSI requirements of resistibility to overvoltages of up to 2500V. It is ideal for use in ADSL/VDSL as well as for harsh environments and other demanding telecom applications requiring high density cable-to-board interface. Metral® HDXS provides interconnection for differential pairs with very low crosstalk.

Designed in accordance with IEC 61076-4-104, Metral® HDXS meets the performance requirement as per Telcordia GR-1217-CORE. It is available in 6 row version of right angle headers with press-fit and pin-in-paste terminations and cable connectors. Cable connectors kits are field installable.



## FEATURES

- Multiple headers & cable connector mating configuration
- Insert Molded Leadframe Assembly (IMLA) based design for header
- Mini press-fit pins for header
- Flat rock housing design for header
- Enhanced Header Connector Footprint
- Staggered pinning
- Die cast shells for cable connector
- Dual IDC termination, Dual lip contact and individual wire retention for cable connector
- Shielded cable connection to front panel
- Recess provision in cable connector allows entry of conductive bosses on the front panel
- Selective loading option for header and receptacle

## BENEFITS

- Enables size flexibility
- Enhances Signal Integrity (SI) performance
- Improves board routing
- Simplifies press-fitting process
- Allows horizontal and vertical routing and minimum layer count
- Clearance and creepage distances complies to ANSI requirements of resistibility to overvoltages of up to 2500V
- Robust and ruggedized design
- Provides high reliability
- Ensures Electromagnetic Compatibility (EMC)
- Guarantees electrical discharge before signal contacts are mated
- Custom loading SI performance



## TECHNICAL INFORMATION

### MATERIALS

- Housing: High temperature thermoplastic; UL 94V-0 compliant
- Contacts: Copper Alloy
- Plating: Performance-based plating
- Covers: Die cast metal

### ELECTRICAL PERFORMANCE

- Contact Resistance: 55 mΩ max.
- Insulation Resistance: 5000 MΩ min.
- Current Rating: 0.8A (all contacts powered)

### ENVIRONMENTAL

- Operating Temperature: -55°C to +85°C

### SPECIFICATIONS

- Product Specification: GS-12-485
- Application Specification: GS-20-091

### MECHANICAL PERFORMANCE

- Mating Force: 36N max for 24 pair
- Unmating Force: 7.2N min for 24 pair

### APPROVALS AND CERTIFICATIONS

- Designed in accordance with IEC 61076-4-104
- Telcordia GR-1217-CORE standards

### TARGET MARKETS/APPLICATIONS

- Telecom

### PACKAGING

- Tube packaging for headers
- Cable connector as kits with components in tray packaging

## PART NUMBERS

Rows	Board Header		Cable Connector	
	Part Number	Number of Pairs	Part Number	Number of Pairs
6	10075388-101LF	24 pair	10078794-101LF	24 pair
			10090081-101LF	48 pair
			10076192-101LF	72 pair

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [High Speed/Modular Connectors](#) category:*

*Click to view products by [Amphenol](#) manufacturer:*

Other Similar products are found below :

[650827-1](#) [74040-1346](#) [1410191-1](#) [1410337-1](#) [1410368-3](#) [1410964-2](#) [1410326-3](#) [1410367-3](#) [1410971-4](#) [1467833-1](#) [2000877-1](#) [2000878-1](#)  
[2041314-1](#) [2065387-1](#) [2187307-1](#) [163P](#) [1934290-1](#) [2000875-1](#) [2065917-1](#) [2102736-2](#) [FSR-40](#) [2169868-2](#) [22354-8](#) [437-5040-000](#) [5-](#)  
[1393565-0](#) [039-0246-000](#) [0761601016](#) [0784461022](#) [10123159-12ELF](#) [030-2415-003/100 PK](#) [030-7380-004](#) [030-2494-001](#) [532939-1](#)  
[5532901-3](#) [3-1469268-7](#) [74748-102LF](#) [73670-0247](#) [10041743-101LF](#) [10066670-100002LF](#) [1-533915-1](#) [249-4515-000](#) [7-1469373-3](#) [DL2-](#)  
[2J/S](#) [2000713-8](#) [2000713-7](#) [3011-21](#) [757105208](#) [EBTF-4-10-2.0-S-RA-1](#) [430305-001](#) [4395800100](#)