

Universal Contact

OVERVIEW

The single spring contact to connect the designed device, such as an antenna to a printed circuit board assembly, this makes it easier for customers to design the board. Single position connector provides a means to electrically connect a device.

The single position spring contact is an excellent means to electrically connect devices, such as an antenna to a printed circuit board assembly, giving customers high flexibility to design the board.



FEATURES

- In accordance with FCI GS-12-500

- Single contact without housing is helpful for customer to make the device thinner

- Various contact height allows customer to design various operation height

BENEFITS

- Domed contact points for good normal force and low contact resistance

- Solderwell design prevents solder wicking up the contact

- Freedom to position part – no fixed mating interface





TECHNICAL INFORMATION

MATERIALS

- Beryllium/Titanium Copper Alloy
- Contact Area: 40u" Gold or 40u" GXT over Nickel
- Solder Area: Gold Flash over Nickel

ELECTRICAL PERFORMANCES

- Rated Voltage: Maximum 12V
- Rated Current: 2 Amps @ 30 °C
- Contact Resistance: 20 Milliohms Maximum

ENVIRONMENTAL

- Operating Temperature Range: - 40 °C to + 85 °C without loss of function
- Storage Temperature Range: - 40 °C to + 85 °C without loss of function at operating temperatures

MECHANICAL PERFORMANCES

Universal Contacts

Part Number	Spring Height (mm)	Pre-load Apply Load (N)	Pre-load Un-Appling Load (N)	Max Deflection (mm)	Minimal Normal Force @ max Deflection (N)	Spring Rate (N/mm)
10123973-00*RLF	1.2	-	-	0.65	0.6	0.92
10094594-00*RLF	1.3	0.78	0.58	0.32	0.87	1.2
10104320-00*RLF	1.3	0.41	0.36	0.4	0.7	1.5
10115748-00*RLF	1.55	0.44	0.26	0.6	0.73	0.78
10103955-00*RLF	1.8	0.35	0.15	0.8	0.75	0.74
10128200-00*RLF	2.1	0.5	0.36	0.45	0.6	0.67
10104319-00*RLF	2.5	0.42	0.31	1	0.54	0.32
10104321-00*RLF	3.5	0.56	0.38	1.3	1.02	0.49

SPECIFICATIONS

- GS-12-500

PACKAGING

- Reel & Tape

TARGET MARKETS/APPLICATIONS

- Consumer
 - Smartphone
 - Wearable Device
 - Gaming Device
 - Tablet
- Industrial & Instrumentation
 - LED lighting
 - Switch

PART NUMBERS

40u" Gold Plating	40u" GXT Plating
XXXXXXXX-001RLF	XXXXXXXX-009RLF

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Power to the Board](#) category:

Click to view products by [Amphenol](#) manufacturer:

Other Similar products are found below :

[6450171-4](#) [6450552-7](#) [6600323-8](#) [6643429-1](#) [6646040-2](#) [6651939-1](#) [6766604-1](#) [120959-1](#) [1393557-2](#) [1393532-2](#) [1393532-3](#) [1393532-4](#)
[1393557-1](#) [1600812-5](#) [1-6450861-2](#) [1744132-7](#) [1761122-1](#) [1766250-1](#) [1892109-1](#) [2-6450860-5](#) [2-6450870-0](#) [1-6450161-4](#) [1-6450850-6](#) [1-6450869-6](#) [1645526-2](#) [1-6600130-0](#) [2005243-2](#) [TE34-12-16P-F0](#) [5-6450830-6](#) [5646956-4](#) [4-6450830-9](#) [4-6600333-3](#) [10125416-4050LF](#)
[6600320-3](#) [3-6450860-5](#) [1888123-2](#) [6450166-1](#) [6643978-1](#) [6766605-1](#) [N11444](#) [6651938-1](#) [6450810-7](#) [46437-1112](#) [1-1589677-8](#) [5646956-5](#)
[6450813-2](#) [6450129-4](#) [1645523-1](#) [PSS-06-01-T-S](#) [0465621864](#)