

# BergStak® 0.8mm Mezzanine Connector

Extraordinary product range, Benchmark performance, Dual-source champion

## FLEXIBLE SOLUTION FOR HIGH DENSITY APPLICATIONS

Amphenol's BergStak® 0.8mm is a flexible solution designed for high speed and high density, parallel board-to-board connector system with 16 PCB stack heights in 9 sizes up to 200 positions.

- Housing and terminal profile guarantees support of up to 12Gb/s
- Vertical versus vertical mating configuration
- 40 to 200 position sizes in 20 position increments
- 5mm to 20mm stack heights in 1mm increments



## FEATURES

- Housing and terminal profile guarantees support of up to 12Gb/s
- Vertical versus vertical mating configuration
- 40 to 200 position sizes in 20 position increments
- 5mm to 20mm stack heights in 1mm increments
- 0.8mm double-row contact pitch conserves printed circuit board space
- Scoop-proof feature housings
- Multiple plating options available
- Multiple packaging options available
- PCB locator pegs option
- Available in UL94-V0 material
- RoHS compliant and lead-free

## BENEFITS

- Compatible with PCIe Gen 2/3 and SAS 3.0 high speed performance on selected stack heights
- Suitable for parallel board stacking applications
- Comprehensive range of sizes and stack heights to satisfy all needs
- High density for all electrical applications needs
- Prevents reverse mating
- Satisfies different application requirement
- Suitable for varies feeding processing
- Facilitates ease and accuracy during manual assembly
- High flammability rating
- Meets environmental, health and safety requirements

\*The PCIe® mark is a registered trademark of the PCI-SIG Corp

## TECHNICAL INFORMATION

### MATERIAL

- Housing: Glass filled LCP, UL94V-0
- Contact Base Metal
  - Receptacle: Copper Alloy, High Spring
  - Plug: Brass
- Contact Area Finish: Gold or Gold flash over Palladium-nickel (GXT) over Nickel
- Solder Area Finish: Matte pure Tin over Nickel

### MECHANICAL PERFORMANCE

- Durability: 100 mating cycles
- Mating Force: 0.9N max./contact
- Unmating Force: 0.1N min./contact

### ELECTRICAL PERFORMANCE

- Insulation Resistance:
  - Initial: 1000M $\Omega$  min.
  - After Test: 100M $\Omega$  min.
- Current Rating: 0.8A/contact
- Contact Resistance:
  - Initial: 30m $\Omega$  max.
  - After Test: 50m $\Omega$  max.
- Voltage Rating: 100VAC
- Signal Integrity (Differential pairs, connector and SMT pads only)
  - Impedance Range: 81 to 108 $\Omega$  @ 50 ps edge (10-90%)
  - Return Loss: < 10dB up to 5GHz
  - Insertion Loss: < 1.5dB up to 5GHz
  - NEXT:  $\leq$  4.0% for a 50 ps edge (10-90%)
  - FEXT:  $\leq$  2.4% for a 50 ps edge (10-90%)

### ENVIRONMENTAL

- Temperature Range: -40°C to +125°C
- High Temperature Life: 105°C  $\pm$  5°C for 1000 hours
- Humidity: 90-95% relative humidity for 96 hours
- Mixed Flowing Gas Class 2a (30 GXT)

### APPROVALS AND CERTIFICATIONS

- UL E66906
- File no. LR46923

### SPECIFICATIONS

- Product Specification: GS-12-547
- Test Report: DGS-29-010

### PACKAGING

- Tape & Reel
- Tubes

### TARGET MARKETS/APPLICATIONS



IP Phone  
Router



Server




Industrial and Instrumentation  
Office Equipment  
Point-Of-Sale Terminal  
Portable Industrial Terminal  
Test and Measurement



Diagnostics System


## RECEPTACLE



Early-contact point allows early engagement/ late disengagement and increases mating wipe

Precision-tapered contacts control mating stress while providing reliable, high normal force

## HEADER



Coined contact tips assure smooth, safe wiping action during connector mating

# PART NUMBER SELECTOR

XXXXX		XX		X	X	X	X	X																																			
<b>BASE PART NUMBER</b>		<b>TOTAL POSITIONS</b>		<b>HOUSING HEIGHT</b>	<b>PLATING CODE</b>	<b>PEG OPTION</b>	<b>PACKAGING OPTION</b>	<b>LF</b>																																			
<table border="1"> <tr><td>Receptacle</td><td>61082</td></tr> <tr><td>Plug</td><td>61083</td></tr> </table>		Receptacle	61082	Plug	61083	<table border="1"> <tr><td>40 pos</td><td>04</td></tr> <tr><td>60 pos</td><td>06</td></tr> <tr><td>80 pos</td><td>08</td></tr> <tr><td>100 pos</td><td>10</td></tr> <tr><td>120 pos</td><td>12</td></tr> <tr><td>140 pos</td><td>14</td></tr> <tr><td>160 pos</td><td>16</td></tr> <tr><td>180 pos</td><td>18</td></tr> <tr><td>200 pos</td><td>20</td></tr> </table>		40 pos	04	60 pos	06	80 pos	08	100 pos	10	120 pos	12	140 pos	14	160 pos	16	180 pos	18	200 pos	20	<table border="1"> <tr><td>Tube without metal cap</td><td>0</td></tr> <tr><td>Tape &amp; Reel with metal caps</td><td>2</td></tr> <tr><td>Tape &amp; Reel without metal cap (with Kapton tape)</td><td>6</td></tr> <tr><td>Tube with metal caps</td><td>9</td></tr> </table>		Tube without metal cap	0	Tape & Reel with metal caps	2	Tape & Reel without metal cap (with Kapton tape)	6	Tube with metal caps	9	<table border="1"> <tr><td>Includes polarization pegs</td><td>0</td></tr> </table>		Includes polarization pegs	0	<table border="1"> <tr><td>Lead-free, RoHS compatible</td><td>LF</td></tr> </table>		Lead-free, RoHS compatible	LF
Receptacle	61082																																										
Plug	61083																																										
40 pos	04																																										
60 pos	06																																										
80 pos	08																																										
100 pos	10																																										
120 pos	12																																										
140 pos	14																																										
160 pos	16																																										
180 pos	18																																										
200 pos	20																																										
Tube without metal cap	0																																										
Tape & Reel with metal caps	2																																										
Tape & Reel without metal cap (with Kapton tape)	6																																										
Tube with metal caps	9																																										
Includes polarization pegs	0																																										
Lead-free, RoHS compatible	LF																																										
				<table border="1"> <tr><td>Gold 0.2um min./Pure Tin 2um min. (Lead-free) Nickel underplate overall 1.27um min.</td><td>4</td></tr> <tr><td>Gold 0.38um min./Pure Tin 2um min. (Lead-free) Nickel underplate overall 1.27um min.</td><td>5</td></tr> <tr><td>Gold Flash (0.1um min.) over Palladium-Nickel 0.76um min./Pure Tin 2um (Lead-free) Nickel underplate overall 1.27um min.</td><td>6</td></tr> </table>		Gold 0.2um min./Pure Tin 2um min. (Lead-free) Nickel underplate overall 1.27um min.	4	Gold 0.38um min./Pure Tin 2um min. (Lead-free) Nickel underplate overall 1.27um min.	5	Gold Flash (0.1um min.) over Palladium-Nickel 0.76um min./Pure Tin 2um (Lead-free) Nickel underplate overall 1.27um min.	6																																
Gold 0.2um min./Pure Tin 2um min. (Lead-free) Nickel underplate overall 1.27um min.	4																																										
Gold 0.38um min./Pure Tin 2um min. (Lead-free) Nickel underplate overall 1.27um min.	5																																										
Gold Flash (0.1um min.) over Palladium-Nickel 0.76um min./Pure Tin 2um (Lead-free) Nickel underplate overall 1.27um min.	6																																										

X	FOR PLUG, SEE DWG. NO. 61083			
COMBINATION OF MATED HEIGHT	Plug 1 	Plug 2 	Plug 3 	Plug 4 
Recep 1 				
Recep 2 				
Recep 3 				
Recep 4 				

BWBBERG08087EA4

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Board to Board & Mezzanine Connectors](#) category:*

*Click to view products by [Amphenol](#) manufacturer:*

Other Similar products are found below :

[589158040000018](#) [MDF7C-18P-2.54DSA\(55\)](#) [FCN-230C068-11](#) [FCN-268F012-G/BD](#) [FCN-268F036-G/BD](#) [FCN-268M012-G/0D](#) [FCN-268M024-G/1D](#) [FCN-723J004/1](#) [MIS-048-01-F-D-DP-K](#) [832-10-034-10-001000](#) [FX4C-80S-1.27DSA](#) [FCN-214Q030-G/0](#) [FCN-234P048-G/0](#) [FCN-235D050-G/C](#) [210-93-314-41-105000](#) [2-22603-0](#) [MDF7-40DP-2.54DSA\(55\)](#) [AXG720047](#) [MIT-114-03-F-D-K](#) [55323-1519](#) [DF33-2P-3.3DSA\(24\)](#) [YFT-20-05-H-03-SB-K](#) [503308-3040](#) [026-6203-PDB](#) [027-6203-PDB](#) [069159702701000](#) [10123981-102LF](#) [101A10019X](#) [55650-0588-C](#) [68682-310LF](#) [68684-306](#) [75140-7012](#) [87471-650](#) [YTW-30-07-H-Q-410-140](#) [FCN-268F024-G0D](#) [10124054-515LF](#) [68685-603](#) [8-1616154-3](#) [MIS-019-01-F-D](#) [FCN-268M024-G/3D](#) [FCN-268M036-G/BD](#) [20021832-06016C1LF](#) [KX15-20KLDL-E1000E](#) [AXE810124](#) [FCN-214J100-G/0](#) [FCN-230C068-E/S](#) [AXE812124](#) [AXE816124](#) [AXE720127](#) [354184](#)