# **INDUSTRIAL MINI I/O CONNECTOR**



# HIGHLY RELIABLE, FIELD INSTALLABLE AND COMPACT I/O SOLUTION

Industrial Mini I/O connector is a compact wire-to-board interface which is field installable in virtually any environment.

- Field installable plug kit
- One quarter the size of a conventional RJ45
- Highly reliable connection with 2 points of contact per line
- Two unique interfaces to prevent mismating
- Unique locking feature with high cable retention force within the metal housing, resulting in minimal space required



#### **TARGET MARKETS**



FEATURES	BENEFITS
<ul> <li>Compact size compared to conventional RJ45</li> </ul>	- Saves up to 75% space
2 points of contact per line	<ul> <li>Reduce contact failure</li> <li>Enable increased productivity and continuity in high vibration environment</li> </ul>
<ul> <li>Unique locking feature with high cable retention force</li> </ul>	<ul> <li>Protects plug from accidental pulling and unplugging</li> <li>Prevents expensive downtime in an industrial environment</li> </ul>
• Plug kit field installable	<ul> <li>Time saving termination</li> <li>Easy to use hand tool which allows field assembly in virtually any environment</li> </ul>
Two unique interfaces	Prevents mismating
• Up to 1500 mating cycles	- Enhanced durability
• Versatile solution supporting a wide variety of applications	<ul> <li>Ideal for PLCs, Robotics, Industrial communications, Motion and Drives</li> </ul>
<ul> <li>High temperature thermoplastic housing</li> </ul>	<ul> <li>Ensures high temperature resistance</li> </ul>

# **► INDUSTRIAL MINI I/O CONNECTOR**

### TECHNICAL INFORMATION

#### **MATERIAL**

• Housing: High Temperature Thermoplastic

■ Shell: Copper Alloy

• Terminal: Copper Alloy

#### **MECHANICAL PERFORMANCE**

• Durability: up to 1500 mating cycle

Extraction Force: 98N min.Cable Diameter: 7.1mm max.

■ Wire Size: 24AW

#### **PACKAGING**

Trays

#### **ELECTRICAL PERFORMANCE**

Rated Voltage: 30VCurrent Rating: 0.5A

#### **ENVIRONMENTAL**

■ Operating Temperature : -40°C to +85°C

#### **SPECIFICATIONS**

■ Standard : IEC/PAS 61076-3-122 & ANSI/TIA-568.C.2

#### **TARGET MARKETS/APPLICATIONS**



Industrial Communications
Motion and Drivers
PowerLine Communication (PLC) Connections
Robotics

# **PART NUMBERS**

Description	Packaging	Part Numbers
Industrial Mini I/O 1.27mm pitch header assembly, Type I	Tray	10137237-001LF
Industrial Mini I/O 1.27mm pitch header assembly, Type II	Tray	10137237-002LF
Industrial Mini I/O 1.27mm pitch, SMT, vertical, Type I	Tray without cap	10137238-0010LF
Industrial Mini I/O 1.27mm pitch, SMT, vertical, Type I	Tray with cap	10137238-0011LF
Industrial Mini I/O 1.27mm pitch, SMT, vertical, Type II	Tray without cap	10137238-0020LF
Industrial Mini I/O 1.27mm pitch, SMT, vertical, Type II	Tray with cap	10137238-0021LF
Mini Industrial I/O plug kit, Type I, insulation diameter 1.05-1.15mm	Tray/Box	10137239-0010LF
Mini Industrial I/O plug kit, Type I, insulation diameter 0.93-1.05mm	Tray/Box	10137239-0011LF
Mini Industrial I/O plug kit, Type I, insulation diameter 1.10-1.20mm	Tray/Box	10137239-0012LF
Mini Industrial I/O plug kit, Type II, insulation diameter 0.93-1.05mm, IPC: 1.05-1.15mm	Tray/Box	10137239-0013LF
Mini Industrial I/O plug kit, Type II, insulation diameter 1.05-1.15mm	Tray/Box	10137239-0020LF
Mini Industrial I/O plug kit, Type II, insulation diameter 0.93-1.05mm	Tray/Box	10137239-0021LF

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for I/O Connectors category:

Click to view products by Amphenol manufacturer:

Other Similar products are found below:

571763P 58098-0628 72.250.1628.2 72.250.2428.2 74720-0505 76.350.0729.0 76871-1403 FCN-244F080-G/1 FCN-260A9920 PCR-E36PM PCS-XE26MA+ G38A71314B 1571250010 157-22500-3 MS3471L14-19P L/C 192991-0703 172501-4002 172501-6002 FCN-260C008-A/L0 FCN-260C024-AL0 FCN-261Z008 2000314-1 200331-1 PCR-E36FC+ PCS-E28FS+ PCS-XE26SLFD+ PCS-XE26SLFD+ PCS-XE26SLFD+ G730VID08BDC24 U90B2054081210 UE86K842720321 38113800006 DP3AR020WQ1R200 Z4.102.0680.0 500-1040 500-1052 500-1054 ZP-4008-66L 0709821002 DX40-20P(55) 5554841-1 MS3474W18-8P-LC\* SM3106F14S-7S-LC U90B3054061110 U65-E04-4020 ZPF0000000000097891 557-262M2-06C 747360449 10099439-003C-TRLF 10137239-0021LF E9320-001-01