≣FCi Basics

Amphenol ICC

BergStak® FX10 0.50mm Board-to-Board Connector

HIGH SPEED HIGH DENSITY MINIATURE CONNECTOR

The BergStak® product range is expanded to include 0.50mm BergStak® FX10 board-to-board connector known for its fast data transmission and high signal quality. This connector is offered in 144 positions and is available in 4.30mm and 6.00mm stack height options. Product position is extendable up to 168positions.

BergStak® FX10 supports speed performance up to 15Gb/s+ and is available in vertical SMT configuration. This high density connector saves space on PCB and is highly suitable for high-density applications in automotive, data, medical, communication and industrial markets.

- Licensed to Hirose FX10 series
- Data transmission speed up to 15Gb/s+
- Suitable for high density applications



TARGET MARKETS



FEATURES

- Authorized second source to Hirose FX10 series
- High speed performance up to 15Gb/s+
- Suitable for high-density applications
- OIF MSA-100GLH electrical interface
- Hold-down feature
- Halogen-free and RoHS compliant

BENEFITS

- Fully compatible with Hirose product offering
- Meets next generation high speed transmission requirements
- Saves space
- Standard connector for OIF
- Robust and steady design for customer application
- Meets environmental, health and safety requirements

TECHNICAL INFORMATION

MATERIAL

- Housing:
 - Glass filled LCP (UL94V-0, MSL level 1)
 - High temperature thermoplastic
- Contact Base Metal:
 - Receptacles: Copper alloy
- Headers: Copper alloy
- Plating:
- Solder area finish in gold flash tin over nickel
- Contact Area: Gold

MECHANICAL PERFORMANCE

- Durability: 100 cycles
- Mating and Un-mating Force: 86.4N max. and 11.5N min.

ELECTRICAL PERFORMANCE

- Current Rating: 0.4A per contact
- Contact Resistance: 60m Ω max.
- Voltage Resistance: 150V AC applied for 1 minute
- Signal Integrity:
- Data Rate: Up to 15Gb/s+
- Differential Impedance: 100 Ω
- Single Ended Impedance: 50 Ω

SPECIFICATIONS

Amphenol Product Specification: GS-12-1529

ENVIRONMENTAL

- Industrial Atmosphere: Duration 14days
- Vibration Sinusoidal: 10g
- Shock Halfsine: 50g

APPROVALS AND CERTIFICATIONS

UL/CSA E66906

PACKAGING

• Tape & Reel

TARGET MARKETS/APPLICATIONS



Display Module Camera Body Control



IP Phones Datacom Telecom Router



Drone



Server Storage



Measurement Equipment POS Equipment Portable Industrial Terminal Security Systems Test Equipment Embedded Computer



Laser System

www.amphenol-icc.com


Disclaimer

Please note that the above information is subject to change without notice.

BergStak® FX10 0.50mm Board-to-Board Connector

Stack Height Dimension "A"	Receptacle 1 10147523-XXX-1HLF
Header 1 10147520-XXX-SHLF	4.30mm
Header 2 10147520-XXX-THLF	6.00mm

XXX denotes the number of positions



PART NUMBERS

Description	Part Numbers
BergStak® FX10 0.50mm board-to-board header for 4.30mm stack height	10147520-144-SHLF
BergStak® FX10 0.50mm board-to-board header for 6.00mm stack height	10147520-144-THLF
Bergstak® FX10 0.50mm board-to-board receptacle	10147523-144-1HLF

www.amphenol-icc.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Board to Board & Mezzanine Connectors category:

Click to view products by Amphenol manufacturer:

Other Similar products are found below :

 589158040000018
 MDF7C-18P-2.54DSA(55)
 FCN-230C068-11
 FCN-268F012-G/BD
 FCN-268F036-G/BD
 FCN-268M012-G/OD
 FCN-234P048-G/O

 FCN-235D050-G/C
 210-93-314-41-105000
 2-22603-0
 MDF7-40DP-2.54DSA(55)
 AXG720047
 MIT-114-03-F-D-K
 55323-1519
 DF33-2P

 3.3DSA(24)
 YFT-20-05-H-03-SB-K
 503308-3040
 026-6203-PDB
 027-6203-PDB
 069159702701000
 10123981-102LF
 101A10019X

 55650-0588-C
 68682-310LF
 68684-306
 75140-7012
 87471-650
 YTW-30-07-H-Q-410-140
 FCN-268F024-G0D
 10124054-515LF
 68685

 603
 8-1616154-3
 MIS-019-01-F-D
 FCN-268M024-G/3D
 FCN-268M036-G/BD
 20021832-06016C1LF
 KX15-20KLDL-E1000E

 AXE810124
 FCN-214J100-G/0
 FCN-230C068-E/S
 AXE816124
 AXE720127
 354184