

MATERIAL:

BODY, & CONTACT:

BERYLLIUM COPPER PER ASTM B196, ALLOY No. UNS C17300, TD04

PTFE PER ASTM D1710, TYPE I, GRADE 1, CLASS B **INSULATOR:**

FINISH:

BODY &	GOLD PER ASTM B 488, TYPE II, CODE C, CLASS 1.27,
CONTACT:	OVER NICKEL PER AMS-QQ-N-290, CLASS 1, .00005" MIN.
	OVER NICRELPER AWS - QQ - N - 290, CLASS 1, .00005 WIIN.

PERFORMANCE:

IMPEDANCE: VSWR:	50 OHMS 1.15:1 DC TO 40 GHz TYPICAL 1.25:1 TO 65 GHz TYPICAL			
INSERTION LOSS: DWV: OPERATING TEMP.:	1.25.110 65 GH2 TTFICAL .12 X SQRT(F(F IN GHz)) 250 VRMS -55°C TO +165°C			

ENGAGEMENT: 3.5 LBS TYPICAL IN FULL DETENT 1.6 LBS TYPICAL IN SMOOTH BORE DISENGAGEMENT: 2.0 LBS TYPICAL IN FULL DETENT 0.5 LBS TYPICAL IN SMOOTH BORE

MATERIAL: SEE NOTES	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL: +1/64 ANGULAR: X° +1°0'	UNLESS O
FINISH: SEE NOTES	DECIMAL: X ±.030 .XX ±.010	1) ALL DIMENSIONS 2) ALL DIMENSIONS 3) BREAK CORNER 4) CHAM, 1ST & LAS
SURFACE AREA: N/A	.XXX ±.005 INTERPRET DIMENSIONS AND TOLERANCES	5) SURFACE ROUGI 6) DIA.'S ON COMMO WITHIN .005 T.I.R 7) REMOVE ALL BUI
PROPRIETARY	PER ASME Y14.5M - 1994	I) NEWOVE ALL DO
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SV MICROWAVE, INC.	THIRD ANGLE PROJECTION	DRAWN:
ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF		CHECKED
SV MICROWAVE, INC IS PROHIBITED.		APPROVE

THERWISE SPECIFIED		SV Microwave, Inc.				
IS ARE IN INCHES [MILLIMETERS] IS ARE AFTER PLATING. RS & EDGES .005 R. MAX. ST THREADS. AINLESS 63-MIL-STD-10. MON CENTERS TO BE CONCENTRIC R JRRS		2400 Centrepark West Drive, Suite 100 West Palm Beach, FL 33409				
		SMPS FEMALE TO FEMALE STRAIGHT ADAPTER				
FEI	FED 02/28/11					
D: ST	N 02/28/11	SIZE B	CAGE CODE 95077	DWG. NO.	1138-4	-003
ED: ST\	N 02/28/11	S	CALE: 40:1			SHEET 1 OF 1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for RF Adapters - In Series category:

Click to view products by Amphenol manufacturer:

Other Similar products are found below :

 5916-1103-603
 5918-1103-000
 5919-1503-000
 651A505
 82-5552
 9030-9523-502
 A0407000
 R114703000W
 R125704000
 R125771001

 R141710000W
 R141723161
 R141730000
 R143730700
 R143770000
 R161703000W
 R161753000W
 R161791530W

 R201705000
 R222705200
 R222M40010W
 R223703180
 R316754000
 R405006000
 R443162000
 AD78TL
 HRM-513S
 1996352-2

 2157155-1
 252169-75
 AD158
 2101130-1
 252186
 R114704000W
 R114720000W
 R125705001
 R125771000
 R125771001W

 R125791501W
 R127704001
 R127.870.001
 R127872001
 R141717000
 R142710000
 R143703000
 R143704000
 R143705700