

# USB Type C Connector System

## SCALABLE, SUPERSPEED CONNECTOR SYSTEM

USB Type C connectors are expected to be widely used as a next-generation interface. They support a variety of protocols such as USB2.0/3.0/3.1 and meet Superspeed communication 10Gb/s, 5A and 20V power supply.

The usability for USB 3.1 Type C connector is enhanced also by its low profile and reversible product design. It is ideal for emerging product designs.

- Reversible plug and cable orientation
- Meets USB 3.1/3.0/2.0 speed performance
- Supports high speed transmission up to 10Gb/s
- Extended 5A current rating for USB Power delivery
- Vertical, right angle and straddle mount configurations and waterproof type available

**NEW**


### TARGET MARKETS



### FEATURES

- Tailored for emerging product designs
- Similar size as Micro USB
- Supports high speed transmission up to 10Gb/s
- Extended 5A current rating for USB Power delivery
- Designed to establish future USB performance needs
- Up to 10,000 mating cycles

### BENEFITS

- Reversible plug and cable orientation for better user experience
- Smaller connector size saves space
- Meets USB 3.1 specification
- Backward compatible with USB 2.0/3.0 to meet different application requirements
- Meets USB power delivery protocol
- Supports audio and video signal output with alternate mode
- Enhanced durability

## TECHNICAL INFORMATION

### MATERIAL

- Housing: High Temperature Polymer, UL94V-0, Black
- Contact: Copper Alloy
- Shell: Stainless Steel

### MECHANICAL PERFORMANCE

- Insertion Force: 5N to 20N
- Extraction Force: 8N to 20N
- Extraction Force (after durability): 6N to 20N
- Durability: 10,000 mating cycles

### ELECTRICAL PERFORMANCE

- Contact Resistance: 40mΩ max. initial for VBUS, GND and all other contacts
- Insulation Resistance: 100mΩ min. initial
- Dielectric Withstanding Voltage: 100V AC

### PACKAGING

- Tray/Tape and Reel available upon request

### SPECIFICATION

- Amphenol Product Specification: USB Type C Series Spec

### APPROVALS AND CERTIFICATIONS

- RoHS

## PART NUMBERS

Product	Description	Part Numbers
USB 3.1 Gen 2 Type C Receptacle	Right angle, Top mount dual SMT, 0.9mm shell tab	12401610E4#2A
USB 3.1 Gen 2 Type C Receptacle	Right angle, Top mount dual SMT, 2.1mm shell tab	12401598E4#2A
USB 3.1 Gen 2 Type C Receptacle	Right angle, Top mount dual SMT, 1.3mm shell tab	12401832E4#2A
USB 3.1 Gen 2 Type C Receptacle	Right angle, Top mount dual SMT, for 1.6mm PCB	12401826E412A
USB 2.0 Type C Receptacle	Right angle, Mid mount SMT	12401834E412A
USB 3.1 Gen 2 Type C Receptacle	Right angle, Mid mount SMT, Short type	124018402112A
USB 3.1 Gen 2 Type C Receptacle	Right angle, Top mount SMT, High-rise type	GSB4C3JXXXHHHR
USB 3.1 Gen 1 Type C Receptacle	Right angle, Mid mount SMT, IPX8 waterproof	1240183121#2A
USB 3.1 Gen 1 Type C Receptacle	Right angle, Top mount Hybrid, Double shells	GSB3CA1X315HHR
USB 3.1 Gen 2 Type C Receptacle	Vertical	12401661E4#2A
USB 3.1 Type C Plug	Straddle mount	GSB3C71X313HHR

### ENVIRONMENTAL

- Humidity: 40±2°C, 90 to 95%(RH), for 96 hours
- Temperature Life: 105±2°C for 120 hours

### TARGET MARKETS/APPLICATIONS



Charger  
Car Media Player/Hub



Telecommunication



Connector Hub  
Flash Disk  
Mobile Phone/Tablet  
VR Camera



Hard Disk Drives  
Solid State Drives



Industrial Computer  
POS System



Medical

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [USB Connectors](#) category:*

*Click to view products by [Amphenol](#) manufacturer:*

Other Similar products are found below :

[65-647-8-BK-BU](#) [950](#) [E8144-B01021-L](#) [A-USB A-LP-SMT-C](#) [A-USB B-TOP-C](#) [MUSBA511N5](#) [MUSBD11135](#) [217450-1](#) [CA 6 W LD](#)  
[KMBVX-TH-5S-B30](#) [896-30-004-00-000000](#) [KUSBVX-BS1N-W30](#) [KUSBX-AP-KIT-SCBLK](#) [KUSBX-AS2N-W](#) [KUSBX-SMT2AP1S-W](#)  
[KUSBX-SMT2AP1S-W30](#) [935](#) [957](#) [30-498-6](#) [17-210051](#) [1734082-1](#) [30-1574](#) [30-470](#) [30-489](#) [30-541](#) [30-572-3](#) [MAB 8 SN V](#) [A-USB A-](#)  
[2P-C](#) [MIKROE-1451](#) [USBFTV2PEM2G](#) [USBFTVC6ZN](#) [KUSBX-AS2N-W30](#) [KUSBX-SLAS1N-W](#) [KUSBX-SMT-AS1N-W30](#) [4689-1](#) [1-](#)  
[1734084-2](#) [E8110-001-01](#) [MUSBA81130](#) [33UBARS1-04SW11](#) [33UBAR-04SW11](#) [USBF21ZNSCC](#) [USBBFTV6ZC](#) [10135326-001LF](#)  
[M9177/3-1](#) [USB-A-S-F-B-VT](#) [925](#) [4198](#) [690-024-633-031](#) [KUSBEX-BSFS1N-W](#) [USBFTVC6MRG](#)